

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number  
**WO 2004/110021 A2**

- (51) International Patent Classification<sup>7</sup>: **H04L 29/06**, 12/64, G06F 3/14
- (21) International Application Number:  
PCT/US2004/017579
- (22) International Filing Date: 2 June 2004 (02.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/475,459 2 June 2003 (02.06.2003) US
- (71) Applicant (for all designated States except US): **QUALCOMM INCORPORATED** [US/US]; 5775 Morehouse Drive, San Diego, CA 92121 (US).
- (72) Inventors; and  
(75) Inventors/Applicants (for US only): **ANDERSON, Jon, James** [US/US]; 7436 Augusta Drive, Boulder, CO 80301 (US). **STEELE, Brian** [US/US]; 1074 Iliad Way, Lafayette, CO 80026 (US). **WILEY, George, A.** [US/US]; 5740 Brittany Forrest Lane, San Diego, CO 92130 (US). **SHEKHAR, Shashank** [IN/US]; 1597 Holeman Drive, Erie, CO 80516 (US).
- (54) Title: **GENERATING AND IMPLEMENTING A SIGNAL PROTOCOL AND INTERFACE FOR HIGHER DATA RATES**
- (74) Agent: **OGROD, Gregory, D.**; 5775 Morehouse Drive, San Diego, CA 92121 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declarations under Rule 4.17:**  
— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]



cond 61 = sub-frame header packet & good CRC at sub-frame boundary  
cond 62 = no sync pattern or bad CRC at sub-frame boundary  
cond 63 = received link shutdown, packet  
cond 64 = found sync pattern  
cond 65 = Unique word received

(57) Abstract: A data Interface for transferring digital data between a host and a client over a communication path using packet structures linked together to form a communication protocol for communicating a pre-selected set of digital control and presentation data. The signal protocol is used by link controllers configured to generate, transmit, and receive packets forming the communications protocol, and to form digital data into one or more types of data packets, with at least one residing in the host device and being coupled to the client through the communications path. The interface provides a cost-effective, low power, bi-directional, high-speed data transfer mechanism over a short-range "serial" type data link, which lends itself to implementation with miniature connectors and thin flexible cables which are especially useful in connecting display elements such as wearable micro-displays to portable computers and wireless communication devices.



CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE,

IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BE, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

**Published:**

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## **GENERATING AND IMPLEMENTING A SIGNAL PROTOCOL AND INTERFACE FOR HIGHER DATA RATES**

### **CROSS-REFERENCE TO RELATED APPLICATIONS**

- [0001] The present Application for Patent claims priority to Provisional Application No. 60/475,459 entitled "Generating and Implementing a Signal Protocol and Interface for Higher Data Rates" filed June 2, 2003, and assigned to the assignee hereof and hereby expressly incorporated by reference herein.

### **BACKGROUND OF THE INVENTION**

#### **I. Field of the Invention**

- [0002] The present invention relates to a digital signal protocol and process for communicating or transferring signals between a host device and a client audio/visual presentation device at high data rates. More specifically, the present invention relates to a technique for transferring multimedia and other types of digital signals from a wireless device to a micro-display unit or other presentation device using a low power high data rate transfer mechanism.

#### **II. Related Art**

- [0003] Computers, electronic game related products, and various video technologies (for example DVD's and High Definition VCRs) have advanced significantly over the last few years to provide for presentation of increasingly higher resolution still, video, video-on-demand, and graphics images, even when including some types of text, to end users of such equipment. These advances in turn mandated the use of higher resolution electronic viewing devices such as high definition video monitors, HDTV monitors, or specialized image projection elements. Combining such visual images with high-definition or -quality audio data, such as when using CD type sound reproduction, DVDs, and other devices also having associated audio signal outputs, is used to create a more realistic, content rich, or true multimedia experience for an end user. In addition, highly mobile, high quality sound systems and music transport mechanisms, such as MP3 players, have been developed for audio only presentations to end users.

[0004] In a typical video presentation scenario, video data is typically transferred using current techniques at a rate that could be best termed as slow or medium, being on the order of one to tens of kilobits per second. This data is then either buffered or stored in transient or longer-term memory devices, for delayed (later) play out on a desired viewing device. For example, images may be transferred "across" or using the Internet using a program resident on a computer having a modem or internet connection device, to receive or transmit data useful in digitally representing an image. A similar transfer can take place using wireless devices such as portable computers equipped with wireless modems, or wireless Personal Data Assistants (PDAs), or wireless telephones.

[0005] Once received, the data is stored locally in memory elements, circuits, or devices, such as RAM or flash memory, including external storage devices, for playback. Depending on the amount of data and the image resolution, the playback might begin relatively quickly, or be presented with longer-term delay. That is, in some instances, image presentation allows for a certain degree of real time playback for very small or low resolution images not requiring much data, or using some type of buffering, so that after a small delay, some material is presented while more material is being transferred. Provided there are no interruptions in the transfer link, once the presentation begins the transfer is reasonably transparent to the end user of the viewing device.

[0006] The data used to create either still images or motion video are often compressed using one of several well known techniques such as those specified by the Joint Photographic Experts Group (JPEG), the Motion Picture Experts Group (MPEG), and other well known standards organizations or companies in the media, computer, and communications industries to speed the transfer of data over a communication link. This allows transferring images or data faster by using a smaller number of bits to transfer a given amount of information.

[0007] Once the data is transferred to a "local" device such as a computer or other recipient device, the resulting information is un-compressed (or played using special decoding players), and decoded if needed, and prepared for appropriate presentation based on the corresponding available presentation resolution and control elements. For example, a typical computer video resolution in terms of a screen resolution of X by Y pixels typically ranges from as low as 480x640 pixels, through 600x800 to 1024x1024, although a variety of other resolutions are generally possible, either as desired or needed.



[0008] Image presentation is also affected by the image content and the ability of given video controllers to manipulate the image in terms of certain predefined color levels or color depth (bits per pixel used to generate colors) and intensities, and any additional overhead bits being employed. For example, a typical computer presentation would anticipate anywhere from around 8 to 32, or more, bits per pixel to represent various colors (shades and hues), although other values are encountered.

[0009] From the above values, one can see that a given screen image is going to require the transfer of anywhere from 2.45 Megabits (Mb) to around 33.55 Mb of data over the range from the lowest to highest typical resolutions and depth, respectively. When viewing video or motion type images at a rate of 30 frames per second, the amount of data required is around 73.7 to 1,006 Megabits of data per second (Mbps), or around 9.21 to 125.75 Megabytes per second (MBps). In addition, one may desire to present audio data in conjunction with images, such as for a multimedia presentation, or as a separate high resolution audio presentation, such as CD quality music. Additional signals dealing with interactive commands, controls, or signals may also be employed. Each of these options adding even more data to be transferred. In any case, when one desires to transfer high quality or high resolution image data and high quality audio information or data signals to an end user to create a content rich experience, a high data transfer rate link is required between presentation elements and the source or host device that is configured to provide such types of data.

[0010] Data rates of around 115 Kilobytes (KBps) or 920 Kilobits per second (Kbps) can be routinely handled by modern serial interfaces. Other interfaces such as USB serial interfaces, can accommodate data transfers at rates as high as 12 MBps, and specialized high speed transfers such as those configured using the Institute of Electrical and Electronics Engineers (IEEE) 1394 standard, can occur at rates on the order of 100 to 400 MBps. Unfortunately, these rates fall short of the desired high data rates discussed above which are contemplated for use with future wireless data devices and services for providing high resolution, content rich, output signals for driving portable video displays or audio devices. In addition, these interfaces require the use of a significant amount of host or system and client software to operate. Their software protocol stacks also create an undesirably large amount of overhead, especially where mobile wireless devices or telephone applications are contemplated. Such devices have severe memory and power consumption limitations, as well as already taxed computational capacity. Furthermore, some of these interfaces utilize bulky cables

which are too heavy and unsatisfactory for highly aesthetic oriented mobile applications, complex connectors which add cost, or simply consume too much power.

[0011] There are other known interfaces such as the Analog Video Graphics Adapter (VGA), Digital Video Interactive (DVI) or Gigabit Video Interface (GVIF) interfaces. The first two of these are parallel type interfaces which process data at higher transfer rates, but also employ heavy cables and consume large amounts of power, on the order of several watts. Neither of these characteristics are amenable to use with portable consumer electronic devices. Even the third interface consumes too much power and uses expensive or bulky connectors.

[0012] For some of the above interfaces, and other very high rate data systems/protocols or transfer mechanisms associated with data transfers for fixed installation computer equipment, there is another major drawback. To accommodate the desired data transfer rates also requires substantial amounts of power and/or operation at high current levels. This greatly reduces the usefulness of such techniques for highly mobile consumer oriented products.

[0013] Generally, to accommodate such data transfer rates using alternatives such as say optical fiber type connections and transfer elements, also requires a number of additional converters and elements that introduce much more complexity and cost, than desired for a truly commercial consumer oriented product. Aside from the generally expensive nature of optical systems as yet, their power requirements and complexity prevents general use for lightweight, low power, portable applications.

[0014] What has been lacking in the industry for portable or mobile applications, is a technique to provide a high quality presentation experience, whether it be audio, video, or multimedia based, for highly mobile end users. That is, when using portable computers, wireless phones, PDAs, or other highly mobile communication devices or equipment, the current video and audio presentation systems or devices being used simply cannot deliver output at the desired high quality level. Often, the perceived quality that is lacking is the result of unobtainable high data rates needed to transfer the high quality presentation data. Therefore, a new transfer mechanism is needed to increase data throughput between host devices providing the data and client display devices or elements presenting an output to end users.

[0015] Applicants have proposed such new transfer mechanisms in US Patent Application Serial Nos. 10/020,520 and 10/236,657, both entitled "Generating And Implementing A Communication Protocol And Interface For High Data Rate Signal

"Transfer", which are assigned to the assignee of the present invention and incorporated herein by reference. The techniques discussed in those applications can greatly improve the transfer rate for large quantities of data in high speed data signals. However, the demands for ever increasing data rates, especially as related to video presentations, continue to grow. Even with other ongoing developments in data signal technology, there is still a need to strive for even faster transfer rates. Therefore, there is a continuing need to develop a new or improved transfer mechanism which is needed to increase data throughput between host and client devices.

### SUMMARY

[0016] The above drawback, and others, existent in the art are addressed by embodiments of the current invention in which a new protocol and data transfer mechanism has been developed for transferring data between a host device and a recipient client device at high data rates.

[0017] Embodiments for the invention are directed to a Mobile Data Digital Interface (MDDI) for transferring digital data at a high rate between a host device and a client device over a communication path which employs a plurality or series of packet structures linked together to form a communication protocol for communicating a pre-selected set of digital control and presentation data between the host and client devices. The signal communications protocol or link layer is used by a physical layer of host or client link controllers. At least one link controller residing in the host device is coupled to the client device through the communications path or link, and is configured to generate, transmit, and receive packets forming the communications protocol, and to form digital presentation data into one or more types of data packets. The interface provides for bi-directional transfer of information between the host and client.

[0018] In further aspects of embodiments of the invention, at least one client link controller, or client receiver, is disposed in the client device and is coupled to the host device through the communications path or link. The client link controller is also configured to generate, transmit, and receive packets forming the communications protocol, and to form digital presentation data into one or more types of data packets. Generally, the host or link controller employs a state machine for processing data packets used in commands or certain types of signal preparation and inquiry processing, but can use a slower general purpose processor to manipulate data and some of the less

complex packets used in the communication protocol. The host controller comprises one or more differential line drivers; while the client receiver comprises one or more differential line receivers coupled to the communication path.

[0019] The packets are grouped together within media frames that are communicated between the host and client devices having a pre-defined fixed length with a pre-determined number of packets having different variable lengths. The packets each comprise a packet length field, one or more packet data fields, and a cyclic redundancy check field. A Sub-frame Header Packet is transferred or positioned at the beginning of transfers of other packets from the host link controller. One or more Video Stream type packets and Audio Stream type packets are used by the communications protocol to transfer video type data and audio type data, respectively, from the host to the client over a forward link for presentation to a client device user. One or more Reverse Link Encapsulation type packets are used by the communications protocol to transfer data from the client device to the host link controller.

[0020] Filler type packets are generated by the host link controller to occupy periods of forward link transmission that do not have data. A plurality of other packets are used by the communications protocol to transfer video information. Such packets include Color Map, Bit Block Transfer, Bitmap Area Fill, Bitmap Pattern Fill, and Transparent Color Enable type packets. User-Defined Stream type packets are used by the communications protocol to transfer interface-user defined data. Keyboard Data and Pointing Device Data type packets are used by the communications protocol to transfer data to or from user input devices associated with said client device. A Link Shutdown type packet is used by the communications protocol to terminate the transfer of data in either direction over said communication path.

[0021] The communication path generally comprises or employs a cable having a series of four or more conductors and a shield. In some embodiments the link controllers comprise a USB data interface and the cable uses a USB type interface along with the other conductors. In addition, printed wires or flexible conductors can be used, as desired.

[0022] The host link controller requests display capabilities information from the client device in order to determine what type of data and data rates said client is capable of accommodating through said interface. The client link controller communicates display or presentation capabilities to the host link controller using at least one Display Capability type packet. Multiple transfer modes are used by the communications

protocol with each allowing the transfer of different maximum numbers of bits of data in parallel over a given time period, with each mode selectable by negotiation between the host and client link controllers. These transfer modes are dynamically adjustable during transfer of data, and the same mode need not be used on the reverse link as is used on the forward link.

[0023] In other aspects of some embodiments of the invention, the host device comprises a wireless communications device, such as a wireless telephone, a wireless PDA, or a portable computer having a wireless modem disposed therein. A typical client device comprises a portable video display such as a micro-display device, and/or a portable audio presentation system. Furthermore, the host may use storage means or elements to store presentation or multimedia data to be transferred to be presented to a client device user.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0024] Further features and advantages of the invention, as well as the structure and operation of various embodiments of the invention, are described in detail below with reference to the accompanying drawings. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements or processing steps, and the drawing in which an element first appears is indicated by the leftmost digit(s) in the reference number.

[0025] FIG. 1A illustrates a basic environment in which embodiments of the invention might operate including the use of a micro-display device used in conjunction with a portable computer.

[0026] FIG. 1B illustrates a basic environment in which embodiments of the invention might operate including the use of a micro-display device and audio presentation elements used in conjunction with a wireless transceiver.

[0027] FIG. 2 illustrates the overall concept of a Mobile Digital Data Interface with a host and client interconnection.

[0028] FIG. 3 illustrates the structure of a packet useful for realizing data transfers from a client device to a host device.

[0029] FIG. 4 illustrates the use of an MDDI link controller and the types of signals passed between a host and a client over the physical data link conductors for Type I and Type U interfaces.

- [0030] FIG. 5 illustrates the use of an MDDI link controller and the types of signals passed between a host and a client over the physical data link conductors for Types II, II, and IV interfaces.
- [0031] FIG. 6 illustrates the structure of frames and sub-frames used to implement the interface protocol.
- [0032] FIG. 7 illustrates the general structure of packets used to implement the interface protocol.
- [0033] FIG. 8 illustrates the format of a Sub-frame Header Packet.
- [0034] FIG. 9 illustrates the format and contents of a Filler Packet.
- [0035] FIG. 10 illustrates the format of a Video Stream Packet.
- [0036] FIG. 11 illustrates the format and contents for the Video Data Format Descriptor of FIG. 10.
- [0037] FIG. 12 illustrates the use of packed and unpacked formats for data.
- [0038] FIG. 13 illustrates the format of an Audio Stream Packet.
- [0039] FIG. 14 illustrates the use of byte-aligned and packed PCM formats for data.
- [0040] FIG. 15 illustrates the format of a User-Defined Stream Packet.
- [0041] FIG. 16 illustrates the format of a Color Map Packet.
- [0042] FIG. 17 illustrates the format of a Reverse Link Encapsulation Packet.
- [0043] FIG. 18 illustrates the format of a Display Capability Packet.
- [0044] FIG. 19 illustrates the format of a Keyboard Data Packet.
- [0045] FIG. 20 illustrates the format of a Pointing Device Data Packet.
- [0046] FIG. 21 illustrates the format of a Link Shutdown Packet.
- [0047] FIG. 22 illustrates the format of a Display Request and Status Packet.
- [0048] FIG. 23 illustrates the format of a Bit Block Transfer Packet.
- [0049] FIG. 24 illustrates the format of a Bitmap Area Fill Packet.
- [0050] FIG. 25 illustrates the format of a Bitmap Pattern Fill Packet.
- [0051] FIG. 26 illustrates the format of a Communication Link Data Channel Packet.
- [0052] FIG. 27 illustrates the format of a Interface Type Handoff Request Packet.
- [0053] FIG. 28 illustrates the format of an Interface Type Acknowledge Packet.
- [0054] FIG. 29 illustrates the format of a Perform Type Handoff Packet.
- [0055] FIG. 30 illustrates the format of a Forward Audio Channel Enable Packet.
- [0056] FIG. 31 illustrates the format of a Reverse Audio Sample Rate Packet.
- [0057] FIG. 32 illustrates the format of a Digital Content Protection Overhead Packet.
- [0058] FIG. 33 illustrates the format of a Transparent Color Enable Packet.

- [0059] FIG. 34 illustrates the format of a Round Trip Delay Measurement Packet.
- [0060] FIG. 35 illustrates the timing of events during the Round Trip Delay Measurement Packet.
- [0061] FIG. 36 illustrates a sample implementation of a CRC generator and checker useful for implementing the invention.
- [0062] FIG. 37A illustrates the timing of CRC signals for the apparatus of FIG. 36 when sending data packets.
- [0063] FIG. 37B illustrates the timing of CRC signals for the apparatus of FIG. 36 when receiving data packets.
- [0064] FIG. 38 illustrates processing steps for a typical service request with no contention.
- [0065] FIG. 39 illustrates processing steps for a typical service request asserted after the link restart sequence has begun, contending with link start.
- [0066] FIG. 40 illustrates how a data sequence can be transmitted using DATA-STB encoding.
- [0067] FIG. 41 illustrates circuitry useful for generating the DATA and STB signals from input data at the host, and then recovering the data at the client.
- [0068] FIG. 42 illustrates drivers and terminating resistors useful for implementing one embodiment.
- [0069] FIG. 43 illustrates steps and signal levels employed by a client to secure service from the host and by the host to provide such service.
- [0070] FIG. 44 illustrates relative spacing between transitions on the Data0, other data lines (DataX), and the strobe lines (Stb).
- [0071] FIG. 45 illustrates the presence of a delay in response that can occur when a host disables the host driver after transferring a packet.
- [0072] FIG. 46 illustrates the presence of a delay in response that can occur when a host enables the host driver to transfer a packet.
- [0073] FIG. 47 illustrates the relationship at the host receiver input between the timing of the data being transferred and the leading and trailing edges of the strobe pulses.
- [0074] FIG. 48 illustrates switching characteristics and corresponding client output delay developed by the reverse data timing.
- [0075] FIG. 49 illustrates a high level diagram of signal processing steps and conditions by which synchronization can be implemented using a state machine.

- [0076] FIG. 50 illustrates typical amounts of delay encountered for signal processing on the forward and reverse paths in a system employing the MDDI.
- [0077] FIG. 51 illustrates marginal round trip delay measurement.
- [0078] FIG. 52 illustrates Reverse Link data rate changes.
- [0079] FIG. 53 illustrates a graphical representation of values of the Reverse Rate Divisor versus forward link data rate.
- [0080] FIGS. 54A and 54B illustrate steps undertaken in the operation of an interface.
- [0081] FIG. 55 illustrates an overview of the interface apparatus processing packets.
- [0082] FIG. 56 illustrates the format of a Forward Link Packet
- [0083] FIG. 57 illustrates typical values for propagation delay and skew in an Type-I Link interface.
- [0084] FIG. 58 illustrates Data, Stb, and Clock Recovery Timing on a Type-I Link for exemplary signal processing through the interface.
- [0085] FIG. 59 illustrates typical values for propagation delay and skew in Type-II, Type-III or Type-IV Link interfaces.
- [0086] FIGS. 60A, 60B, and 60C illustrate different possibilities for the timing of two data signals and MDDI\_Stb with respect to each other, being ideal, early, and late, respectively.
- [0087] FIG. 61 illustrates interface pin assignments exemplary connectors used with a Type-I/Type-II interfaces.
- [0088] FIGS. 62A and 62B illustrate possible MDDI\_Data and MDDI\_Stb waveforms for both Type-I and Type-II Interfaces, respectively.
- [0089] FIG. 63 illustrates a high level diagram of alternative signal processing steps and conditions by which synchronization can be implemented using a state machine.
- [0090] FIG. 64 illustrates exemplary relative timing between a series of clock cycles and the timing of a various reverse link packets bits and divisor values.
- [0091] FIG. 65 illustrates exemplary error code transfer processing.
- [0092] FIG. 66 illustrates apparatus useful for error code transfer processing.
- [0093] FIG. 67A illustrates error code transfer processing for code overloading.
- [0094] FIG. 67B illustrates error code transfer processing for code reception.
- [0095] FIG. 68A illustrates processing steps for a host initiated wake-up.
- [0096] FIG. 68B illustrates processing steps for a client initiated wake-up.
- [0097] FIG. 68C illustrates processing steps for host and client initiated wake-up with contention.



## DETAILED DESCRIPTION OF THE EMBODIMENTS

### I. Overview

[0098] A general intent of the invention is to provide a Mobile Display Digital Interface (MDDI), as discussed below, which results in or provides a cost-effective, low power consumption, transfer mechanism that enables high- or very-high- speed data transfer over a short-range communication link between a host device and a display device using a "serial" type of data link or channel. This mechanism lends itself to implementation with miniature connectors and thin flexible cables which are especially useful in connecting display elements or devices such as wearable micro-displays (goggles or projectors) to portable computers, wireless communication devices, or entertainment devices.

[0099] An advantage of embodiments of the invention is that a technique is provided for data transfer that is low in complexity, low cost, has high reliability, fits well within the environment of use, and is very robust, while remaining very flexible.

[00100] The present invention can be used in a variety of situations to communicate or transfer large quantities of data, generally for audio, video, or multimedia applications from a host or source device where such data is generated or stored, to a client display or presentation device at a high rate. A typical application, which is discussed below, is the transfer of data from either a portable computer or a wireless telephone or modem to a visual display device such as a small video screen or a wearable micro-display appliance, such as in the form of goggles or helmets containing small projection lenses and screens, or from a host to client device within such components. That is, from a processor to an internal screen or other presentation element.

[00101] The characteristics or attributes of the MDDI are such that they are independent of specific display technology. This is a highly flexible mechanism for transferring data at a high rate without regards to the internal structure of that data, nor the functional aspects of the data or commands it implements. This allows the timing of data packets being transferred to be adjusted to adapt to the idiosyncrasies of particular display devices, or unique display desires for certain devices, or to meet the requirements of combined audio and video for some A-V systems. The interface is very display element or client device agnostic, as long as the selected protocol is followed. In addition, the aggregate serial link data or data rate can vary over several orders of magnitude which

allows a communication system or host device designer to optimize the cost, power requirements, client device complexity, and display device update rates.

- [00102] The data interface is presented primarily for use in transferring large amounts of high rate data over a "wired" signal link or small cable. However, some applications may take advantage of a wireless link as well, including optical based links, provided it is configured to use the same packet and data structures developed for the interface protocol, and can sustain the desired level of transfer at low enough power consumption or complexity to remain practical.

## II. Environment

- [00103] A typical application can be seen in FIGS. 1A and 1B where a portable or laptop computer 100 and wireless telephone or PDA device 102 are shown communicating data with display devices 104 and 106, respectively, along with audio reproduction systems 108 and 112. In addition, FIG 1A shows potential connections to a larger display or screen 114 or an image projector 116, which are only shown in one figure for clarity, but are connectable to wireless device 102 as well. The wireless device can be currently receiving data or have previously stored a certain amount of multimedia type data in a memory element or device for later presentation for viewing and/or hearing by an end user of the wireless device. Since a typical wireless device is used for voice and simple text communications most of the time, it has a rather small display screen and simple audio system (speakers) for communicating information to the device 102 user.
- [00104] Computer 100 has a much larger screen, but still inadequate external sound system, and still falls short of other multimedia presentation devices such as a high definition television, or movie screens. Computer 100 is used for purposes of illustration and other types of processors, interactive video games, or consumer electronics devices can also be used with the invention. Computer 100 can employ, but is not limited to or by, a wireless modem or other built in device for wireless communications, or be connected to such devices using a cable or wireless link, as desired.
- [00105] This makes presentation of more complex or "rich" data a less than a useful or enjoyable experience. Therefore, the industry is developing other mechanisms and devices to present the information to end users and provide a minimum level of desired enjoyment or positive experience.

[00106] As previously discussed above, several types of display devices have or are currently being developed for presenting information to end users of device 100. For example, one or more companies have developed sets of wearable goggles that project an image in front of the eyes of a device user to present a visual display. When correctly positioned such devices effectively "project" a virtual image, as perceived by a users eyes, that is much larger than the element providing the visual output. That is, a very small projection element allows the eye(s) of the user to "see" images on a much larger scale than possible with typical LCD screens and the like. The use of larger virtual screen images also allows the use of much higher resolution images than possible with more limited LCD screen displays. Other display devices could include, but are not limited to, small LCD screens or various flat panel display elements, projection lenses and display drivers for projecting images on a surface, and so forth.

[00107] There may also be additional elements connected to or associated with the use of wireless device 102 or computer 100 for presenting an output to another user, or to another device which in turn transfers the signals elsewhere or stores them. For example, data may be stored in flash memory, in optical form, for example using a writeable CD media or on magnetic media such as in a magnetic tape recorder and similar devices, for later use.

[00108] In addition, many wireless devices and computers now have built-in MP3 music decoding capabilities, as well as other advanced sound decoders and systems. Portable computers utilize CD and DVD playback capabilities as a general rule, and some have small dedicated flash memory readers for receiving pre-recorded audio files. The issue with having such capabilities is that digital music files promise a highly increased feature rich experience, but only if the decoding and playback process can keep pace. The same holds true for the digital video files.

[00109] To assist with sound reproduction, external speakers 114 are shown in FIG. 1a, which could also be accompanied by addition elements such as sub-woofers, or "surround-sound" speakers for front and rear sound projection. At the same time, speakers or earphones 108 are indicated as built-in to the support frame or mechanism of micro-display device 106 of FIG. 1b. As would be known, other audio or sound reproduction elements can be used including power amplification or sound shaping devices.

[00110] In any case, as discussed above, when one desires to transfer high quality or high resolution image data and high quality audio information or data signals from a data

source to an end user over one or more communication links 110, a high data rate is required. That is, transfer link 110 is clearly a potential bottleneck in the communication of data as discussed earlier, and is limiting system performance, since current transfer mechanisms do not achieve the high data rates typically desired. As discussed above for example, for higher image resolutions such as 1024 by 1024 pixels, with color depths of 24-32 bits per pixel and at data rates of 30 fps, the data rates can approach rates in excess of 755 Mbps or more. In addition, such images may be presented as part of a multimedia presentation which includes audio data and potentially additional signals dealing with interactive gaming or communications, or various commands, controls, or signals, further increasing the quantity of data and the data rate.

[00111] It is also clear that fewer cables or interconnections required for establishing a data link, means that mobile devices associated with a display are easier to use, and more likely to be adopted by a larger user base. This is especially true where multiple devices are commonly used to establish a full audio-visual experience, and more especially as the quality level of the displays and audio output devices increases.

[00112] Unfortunately, the higher data rates exceed current technology available for transferring data. What is needed is a technique for transferring data at higher rates for the data transfer link or communication path between presentation elements and the data source, which allows for consistently low(er) power, light weight, and as simple and economical a cabling structure as possible. Applicants have developed a new technique, or method and apparatus, to achieve these and other goals to allow an array of mobile, portable, or even fixed location devices to transfer data to desired displays, micro-displays, or audio transfer elements, at very high data rates, while maintaining a desired low power consumption, and complexity.

### **III. High Rate Digital Data Interface System Architecture**

[00113] In order to create and efficiently utilize a new device interface, a signal protocol and system architecture has been formulated that provides a very high data transfer rate using low power signals. The protocol is based on a packet and common frame structure, or structures linked together to form a protocol for communicating a pre-selected set of data or data types along with a command or operational structure imposed on the interface.

### A. Overview

[00114] The devices connected by or communicating over the MDDI link are called the host and client, with the client typically being a display device of some type. Data from the host to the display travels in the forward direction (referred to as forward traffic or link), and data from the display to the host travels in the reverse direction (reverse traffic or link), as enabled by the host. This is illustrated in the basic configuration shown in FIG. 2. In FIG. 2, a host 202 is connected to a client 204 using a bi-directional communication channel 206 which is illustrated as comprising a forward link 208 and a reverse link 210. However, these channels are formed by a common set of conductors whose data transfer is effectively switched between the forward or reverse link operations.

[00115] As discussed elsewhere, the host comprises one of several types of devices that can benefit from using the present invention. For example, host 202 could be a portable computer in the form of a handheld, laptop, or similar mobile computing device, it could be a PDA, a paging device, or one of many wireless telephones or modems. Alternatively, host 202 could be a portable entertainment or presentation device such as a portable DVD or CD player, or a game playing device. At the same time, client 204 could comprise a variety of devices useful for presenting information to an end user. For example, a micro-display incorporated in goggles or glasses, a projection device built into a hat or helmet, a small screen or even holographic element built into a vehicle, such as in a window or windshield, or various speaker, headphone, or sound systems for presenting high quality sound or music. However, those skilled in the art will readily recognize that the present invention is not limited to these devices, there being many other devices on the market, and proposed for use, that are intended to provide end users with high quality images and sound, either in terms of storage and transport or in terms of presentation at playback. The present invention is useful in increasing the data throughput between various devices to accommodate the high data rates needed for realizing the desired user experience.

### B. Interface Types

[00116] The MDD Interface is contemplated as addressing five or more somewhat distinct physical types of interfaces found in the communications and computer industries. These are labeled at this point simply as Type-I, Type-II, Type-III, Type-IV and Type-U.

[00117] The Type-I interface is configured as a 6-wire (conductor) interface which makes it suitable for mobile or wireless telephones, PDAs, e-Books, electronic games, and portable media players, such as CD players, or MP3 players, and devices on similar types of electronic consumer technology. The Type-U interface is configured as an 8-wire (conductor) interface which is more suitable for laptop, notebook, or desktop personal computers and similar devices or applications, that do not require the display to be updated rapidly and do not have a built-in MDDI link controller. This interface type is also distinguishable by the use of an additional two-wire Universal Serial Bus (USB) interface, which is extremely useful in accommodating existing operating systems or software support found on most personal computers. Type-U interfaces can also be used in a USB-only mode where the display simply has a USB connector that connects to a standard USB port on a computer or similar device, for example a consumer electronics device equipped with such a port, such as digital cameras or video players.

[00118] Type-II, Type-III, and Type-IV interfaces are suitable for high performance displays or devices and use larger more complex cabling with additional twisted-pair type conductors to provide the appropriate shielding and low loss transfers for data signals.

[00119] The Type-I interface passes signals which can comprise both the display, audio, control, and limited signaling information, and is typically used for devices that do not require high-resolution full-rate video data. This type of interface is primarily intended for devices, such as mobile wireless devices, where a USB host is typically not available within the device for connection and transfer of signals. In this configuration, the mobile device is a MDDI host device, and acts as the "master" that controls the communication link from the host, which generally sends display data to the client (forward traffic or link).

[00120] In this interface, a host enables receipt of communication data at the host from the client (reverse traffic or link) by sending a special command or packet type to the client that allows it to take over the bus (link) for a specified duration and send data to the host as reverse packets. This is illustrated in FIG. 3, where a type of packet referred to as an encapsulation packet (discussed below) is used to accommodate the transfer of reverse packets over the transfer link, creating the reverse link. The time interval allocated for the host to poll the display for data is pre-determined by the host, and is based on the requirements of each specified application. This type of half-duplex bi-

directional data transfer is especially advantageous where a USB port is not available for transfer of information or data from the client.

[00121] The Type-U interface transfers signals which are well suited for use in laptop and desktop applications where a USB interface is widely supported by extensive amounts of motherboards or other hardware, and by operating system software. The use of an added USB interface allows use with "plug-and-play" features and easy application configuration. The inclusion of USB also allows general-purpose bi-directional flow of commands, status, audio data, and so forth while video and audio data intended for the client device can be transferred using the twisted pairs at low power and high speed. Power can be transferred using other wires, as discussed below. Embodiments of the invention using a USB interface allow high speed transfers over one set of conductors while implementing mainly signaling and control through the USB connection, which can be shut down when not in use and consumes little power.

[00122] The USB interface is a very extensively used standard for modern personal computer equipment, and the details of a USB interface and its operation are very well known in the art, so not explained here. For the USB interface, communication between the host and display are compliant with the Universal Serial Bus Specification, Revision 2.0. In applications using the Type-U interface where USB is the primary signaling channel and possibly a voice return channel, it is optional for the host to poll the client through the MDDI serial data signals.

[00123] High-performance displays capable of HDTV type or similar high resolutions require around 1.5 Gbps rate data streams in order to support full-motion video. The Type-II interface supports high data rates by transmitting 2 bits in parallel, the Type-III by transmitting 4 bits in parallel, and the Type-IV interface transfers 8 bits in parallel. The protocol used by the MDDI allows each Type-I, -II, -III, or -IV host to generally communicate with any Type-I, -II, -III, or -IV client or display by negotiating what is the highest data rate possible that can be used. The capabilities or available features of what can be referred to as the least capable device is used to set the performance of the link. As a rule, even for systems where the host and client are both capable using Type-II, Type-III, or Type-IV interfaces, both begin operation as a Type-I interface. The host then determines the capability of the target client or display, and negotiates a hand-off or reconfiguration operation to either Type-II, Type-III, or Type-IV mode, as appropriate for the particular application.

[00124] It is generally possible for the host to use the proper link-layer protocol (discussed further below) and at any time to step down or again reconfigure operation to a slower mode to save power or to step up to a faster mode to support higher speed transfers, such as for higher resolution display content. For example, a host may change display modes when the display system switches from a power source such as a battery to AC power, or when the source of the display media switches to a lower or higher resolution format, or a combination of these or other conditions or events may be considered as a basis for changing a display or data transfer mode.

[00125] It is also possible for a system to communicate data using one mode in one direction and another mode in another direction. For example, a Type IV interface mode could be used to transfer data to a display at a high rate, while a Type I or Type U mode is used when transferring data to a host device from peripheral devices such as a keyboard or a pointing device.

### **C. Physical Interface Structure**

[00126] The general disposition of a device or link controller for establishing communications between host and client devices is shown in FIGS. 4 and 5. In FIG. 4 and 5, a MDDI link controller 402 and 502 is shown installed in a host device 202 and a MDDI link controller 404 and 504 is shown installed in a client device 204. As before, host 202 is connected to a client 204 using a bi-directional communication channel 406 comprising a series of conductors. As discussed below, both the host and client link controllers can be manufactured as an integrated circuit using a single circuit design that can be set, adjusted or programmed to respond as either a host controller (driver) or a client controller (receiver). This provides for lower costs due to larger scale manufacturing of a single circuit device.

[00127] In FIG. 4, a USB host device 408 and a USB client device 410 are also shown for use in implementing Type U interface versions of the MDDI. Circuits and devices for implementing such functions are well known in the art, and are not described in further detail herein.

[00128] In FIG. 5, a MDDI link controller 502 is shown installed in a host device 202' and a MDDI link controller 504 is shown installed in a client device 204'. As before, host 202' is connected to a client 204' using a bi-directional communication channel 506 comprising a series of conductors. As discussed before, both the host and client link controllers can be manufactured using a single circuit design.



[00129] Signals passed between a host and a client, such as a display device, over the MDDI link, or the physical conductors used, are also illustrated in FIGS. 4 and 5. As seen in FIGS. 4 and 5, the primary path or mechanism for transferring data through the MDDI uses data signals labeled as MDDI\_Data0+/- and MDDI\_Stb+/- . Each of these are low voltage data signals that are transferred over a differential pair of wires in a cable. There is only one transition on either the MDDI\_Data0 pair or the MDDI\_Stb pair for each bit sent over the interface. This is a voltage based transfer mechanism not current based, so static current consumption is near zero. The host drives the MDDI\_Stb signals to the client display.

[00130] While data can flow in both the forward and reverse directions over the MDDI\_Data pairs, that is, it is a bi-directional transfer path, the host is the master or controller of the data link. The MDDI\_Data0 and MDDI\_Stb signal paths are operated in a differential mode to maximize noise immunity. The data rate for signals on these lines is determined by the rate of the clock sent by the host, and is variable over a range of about 1 kbps up to 400 Mbps or more.

[00131] The Type-II interface contains one additional data pair or conductors or paths beyond that of the Type-I, referred to as MDDI\_Data1+/- . The Type-III interface contains two additional data pairs or signal paths beyond that of the Type-II interface referred to as MDDI\_Data2+/- , and MDDI\_Data3+/- . The Type-IV interface contains four more data pairs or signal paths beyond that of the Type-III interface referred to as: MDDI\_data4+/- , MDDI\_Data5+/- , MDDI\_Data6+/- , and MDDI\_Data7+/- , respectively. In each of the above interface configurations, a host can send power to the client or display using the wire-pair or signals designated as MDDI\_Pwr and MDDI\_Gnd.

[00132] A type of transfer generally only made available for the Type-U configuration is the MDDI USB connection or signal path. The MDDI USB connection comprises a secondary path for communication between a host and a client display. In certain applications it may be more advantageous to send certain information at a relatively low data rate between a host and client. Using the USB transfer link allows devices without an MDDI Link Controller that have a USB host or limited host capability to communicate with an MDDI-compatible client or display equipped with the Type-U interface. Examples of information that can be usefully transferred over a USB interface to a display are: static bitmaps, digital audio streams, pointing device data, keyboard data, and control and status information. Functionality supported through the

USB interface can also be implemented using the primary MDDI high-speed serial data path. While the data (see packets below) defined above may be sent over a USB type interface, the requirements for chaining data in the form of packets back-to-back do not apply to such a USB interface, neither does use of packets supporting MDDI Type handoff.

[00133] A summary of the signals passed between the host and client (display) over the MDDI link are illustrated in Table I, below, in accordance with the interface type.

[00134] **Table I**

<u>Type-I</u>	<u>Type-II</u>	<u>Type-III</u>	<u>Type-IV</u>
MDDI_Pwr/Gnd	MDDI_Pwr/Gnd	MDDI_Pwr/Gnd	MDDI_Pwr/Gnd
MDDI_Stb+/-	MDDI_Stb+/-	MDDI_Stb+/-	MDDI_Stb+/-
MDDI_Data0+/-	MDDI_Data0+/-	MDDI_Data0+/-	MDDI_Data0+/-
	MDDI_Data1+/-	MDDI_Data1+/-	MDDI_Data1+/-
		MDDI_Data2+/-	MDDI_Data2+/-
		MDDI_Data3+/-	MDDI_Data3+/-
<u>Type-U</u>			
MDDI_Pwr/Gnd			MDDI_Data4+/-
MDDI_Stb+/-			MDDI_Data5+/-
MDDI_Data0+/-			MDDI_Data6+/-
MDDI_USB+/-			MDDI_Data7+/-

[00135] Cabling generally used to implement the above structure and operation is nominally on the order of 1.5 meters in length and contains three twisted pairs of conductors, each in turn being multi-strand 30 AWG wire. A foil shield covering is wrapped or otherwise formed above the three twisted pairs, as an additional drain wire. The twisted pairs and shield drain conductor terminate in the display connector with the shield connected to the shield for the display (client), and there is an insulating layer, covering the entire cable, as would be well known in the art. The wires are paired as: MDDI\_Gnd with MDDI\_Pwr; MDDI\_Stb+ with MDDI\_Stb-; MDDI\_Data0+ with MDDI\_Data0-; MDDI\_Data1+ with MDDI\_Data1-; and so forth. The nominal cable diameter is on the order of 3.0 mm with a nominal impedance of 85 ohms  $\pm 10\%$ , and DC resistance nominally of 110 ohms per 1000 feet. The signal propagation velocity

should be nominally 0.66c, with a maximum delay through the cable less than around 8.0 nsec.

#### D. Data Types and Rates

[00136] To achieve a useful interface for a full range of user experiences and applications, the Mobile Digital Data Interface (MDDI) provides support for a variety of displays and display information, audio transducers, keyboards, pointing devices, and many other input devices that might be integrated into or working in concert with a mobile display device, along with control information, and combinations thereof. The MDD interface is designed to be able to accommodate a variety of potential types of streams of data traversing between the host and client in either the forward or reverse link directions using a minimum number of cables or conductors. Both isochronous streams and asynchronous stream (updates) are supported. Many combinations of data types are possible as long as the aggregate data rate is less than or equal to the maximum desired MDDI link rate. These could include, but are not limited to those items listed in Tables II and III below.

[00137] **Table II**

Transferring from Host to Client		
isochronous video data	720x480, 12bit, 30f/s	~124.5 Mbps
isochronous stereo audio data	44.1kHz, 16bit, stereo	~ 1.4 Mbps
asynchronous graphics data	800x600, 12bit, 10f/s, stereo	~115.2 Mbps
asynchronous control	minimum	<< 1.0 Mbps

[00138] **Table III**

Transferring from Client to Host		
isochronous voice data	8 kHz, 8bit	<< 1.0 Mbps
isochronous video data	640x480, 12bit, 24f/s	~ 88.5 Mbps
asynchronous status, user input, etc.	minimum	<< 1.0 Mbps

[00139] The interface is not fixed but extensible so that it can support the transfer of a variety of information "types" which includes user-defined data, for future system flexibility. Specific examples of data to be accommodated are: full-motion video, either in the form of full or partial screen bitmap fields or compressed video; static bitmaps at

low rates to conserve power and reduce implementation costs; PCM or compressed audio data at a variety of resolutions or rates; pointing device position and selection, and user-definable data for capabilities yet to be defined. Such data may also be transferred along with control or status information to detect device capability or set operating parameters.

[00140] The present invention advances the art for use in data transfers that include, but are not limited to, watching a movie (video display and audio), using a personal computer with limited personal viewing (graphics display, sometimes combined with video and audio), playing a video game on a PC, console, or personal device (motion graphics display, or synthetic video and audio), "surfing" the Internet, using devices in the form of a video phone (bi-directional low-rate video and audio), a camera for still digital pictures, or a camcorder for capturing digital video images, and for productivity enhancement or entertainment use with cell phones, smart phones, or PDAs.

[00141] The mobile data interface as discussed below is presented in terms of providing large amounts of A-V type data over a communication or transfer link which is generally configured as a wire-line or cable type link. However, it will be readily apparent that the signal structure, protocols, timing, or transfer mechanism could be adjusted to provide a link in the form of an optical or wireless media, if it can sustain the desired level of data transfer.

[00142] The MDD interface signals use a concept known as the Common Frame (CF) for the basic signal protocol or structure. The idea behind using of a Common Frame is to provide a synchronization pulse for simultaneous isochronous data streams. A display device can use this common frame rate as a time reference. A low CF rate increases channel efficiency by decreasing overhead to transmit the sub-frame header. On the other hand, a high CF rate decreases the latency, and allows a smaller elastic data buffer for audio samples. The CF rate of the present inventive interface is dynamically programmable and may be set at one of many values that are appropriate for the isochronous streams used in a particular application. That is, the CF value is selected to best suit the given display device and host configuration, as desired.

[00143] The number of bytes generally required per common frame, which is adjustable or programmable, for isochronous data streams that are most likely to be used with an application, such as for a head-mounted micro-display are shown in Table IV.

[00144] Table IV

Common Frame Rate (CFR) = 1200 Hz							
	X	Y	Bit	Frame Rate	Channel	Rate (Mbps)	Byte/ CFR
DVD Movie	720	480	12	30	1	124.4	12960
Stereo Graphics	800	600	12	10	2	115.2	12000
Camcorder	640	480	12	24	1	88.5	9216
CD Audio	1	1	16	44100	2	1.4	147
Voice	1	1	8	8000	1	0.1	6.7

[00145] Fractional counts of bytes per common frame are easily obtained using a simple programmable M/N counter structure. For example, a count of  $26\frac{2}{3}$  bytes per CF is implemented by transferring 2 frames of 27 bytes each followed by one frame of 26 bytes. A smaller CF rate may be selected to produce an integer number of bytes per CF. However, generally speaking, to implement a simple M/N counter in hardware should require less area within an integrated circuit chip or electronic module used to implement part or all of the invention than the area needed for a larger audio sample FIFO buffer.

[00146] An exemplary application that illustrates the impact of different data transfer rates and data types is a Karaoke system. For Karaoke, a system user sings along with a music video program. Lyrics of the song are displayed at the bottom of a screen so the user knows the words to be sung, and roughly the timing of the song. This application requires a video display with infrequent graphics updates, and mixing of the user's voice with a stereo audio stream.

[00147] If one assumes a common frame rate of 300 Hz, then each CF will consist of: 92,160 bytes of video content and 588 bytes of audio content (based on 147 16-bit samples, in stereo) over the forward link to the display device, and an average of 29.67 ( $26\frac{2}{3}$ ) bytes of voice are sent back from a microphone to the mobile Karaoke machine. Asynchronous packets are sent between the host and the display. This includes at most 768 bytes of graphics data (quarter-screen height), and less than about 200 bytes (several) bytes for miscellaneous control and status commands.

[00148] Table V, shows how data is allocated within a Common Frame for the Karaoke example. The total rate being used is selected to be about 225 Mbps. A slightly higher rate of 226 Mbps allows about another 400 bytes of data per sub-frame to be transferred which allows the use of occasional control and status messages.

[00149] **Table V**

Element Rate	Bytes/CF
Music Video at 640 x 480 pixels and 30 fps	92160
Lyric Text at 640 x 120 pixels and 1 fps	768
CD Audio at 44,100 sps, stereo, 16-bit	588
Voice at 8,000 sps, mono, 8-bit	26.67
Sub-frame Header	19
Reverse Link Overhead	$26.67 + 2 \times 9 + 20$
Total Bytes/CF	93626.33
Total Rate (Mbps)	224.7032

### III. High Rate Digital Data Interface System Architecture

#### E. Link Layer

[00150] Data transferred using the MDD interface high-speed serial data signals consists of a stream of time-multiplexed packets that are linked one after the other. Even when a transmitting device has no data to send, a MDDI link controller generally automatically sends filler packets, thus, maintaining a stream of packets. The use of a simple packet structure ensures reliable isochronous timing for video and audio signals or data streams.

[00151] Groups of packets are contained within signal elements or structures referred to as sub-frames, and groups of sub-frames are contained within signal elements or structures referred to as a media-frame. A sub-frame contains one or more packets, depending on their respective size and data transfer uses, and a media-frame contains one more sub-frames. The largest sub-frame provided by the protocol employed by the present invention is on the order of 232-1 or 4,294,967,295 bytes, and the largest media-frame size then becomes on the order of 216-1 or 65,535 sub-frames.

[00152] A special header packet contains a unique identifier that appears at the beginning of each sub-frame, as is discussed below. That identifier is also used for acquiring the frame timing at the client device when communication between the host and client is initiated. Link timing acquisition is discussed in more detail below.

[00153] Typically, a display screen is updated once per media-frame when full-motion video is being displayed. The display frame rate is the same as the media-frame rate. The link protocol supports full-motion video over an entire display, or just a small region of full-motion video content surrounded by a static image, depending on the desired application. In some low-power mobile applications, such as viewing web

pages or email, the display screen may only need to be updated occasionally. In those situations, it is advantageous to transmit a single sub-frame and then shut down or inactivate the link to minimize power consumption. The interface also supports effects such as stereo vision, and handles graphics primitives.

[00154] Sub-frames exist to enable the transmission of high-priority packets on a periodic basis. This allows simultaneous isochronous streams to co-exist with a minimal amount of data buffering. This is one advantage the present invention provides to the display process, allowing multiple data streams (high speed communication of video, voice, control, status, pointing device data, etc.) to essentially share a common channel. It transfers information using relatively few signals. It also enables display-technology-specific actions to exist, such as horizontal sync pulses and blanking intervals for a CRT monitor.

#### **F. Link Controller**

[00155] The MDDI link controller shown in FIGS. 4 and 5 is manufactured or assembled to be a completely digital implementation with the exception of the differential line receivers which are used to receive MDDI data and strobe signals. However, even the differential line drivers and receivers can be implemented in the same digital integrated circuits with the link controller. No analog functions or phase lock loops (PLLs) are required to implement the hardware for the link controller. The host and client link controllers contain very similar functions, with the exception of the display interface which contains a state machine for link synchronization. Therefore, the present invention allows the practical advantage of being able to create a single controller design or circuit that can be configured as either a host or client, which can reduce manufacturing costs for the link controllers, as a whole.

### **IV. Interface Link Protocol**

#### **A. Frame structure**

[00156] The signal protocol or frame structure used to implement the forward link communication for packet transfer is illustrated in FIG. 6. As shown in FIG. 6, information or digital data is grouped into elements known as packets. Multiple packets are in turn grouped together to form what are referred to as a "sub-frame," and multiple sub-frames are in turn grouped together to form a "media" frame. To control the

formation of frames and transfer of sub-frames, each sub-frame begins with a specially predefined packet referred to as a Sub-frame Header Packet (SHP).

[00157] The host device selects the data rate to be used for a given transfer. This rate can be changed dynamically by the host device based on both the maximum transfer capability of the host, or the data being retrieved from a source by the host, and the maximum capability of the display, or other device the data is being transferred to.

[00158] A recipient client device designed for, or capable of, working with the MDDI or inventive signal protocol is able to be queried by the host to determine the maximum, or current maximum, data transfer rate it can use, or a default slower minimum rate may be used, as well as useable data types and features supported. This information could be transferred using a Display Capability Packet (DCP), as discussed further below. The client display device is capable of transferring data or communicating with other devices using the interface at a pre-selected minimum data rate or within a minimum data rate range, and the host will perform a query using a data rate within this range to determine the full capabilities of the client devices.

[00159] Other status information defining the nature of the bitmap and video frame-rate capabilities of the display can be transferred in a status packet to the host so that the host can configure the interface to be as efficient or optimal as practical, or desired within any system constraints.

[00160] The host sends filler packets when there are no (more) data packets to be transferred in the present sub-frame, or when the host cannot transfer at a rate sufficient to keep pace with the data transmission rate chosen for the forward link. Since each sub-frame begins with a sub-frame header packet, the end of the previous sub-frame contains a packet (most likely a filler packet) that exactly fills the previous sub-frame. In the case of a lack of room for data bearing packets per se, a filler packet will most likely be the last packet in a sub-frame, or at the end of a next previous sub-frame and before a sub-frame header packet. It is the task of the control operations in a host device to ensure that there is sufficient space remaining in a sub-frame for each packet to be transmitted within that sub-frame. At the same time, once a host device initiates the sending of a data packet, the host must be able to successfully complete a packet of that size within a frame without incurring a data under-run condition.

[00161] In one aspect of embodiments, sub-frame transmission has two modes. One mode is a periodic sub-frame mode used to transmit live video and audio streams. In this mode, the Sub-frame length is defined as being non-zero. The second mode is an



asynchronous or non-periodic mode in which frames are used to provide bitmap data to a display device only when new information is available. This mode is defined by setting the sub-frame length to zero in the Sub-frame Header Packet. When using the periodic mode, sub-frame packet reception may commence when the display has synchronized to the forward link frame structure. This corresponds to the "in sync" states defined according to the state diagram discussed below with respect to FIG. 49 or FIG. 63. In the asynchronous non-periodic sub-frame mode, reception commences after the first Sub-frame Header packet is received.

#### B. Overall Packet Structure

[00162] The format or structure of packets used to formulate the signaling protocol implemented by the present invention are presented below, keeping in mind that the interface is extensible and additional packet structures can be added as desired. The packets are labeled as, or divided into, different "packet types" in terms of their function in the interface, that is, commands or data they transfer. Therefore, each packet type denotes a pre-defined packet structure for a given packet which is used in manipulating the packets and data being transferred. As will be readily apparent, the packets may have pre-selected lengths or have variable or dynamically changeable lengths depending on their respective functions. The packets could also bear differing names, although the same function is still realized, as can occur when protocols are changed during acceptance into a standard. The bytes or byte values used in the various packets are configured as multi-bit (8- or 16-bit) unsigned integers. A summary of the packets being employed along with their "type" designations, listed in type order, is shown in Table VI. The direction in which transfer of a packet is considered valid is also noted, along with whether or not they are used for a Type-U interface.

[00163] **Table VI**

Packet Name	Packet Type	Valid in Direction		
		Forward	Reverse	Type-U
Sub-frame Header Packet	255	x		x
Filler Packet	0	x	x	
Video Stream Packet	1	x	x	x
Audio Stream Packet	2	x	x	x
Reserved Stream Packets	3 - 55			
User-Defined Stream Packets	56 - 63	x	x	x

Color Map Packet	64	x	x	x
Reverse Link Encapsulation Packet	65	x		
Display Capability Packet	66		x	x
Keyboard Data Packet	67	x	x	x
Packet Name	Packet Type	Valid in Direction		
		Forward	Reverse	Type-U
Pointing Device Data Packet	68	x	x	x
Link Shutdown Packet	69	x		
Display Request and Status Packet	70		x	x
Bit Block Transfer Packet	71	x		x
Bitmap Area Fill Packet	72	x		x
Bitmap Pattern Fill Packet	73	x		x
Communication Link Data Channel Packet	74	x	x	x
Interface Type Handoff Request Packet	75	x		
Interface Type Acknowledge Packet	76		x	
Perform Type Handoff Packet	77	x		
Forward Audio Channel Enable Packet	78	x		x
Reverse Audio Sample Rate Packet	79	x		x
Digital Content Protection Overhead Packet	80	x	x	x
Transparent Color Enable Packet	81	x		x
Round Trip Delay Measurement Packet	82	x		
Forward Link Skew Calibration Packet	83	x		

[00164] Packets have a common basic structure or overall set of minimum fields comprising a Packet Length field, a Packet Type field, Data Bytes field(s), and a CRC field, which is illustrated in FIG. 7. As shown in FIG. 7, the Packet Length field contains information, in the form of a multi-bit or -byte value, that specifies the total number of bits in the packet, or its length between the packet length field and the CRC field. In one embodiment, the packet length field contains a 16-bit or 2-byte wide, unsigned integer, that specifies the packet length. The Packet Type field is another multi-bit field which designates the type of information that is contained within the packet. In an exemplary embodiment, this is an 8-bit or 1-byte wide value, in the form of an 8-bit unsigned integer, and specifies such data types as display capabilities, handoff, video or audio streams, status, and so forth.

[00165] A third field is the Data Bytes field, which contains the bits or data being transferred or sent between the host and client devices as part of that packet. The format of the data is defined specifically for each packet type according to the specific type of data being transferred, and may be separated into a series of additional fields, each with its own format requirements. That is, each packet type will have a defined

format for this portion or field. The last field is the CRC field which contains the results of a 16-bit cyclic redundancy check calculated over the Data Bytes, Packet Type, and Packet Length fields, which is used to confirm the integrity of the information in the packet. In other words, calculated over the entire packet except for the CRC field itself. The client generally keeps a total count of the CRC errors detected, and reports this count back to the host in the Display Request and Status Packet (see further below).

[00166] During transfer of the packets, fields are transmitted starting with the Least Significant Bit (LSB) first and ending with the Most Significant Bit (MSB) transmitted last. Parameters that are more than one byte in length are transmitted using the least significant byte first, which results in the same bit transmission pattern being used for a parameter greater than 8 bits in length, as is used for a shorter parameter where the LSB is transmitted first. The data on the MDDI\_Data0 signal path is aligned with bit '0' of bytes transmitted on the interface in any of the modes, Type-I, Type-II, Type-III, or Type-IV.

[00167] When manipulating data for displays, the data for arrays of pixels are transmitted by rows first, then columns, as is traditionally done in the electronics arts. In other words, all pixels that appear in the same row in a bit map are transmitted in order with the left-most pixel transmitted first and the right-most pixel transmitted last. After the right-most pixel of a row is transmitted then the next pixel in the sequence is the left-most pixel of the following row. Rows of pixels are generally transmitted in order from top to bottom for most displays, although other configurations can be accommodated as needed. Furthermore, in handling bitmaps, the conventional approach, which is followed here, is to define a reference point by labeling the upper-left corner of a bitmap as location or offset "0,0." The X and Y coordinates used to define or determine a position in the bitmap increase in value as one approaches the right and bottom of the bitmap, respectively. The first row and first column start with an index value of zero.

### C. Packet Definitions

#### 1. Sub-frame Header Packet

[00168] The sub-frame header packet is the first packet of every sub-frame, and has a basic structure as illustrated in FIG. 8. As can be seen in FIG. 8, this type of packet is structured to have Packet Length, Packet Type, Unique Word, Sub-Frame Length,

Protocol Version, Sub-Frame Count, and Media-frame Count fields, generally in that order. This type of packet is generally identified as a Type 255 (0xff hexadecimal) packet and uses a pre-selected fixed length of 17 bytes.

[00169] While the Packet Type field uses a 1 byte value, the Unique Word field uses a 3 byte value. The 4-byte combination of these two fields together forms a 32-bit unique word with good autocorrelation. In an exemplary embodiment, the actual unique word is 0x005a3bff where the lower 8 bits are transmitted first as the Packet Type, and the most significant 24 bits are transmitted afterward.

[00170] The Sub-frame Length field contains 4 bytes of information that specifies the number of bytes per sub-frame. The length of this field may be set equal to zero to indicate that only one sub-frame will be transmitted by the host before the link is shut down into an idle state. The value in this field can be dynamically changed "on-the-fly" when transitioning from one sub-frame to the next. This capability is useful in order to make minor timing adjustments in the sync pulses for accommodating isochronous data streams. If the CRC of the Sub-frame Header packet is not valid then the link controller should use the Sub-frame Length of the previous known-good Sub-frame Header packet to estimate the length of the current sub-frame.

[00171] The Protocol Version field contains 2 bytes that specify the protocol version used by the host. The Protocol Version field is set to '0' to specify the first or current version of the protocol as being used. This value will change over time as new versions are created. The Sub-frame Count field contains 2 bytes that specify a sequence number that indicates the number of sub-frames that have been transmitted since the beginning of the media-frame. The first sub-frame of the media-frame has a Sub-frame Count of zero. The last sub-frame of the media-frame has a value of  $n-1$ , where  $n$  is the number of sub-frames per media-frame. Note that if the Sub-frame Length is set equal to zero (indicating a non-periodic sub-frame) then the Sub-frame count must also be set equal to zero.

[00172] The Media-frame Count field contains 3 bytes that specify a sequence number that indicates the number of media-frames that have been transmitted since the beginning of the present media item or data being transferred. The first media-frame of a media item has a Media-frame Count of zero. The Media-frame Count increments just prior to the first sub-frame of each media-frame and wraps back to zero after the maximum Media-frame Count (for example, media-frame number  $224-1 = 16,777,215$ )

is used. The Media-frame Count value may be reset generally at any time by the Host to suit the needs of an end application.

## 2. Filler Packet

[00173] A filler packet is a packet that is transferred to, or from, a client device when no other information is available to be sent on either the forward or reverse link. It is recommended that filler packets have a minimum length in order to allow maximum flexibility in sending other packets when required. At the very end of a sub-frame or a reverse link encapsulation packet (see below), a link controller sets the size of the filler packet to fill the remaining space to maintain packet integrity.

[00174] The format and contents of a Filler Packet are shown in FIG. 9. As shown in FIG. 9, this type of packet is structured to have Packet Length, Packet Type, Filler Bytes, and CRC fields. This type of packet is generally identified as a Type 0, which is indicated in the 1 byte type field. The bits or bytes in the Filler Bytes field comprise a variable number of all zero bit values to allow the filler packet to be the desired length. The smallest filler packet contains no bytes in this field. That is, the packet consists of only the packet length, packet type, and CRC, and uses a pre-selected fixed length of 3 bytes.

## 3. Video Stream Packet

[00175] Video Stream Packets carry video data to update typically rectangular regions of a display device. The size of this region may be as small as a single pixel or as large as the entire display. There may be an almost unlimited number of streams displayed simultaneously, limited by system resources, because all context required to display a stream is contained within the Video Stream Packet. The format of the video stream packet (Video Data Format Descriptor) is shown in FIG. 10. As seen in FIG. 10, this type of packet is structured to have Packet Length (2 bytes), Packet Type, Video Data Descriptor, Display Attributes, X Left Edge, Y Top Edge, X Right Edge, Y Bottom Edge, X and Y Start, Pixel Count, Parameter CRC, Pixel Data, and CRC fields. This type of packet is generally identified as a Type 1, which is indicated in the 1 byte type field.

[00176] The common frame concept discussed above is an effective way to minimize the audio buffer size and decrease latency. However, for video data it may be necessary to spread the pixels of one video frame across multiple Video Stream Packets within a

media-frame. It is also very likely that the pixels in a single Video Stream Packet will not exactly correspond to a perfect rectangular window on the display. For the exemplary video frame rate of 30 frames per second, there are 300 sub-frames per second, which results in 10 sub-frames per media-frame. If there are 480 rows of pixels in each frame, each Video Stream Packet in each sub-frame will contain 48 rows of pixels. In other situations, the Video Stream Packet might not contain an integer number of rows of pixels. This is true for other video frame sizes where the number of sub-frames per media-frame does not divide evenly into the number of rows (also known as video lines) per video frame. Each Video Stream Packet generally must contain an integer number of pixels, even though it might not contain an integer number of rows of pixels. This is important if pixels are more than one byte each, or if they are in a packed format as shown in FIG. 12.

[00177] The format and contents employed for realizing the operation of an exemplary Video Data Descriptor field, as mentioned above, are shown in FIGS. 11a-11d. In FIGS. 11a-11d, the Video Data Format Descriptor field contains 2 bytes in the form of a 16-bit unsigned integer that specifies the format of each pixel in the Pixel Data in the present stream in the present packet. It is possible that different Video Stream packets may use different pixel data formats, that is, use a different value in the Video Data Format Descriptor, and similarly, a stream (region of the display) may change its data format on-the-fly. The Video Data Format Descriptor defines the pixel format for the present packet only which does not imply that a constant format will continue to be used for the lifetime of a particular video stream.

[00178] FIGS. 11a through 11d illustrate how the Video Data Format Descriptor is coded. As used in these figures, and in this embodiment, when bits [15:13] are equal to '000', as shown in FIG. 11a, then the video data consists of an array of monochrome pixels where the number of bits per pixel is defined by bits 3 through 0 of the Video Data Format Descriptor word. Bits 11 through 4 are set to zero in this situation. When bits [15:13] are instead equal to '001', as shown in FIG. 11b, then the video data consists of an array of color pixels that each specify a color through a color map. In this situation, bits 5 through 0 of the Video Data Format Descriptor word define the number of bits per pixel, and bits 11 through 6 are set equal to zero. When bits [15:13] are instead equal to '010', as shown in FIG. 11c, then the video data consists of an array of color pixels where the number of bits per pixel of red is defined by bits 11 through 8, the number of bits per pixel of green is defined by bits 7 through 4, and the number of

bits per pixel of blue is defined by bits 3 through 0. In this situation, the total number of bits in each pixel is the sum of the number of bits used for red, green, and blue.

[00179] However, when bits [15:13] are instead equal to '011', as shown in FIG. 11d, then the video data consists of an array of video data in 4:2:2 format with luminance and chrominance information, where the number of bits per pixel of luminance (Y) is defined by bits 11 through 8, the number of bits of the Cr component is defined by bits 7 through 4, and the number of bits of the Cb component is defined by bits 3 through 0. The total number of bits in each pixel is the sum of the number of bits used for red, green, and blue. The Cr and Cb components are sent at half the rate as Y. In addition, the video samples in the Pixel Data portion of this packet are organized as follows: Y<sub>n</sub>, Cr<sub>n</sub>, Cb<sub>n</sub>, Y<sub>n+1</sub>, Y<sub>n+2</sub>, Cr<sub>n+2</sub>, Cb<sub>n+2</sub>, Y<sub>n+3</sub>, ... where Cr<sub>n</sub> and Cb<sub>n</sub> are associated with Y<sub>n</sub> and Y<sub>n+1</sub>, and Cr<sub>n+2</sub> and Cb<sub>n+2</sub> are associated with Y<sub>n+2</sub> and Y<sub>n+3</sub>, and so on. If there are an odd number of pixels in a row (X Right Edge – X Left Edge + 1) in the present stream, then the Cb value corresponding to the last pixel in each row will be followed by the Y value of the first pixel of the next row.

[00180] For all four formats shown in the figures, bit 12, which is designated as "P", specifies whether or not the Pixel Data samples are packed, or byte-aligned pixel data. A value of '0' in this field indicates that each pixel and each color within each pixel in the Pixel Data field is byte-aligned with an MDD interface byte boundary. A value of '1' indicates that each pixel and each color within each pixel in the Pixel Data is packed up against the previous pixel or color within a pixel leaving no unused bits.

[00181] The first pixel in the first video stream packet of a media frame for a particular display window will go into the upper left corner of the stream window defined by an X Left Edge and a Y Top Edge, and the next pixel received is placed in the next pixel location in the same row, and so on. In this first packet of a media frame, the X start value will usually be equal to X Left Edge, and Y start value will usually be equal to Y Top Edge. In subsequent packets corresponding to the same screen window, the X and Y start values will usually be set to the pixel location in the screen window that would normally follow after the last pixel sent in the Video Stream Packet that was transmitted in the previous sub-frame.

#### 4. Audio Stream Packet

[00182] The audio stream packets carry audio data to be played through the audio system of the display, or for a stand alone audio presentation device. Different audio data

streams may be allocated for separate audio channels in a sound system, for example: left-front, right-front, center, left-rear, and right-rear, depending on the type of audio system being used. A full complement of audio channels is provided for headsets that contain enhanced spatial-acoustic signal processing. The format of Audio Stream Packets are illustrated in FIG. 13. As shown in FIG. 13, this type of packet is structured to have Packet Length, Packet Type, Audio Channel ID, Audio Sample Count, Bits Per Sample and Packing, Audio Sample Rate, Parameter CRC, Digital Audio Data, and Audio Data CRC fields. In one embodiment, this type of packet is generally identified as a Type 2 packet.

[00183] The Bits Per Sample and Packing field contains 1 byte in the form of an 8-bit unsigned integer that specifies the packing format of audio data. The format generally employed is for Bits 4 through 0 to define the number of bits per PCM audio sample. Bit 5 then specifies whether or not the Digital Audio Data samples are packed. The difference between packed and byte-aligned audio samples is illustrated in FIG. 14. A value of '0' indicates that each PCM audio sample in the Digital Audio Data field is byte-aligned with an MDDI interface byte boundary, and a value of '1' indicates that each successive PCM audio sample is packed up against the previous audio sample. This bit is effective only when the value defined in bits 4 through 0 (the number of bits per PCM audio sample) is not a multiple of eight. Bits 7 through 6 are reserved for future use and are generally set at a value of zero.

## **5. Reserved Stream Packets**

[00184] In one embodiment, packet types 3 through 55 are reserved for stream packets to be defined for use in future versions or variations of the packet protocols, as desired for various applications encountered. Again, this is part of making the MDD interface more flexible and useful in the face of ever changing technology and system designs as compared to other techniques.

## **6. User-Defined Stream Packets**

[00185] Eight data stream types, known as Types 56 through 63, are reserved for use in proprietary applications that may be defined by equipment manufacturers for use with a MDDI link. These are known as User-defined Stream Packets. The video stream packets carry video data to update (or not) a rectangular region of the display. The definition of the stream parameters and data for these packet types is left to the specific



equipment manufacturers seeking their use. The format of the user-defined stream packets is illustrated in FIG. 15. As shown in FIG. 15, this type of packet is structured to have Packet Length (2 bytes), Packet Type, Stream ID number, Stream Parameters, Parameter CRC, Stream Data, and Stream Data CRC fields.

## **7. Color Map Packets**

[00186] The color map packets specify the contents of a color map look-up table used to present colors for a display. Some applications may require a color map that is larger than the amount of data that can be transmitted in a single packet. In these cases, multiple Color Map packets may be transferred, each with a different subset of the color map by using the offset and length fields described below. The format of the Color Map packet is illustrated in FIG. 16. As shown in FIG. 16, this type of packet is structured to have Packet Length, Packet Type, Color Map Data Size, Color Map Offset, Parameter CRC, Color Map Data, and Data CRC fields. This type of packet is generally identified as a Type 64 packet.

## **8. Reverse Link Encapsulation Packets**

[00187] In an exemplary embodiment, data is transferred in the reverse direction using a Reverse Link Encapsulation Packet. A forward link packet is sent and the MDDI link operation (transfer direction) is changed or turned around in the middle of this packet so that packets can be sent in the reverse direction. The format of the Reverse Link Encapsulation packet is illustrated in FIG. 17. As shown in FIG. 17, this type of packet is structured to have Packet Length, Packet Type, Reverse Link Flags, Turn-Around Length, Parameter CRC, Turn-Around 1, Reverse Data packets, and Turn-Around 2 fields. This type of packet is generally identified as a Type 65 packet.

[00188] The MDDI link controller behaves in a special manner while sending a Reverse Link Encapsulation Packet. The MDD interface has a strobe signal that is always driven by the host. The host behaves as if it were transmitting a zero for each bit of the Turn-Around and Reverse Data Packets portions of the Reverse Link Encapsulation packet. The host toggles a MDDI\_Strobe signal at each bit boundary during the two turn-around times and during the time allocated for reverse data packets. (This is the same behavior as if it were transmitting all-zero data.) The host disables its MDDI data signal line drivers during the time period specified by Turn-Around 1, and the client re-enables its line drivers during the Driver Re-enable field following the time period

specified by Turn-Around 2 field. The display reads the Turn-Around Length parameter and drives the data signals toward the host immediately after the last bit in the Turn-Around 1 field. The display uses the Packet Length and Turn-Around Length parameters to know the length of time it has available to send packets to the host. The client may send filler packets or drive the data lines to a zero state when it has no data to send to the host. If the data lines are driven to zero, the host interprets this as a packet with a zero length (not a valid length) and the host does not accept any more packets from the client for the duration of the current Reverse Link Encapsulation Packet.

[00189] The client display drives the MDDI data lines to the zero level for at least one reverse link clock period before the start of the Turn Around 2 field. This keeps the data lines in a deterministic state during the Turn Around 2 time period. If the client has no more packets to send, it may even disable the data lines after driving them to a zero level because the hibernation bias resistors (discussed elsewhere) keep the data lines at a zero level for the remainder of the Reverse Data Packets field.

[00190] The Reverse Link Request field of the Display Request and Status Packet may be used to inform the host of the number of bytes the display needs in the Reverse Link Encapsulation Packet to send data back to the host. The host attempts to grant the request by allocating at least that number of bytes in the Reverse Link Encapsulation Packet. The host may send more than one Reverse Link Encapsulation Packet in a sub-frame. The display may send a Display Request and Status Packet at almost any time, and the host will interpret the Reverse Link Request parameter as the total number of bytes requested in one sub-frame.

## 9. Display Capability Packets

[00191] A host needs to know the capability of the display (client) it is communicating with in order to configure the host-to-display link in an generally optimum or desired manner. It is recommended that a display send a Display Capability Packet to the host after forward link synchronization is acquired. The transmission of such a packet is considered required when requested by the host using the Reverse Link Flags in the Reverse Link Encapsulation Packet. The format of the Display Capability packet is illustrated in FIG. 18. As shown in FIG. 18, this type of packet is structured to have Packet Length, Packet Type, Protocol Version, Min Protocol Version, Bitmap Width, Bitmap Height, Monochrome Capability, Color Map Capability, RGB Capability, Y Cr Cb Capability, Display Feature Capability, Data Rate Capability, Frame Rate

Capability, Audio Buffer Depth, Audio Stream Capability, Audio Rate Capability, Min Sub-frame rate, and CRC fields. In an exemplary embodiment, this type of packet is generally identified as a Type 66 packet.

#### **10. Keyboard Data Packets**

[00192] A keyboard data packet is used to send keyboard data from the client device to the host. A wireless (or wired) keyboard may be used in conjunction with various displays or audio devices, including, but not limited to, a head mounted video display/audio presentation device. The Keyboard Data Packet relays keyboard data received from one of several known keyboard-like devices to the host. This packet can also be used on the forward link to send data to the keyboard. The format of a Keyboard Data Packet is shown in FIG. 19, and contains a variable number of bytes of information from or for a keyboard. As shown in FIG. 19, this type of packet is structured to have Packet Length, Packet Type, Keyboard Data, and CRC fields. Here, this type of packet is generally identified as a Type 67 packet.

#### **11. Pointing Device Data Packets**

[00193] A pointing device data packet is used to send position information from a wireless mouse or other pointing device from the display to the host. Data can also be sent to the pointing device on the forward link using this packet. An exemplary format of a Pointing Device Data Packet is shown in FIG. 20, and contains a variable number of bytes of information from or for a pointing device. As shown in FIG. 20, this type of packet is structured to have Packet Length, Packet Type, Pointing Device Data, and CRC fields. In an exemplary embodiment, this type of packet is generally identified as a Type 68 packet in the 1-byte type field.

#### **12. Link Shutdown Packets**

[00194] A Link Shutdown Packet is sent from the host to the client display to indicate that the MDDI data and strobe will be shut down and go into a low-power consumption "hibernation" state. This packet is useful to shut down the link and conserve power after static bitmaps are sent from a mobile communication device to the display, or when there is no further information to transfer from a host to a client for the time being. Normal operation is resumed when the host sends packets again. The first packet sent after hibernation is a sub-frame header packet. The format of a Display

Status Packet is shown in FIG. 21. As shown in FIG. 21, this type of packet is structured to have Packet Length, Packet Type, and CRC fields. In one embodiment, this type of packet is generally identified as a Type 69 packet in the 1-byte type field, and uses a pre-selected fixed length of 3 bytes.

[00195] In the low-power hibernation state, the MDDI\_Data driver is disabled into a high-impedance state, and the MDDI\_Data signals are pulled to a logic zero state using a high-impedance bias network that can be overdriven by the display. The strobe signal used by the interface is set to a logic zero level in the hibernation state to minimize power consumption. Either the host or client may cause the MDDI link to "wake up" from the hibernation state as described elsewhere, which is a key advance for and advantage of the present invention.

### 13 Display Request and Status Packets

[00196] The host needs a small amount of information from the display so it can configure the host-to-display link in a generally optimum manner. It is recommended that the display send one Display Status Packet to the host each sub-frame. The display should send this packet as the first packet in the Reverse Link Encapsulation Packet to ensure that it is delivered reliably to the host. The format of a Display Status Packet is shown in FIG. 22. As shown in FIG. 22, this type of packet is structured to have Packet Length, Packet Type, Reverse Link Request, CRC Error Count, and CRC fields. This type of packet is generally identified as a Type 70 packet in the 1-byte type field, and uses a pre-selected fixed length of 8 bytes.

[00197] The Reverse Link Request field may be used to inform the host of the number of bytes the display needs in the Reverse Link Encapsulation Packet to send data back to the host. The host should attempt to grant the request by allocating at least that number of bytes in the Reverse Link Encapsulation Packet. The host may send more than one Reverse Link Encapsulation Packet in a sub-frame in order to accommodate data. The client may send a Display Request and Status Packet at any time and the host will interpret the Reverse Link Request parameter as the total number of bytes requested in one sub-frame. Additional details and specific examples of how reverse link data is sent back to the host are shown below.

#### 14. Bit Block Transfer Packets

[00198] The Bit Block Transfer Packet provides a means to scroll regions of the display in any direction. Displays that have this capability will report the capability in bit 0 of the Display Feature Capability Indicators field of the Display Capability Packet. The format of a Bit Block Transfer Packet is shown in FIG. 23. As shown in FIG. 23, this type of packet is structured to have Packet Length, Packet Type, Upper Left X Value, Upper Left Y Value, Window Width, Window Height, Window X Movement, Window Y Movement, and CRC fields. This type of packet is generally identified as a Type 71 packet, and uses a pre-selected fixed length of 15 bytes.

[00199] The fields are used to specify the X and Y values of the coordinate of the upper left corner of the window to be moved, the width and height of the window to be moved, and the number of pixels that the window is to be moved horizontally, and vertically, respectively. Positive values for the latter two fields cause the window to be moved to the right, and down, and negative values cause movement to the left and up, respectively..

#### 15. Bitmap Area Fill Packets

[00200] The Bitmap Area Fill Packet provides a means to easily initialize a region of the display to a single color. Displays that have this capability will report the capability in bit 1 of the Display Feature Capability Indicators field of the Display Capability Packet. The format of a Bitmap Area Fill Packet is shown in FIG. 24. As shown in FIG. 24, this type of packet is structured to have Packet Length, Packet Type, Upper Left X Value, Upper Left Y Value, Window Width, Window Height, Data Format Descriptor, Pixel Area Fill Value, and CRC fields. This type of packet is generally identified as a Type 72 packet in the 1-byte type field, and uses a pre-selected fixed length of 17 bytes.

#### 16. Bitmap Pattern Fill Packets

[00201] The Bitmap Pattern Fill Packet provides a means to easily initialize a region of the display to a pre-selected pattern. Displays that have this capability will report the capability in bit 2 of the Display Feature Capability Indicators field of the Display Capability Packet. The upper left corner of the fill pattern is aligned with the upper left corner of the window to be filled. If the window to be filled is wider or taller than the fill pattern, then the pattern may repeated horizontally or vertically a number of times to

fill the window. The right or bottom of the last repeated pattern is truncated as necessary. If the window is smaller than the fill pattern, then the right side or bottom of the fill pattern may be truncated to fit the window.

[00202] The format of a Bitmap Pattern Fill Packet is shown in FIG. 25. As shown in FIG. 25, this type of packet is structured to have Packet Length, Packet Type, Upper Left X Value, Upper Left Y Value, Window Width, Window Height, Pattern Width, Pattern Height, Data Format Descriptor, Parameter CRC, Pattern Pixel Data, and Pixel Data CRC fields. This type of packet is generally identified as a Type 73 packet in the 1-byte type field.

#### **17. Communication Link Data Channel Packets**

[00203] The Communication Link Data Channel Packet provides a means for a display with high-level computing capability, such as a PDA, to communicate with a wireless transceiver such as a cell phone or wireless data port device. In this situation, the MDDI link is acting as a convenient high-speed interface between the communication device and the computing device with the mobile display, where this packet transports data at a Data Link Layer of an operating system for the device. For example, this packet could be used if a web browser, email client, or an entire PDA were built into a mobile display. Displays that have this capability will report the capability in bit 3 of the Display Feature Capability Indicators field of the Display Capability Packet.

[00204] The format of a Communication Link Data Channel Packet is shown in FIG. 26. As shown in FIG. 26, this type of packet is structured to have Packet Length, Packet Type, Parameter CRC, Communication Link Data, and Communication Data CRC fields. This type of packet is generally identified as a Type 74 packet in the type field.

#### **18. Interface Type Handoff Request Packets**

[00205] The Interface Type Handoff Request Packet enables the host to request that the client or display shift from an existing or current mode to the Type-I (serial), Type-II (2-bit parallel), Type-III (4-bit parallel), or Type-IV (8-bit parallel) modes. Before the host requests a particular mode it should confirm that the display is capable of operating in the desired mode by examining bits 6 and 7 of the Display Feature Capability Indicators field of the Display Capability Packet. The format of a Interface Type Handoff Request Packet is shown in FIG. 27. As shown in FIG. 27, this type of packet is structured to have Packet Length, Packet Type, Interface Type, and CRC fields. This type of packet

is generally identified as a Type 75 packet, and uses a pre-selected fixed length of 4 bytes.

#### **19. Interface Type Acknowledge Packets**

[00206] The Interface Type Acknowledge Packet is sent by the display to confirm receipt of the Interface Type Handoff Packet. The requested mode, Type-I (serial), Type-II (2-bit parallel), Type-III (4-bit parallel), or Type-IV (8-bit parallel) mode, is echoed back to the host as a parameter in this packet. The format of a Interface Type Acknowledge Packet is shown in FIG. 28. As shown in FIG. 28, this type of packet is structured to have Packet Length, Packet Type, Interface Type, and CRC fields. This type of packet is generally identified as a Type 76 packet, and uses a pre-selected fixed length of 4 bytes.

#### **20. Perform Type Handoff Packets**

[00207] The Perform Type Handoff Packet is a means for the host to command the display to handoff to the mode specified in this packet. This is to be the same mode that was previously requested and acknowledged by the Interface Type Handoff Request Packet and Interface Type Acknowledge Packet. The host and display should switch to the agreed upon mode after this packet is sent. The display may lose and re-gain link synchronization during the mode change. The format of a Perform Type Handoff Packet is shown in FIG. 29. As shown in FIG. 29, this type of packet is structured to have Packet Length, Packet Type, Packet Type, and CRC fields. This type of packet is generally identified as a Type 77 packet in the 1-byte type field, and uses a pre-selected fixed length of 4 bytes.

#### **21. Forward Audio Channel Enable Packets**

[00208] This packet allows the host to enable or disable audio channels in the display. This capability is useful so the display (client) can power off audio amplifiers or similar circuit elements to save power when there is no audio to be output by the host. This is significantly more difficult to implement implicitly simply using the presence or absence of audio streams as an indicator. The default state when the display system is powered-up is that all audio channels are enabled. The format of a Forward Audio Channel Enable Packet is shown in FIG. 30. As shown in FIG 30, this type of packet is structured to have Packet Length, Packet Type, Audio Channel Enable Mask, and CRC

fields. This type of packet is generally identified as a Type 78 packet in the 1-byte type field, and uses a pre-selected fixed length of 4 bytes.

## **22. Reverse Audio Sample Rate Packets**

[00209] This packet allows the host to enable or disable the reverse-link audio channel, and to set the audio data sample rate of this stream. The host selects a sample rate that is defined to be valid in the Display Capability Packet. If the host selects an invalid sample rate then the display will not send an audio stream to the host. The host may disable the reverse-link audio stream by setting the sample rate to 255. The default state assumed when the display system is initially powered-up or connected is with the reverse-link audio stream disabled. The format of a Reverse Audio Sample Rate Packet is shown in FIG. 31. As shown in FIG. 31, this type of packet is structured to have Packet Length, Packet Type, Audio Sample Rate, and CRC fields. This type of packet is generally identified as a Type 79 packet, and uses a pre-selected fixed length of 4 bytes.

## **23. Digital Content Protection Overhead Packets**

[00210] This packet allows the host and a display to exchange messages related to the digital content protection method being used. Presently two types of content protection are contemplated, Digital Transmission Content Protection (DTCP), or High-bandwidth Digital Content Protection System (HDCP), with room reserved for future alternative protection scheme designations. The method being used is specified by a Content Protection Type parameter in this packet. The format of a Digital Content Protection Overhead Packet is shown in FIG. 32. As shown in FIG. 32, this type of packet is structured to have Packet Length, Packet Type, Content Protection Type, Content Protection Overhead Messages, and CRC fields. This type of packet is generally identified as a Type 80 packet.

## **24. Transparent Color Enable Packets**

[00211] The Transparent Color Enable Packet is used to specify which color is transparent in a display and to enable or disable the use of a transparent color for displaying images. Displays that have this capability will report that capability in bit 4 of the Display Feature Capability Indicators field of the Display Capability Packet. When a pixel with the value for transparent color is written to the bitmap, the color does



not change from the previous value. The format of a Transparent Color Enable Packet is shown in FIG. 33. As shown in FIG. 33, this type of packet is structured to have Packet Length, Packet Type, Transparent Color Enable, Data Format Descriptor, Transparent Pixel Value, and CRC fields. This type of packet is generally identified as a Type 81 packet in the 1-byte type field, and uses a pre-selected fixed length of 10 bytes.

## **25. Round Trip Delay Measurement Packets**

[00212] The Round Trip Delay Measurement Packet is used to measure the propagation delay from the host to a client (display) plus the Delay from the client (display) back to the host. This measurement inherently includes the delays that exist in the line drivers and receivers, and an interconnect sub-system. This measurement is used to set the turn around delay and reverse link rate divisor parameters in the Reverse Link Encapsulation Packet, described generally above. This packet is most useful when the MDDI link is running at the maximum speed intended for a particular application. The MDDI\_Stb signal behaves as though all zero data is being sent during the following fields: All Zero, both Guard Times, and the Measurement Period. This causes MDDI\_Stb to toggle at half the data rate so it can be used as periodic clock in the display during the Measurement Period.

[00213] The format of a of Round Trip Delay Measurement Packet is shown in FIG. 34. As shown in FIG. 34, this type of packet is structured to have Packet Length, Packet Type, Parameter CRC, All Zero, Guard Time 1, Measurement Period, Guard Time 2, and Driver Re-enable fields. This type of packet is generally identified as a Type 82 packet, and uses a pre-selected fixed length of 533 bits.

[00214] The timing of events that take place during the Round Trip Delay Measurement Packet are illustrated in FIG. 35. In FIG. 35, the host transmits the Round Trip Delay Measurement Packet, shown by the presence of the Parameter CRC and Strobe Alignment fields followed by the All Zero and Guard Time 1 fields. A delay 3502 occurs before the packet reaches the client display device or processing circuitry. As the display receives the packet, it transmits the 0xff, 0xff, 0x0 pattern as precisely as practical at the beginning of the Measurement Period as determined by the display. The actual time the display begins to transmit this sequence is delayed from the beginning of the Measurement Period from the point of view of the host. The amount of this delay is substantially the time it takes for the packet to propagate through the line drivers and

receivers and the interconnect subsystem. A similar amount of delay 3504 is incurred for the pattern to propagate from the display back to the host.

[00215] In order to accurately determine the round trip delay time for signals traversing to and from the client, the host counts the number of bit time periods occurring after the start of the Measurement Period until the beginning of the 0xff, 0xff, 0x0 sequence is detected upon arrival. This information is used to determine the amount of time for a round trip signal to pass from the host to the client and back again. Then, about one half of this amount is attributed to a delay created for the one way passage of a signal to the client.

[00216] The display disables its line drivers substantially immediately after sending the last bit of the 0xff, 0xff, 0x0 pattern. Guard Time 2 allows time for the display's line drivers to go completely to the high-impedance state before the host transmits the Packet Length of the next packet. The hibernation pull-up and pull-down resistors (see FIG. 42) ensure that the MDDI\_Data signals are held at a valid low level in the intervals where the line drivers are disabled in both the host and display.

## 26. Forward Link Skew Calibration Packet

[00217] The Forward Link Skew Calibration Packet allows a client or Display to calibrate itself for differences in the propagation delay of the MDDI\_Data signals with respect to the MDDI\_Stb signal. Without delay skew compensation, the maximum data rate is generally limited to account for potential worst-case variation in these delays. Generally, this packet is only sent when the forward link data rate is configured to a rate of around 50 Mbps or lower. After sending this packet to calibrate the display, the data rate may be stepped up above 50 Mbps. If the data rate is set too high during the skew calibration process, the display might synchronize to an alias of the bit period which could cause the delay skew compensation setting to be off by more than one bit time, resulting in erroneous data clocking. The highest data rate type of interface or greatest possible Interface Type is selected prior to sending the Forward Link Skew Calibration Packet so that all existing data bits are calibrated.

[00218] The format of a Forward Link Skew Calibration Packet is shown in FIG. 56. As shown in FIG. 56, this type of packet is structured to have Packet Length (2 bytes), Packet Type, Parameter CRC, Calibration Data Sequence, and CRC fields. This type of packet is generally identified as a Type 83 packet in the type field, and has a pre-selected length of 515.

#### D. Packet CRC

[00219] The CRC fields appear at the end of the packets and sometimes after certain more critical parameters in a packet that may have a significantly large data field, and thus, an increased likelihood of errors during transfer. In packets that have two CRC fields, the CRC generator, when only one is used, is re-initialized after the first CRC so that the CRC computations following a long data field are not affected by the parameters at the beginning of the packet.

[00220] In an exemplary embodiment, the polynomial used for the CRC calculation is known as the CRC-16, or  $X^{16} + X^{15} + X^2 + X^0$ . A sample implementation of a CRC generator and checker 3600 useful for implementing the invention is shown in FIG. 36. In FIG. 36, a CRC register 3602 is initialized to a value of 0x0001 just prior to transfer of the first bit of a packet which is input on the Tx\_MDDI\_Data\_Before\_CRC line, then the bytes of the packet are shifted into the register starting with the LSB first. Note that the register bit numbers in this figure correspond to the order of the polynomial being used, and not the bit positions used by the MDDI. It is more efficient to shift the CRC register in a single direction, and this results in having CRC bit 15 appear in bit position 0 of the MDDI CRC field, and CRC register bit 14 in MDDI CRC field bit position 1, and so forth until MDDI bit position 14 is reached.

[00221] As an example, if the packet contents for the Display Request and Status Packets are: 0x07, 0x46, 0x000400, 0x00 (or represented as a sequence of bytes as: 0x07, 0x00, 0x46, 0x00, 0x04, 0x00, 0x00), and are submitted using the inputs of the multiplexors 3604 and 3606, and NAND gate 3608, the resulting CRC output on the Tx\_MDDI\_Data\_With\_CRC line is 0x0ea1 (or represented as a sequence as 0xa1, 0x0e).

[00222] When CRC generator and checker 3600 is configured as a CRC checker, the CRC that is received on the Rx\_MDDI\_Data line is input to multiplexor 3604 and NAND gate 3608, and is compared bit by bit with the value found in the CRC register using NOR gate 3610, exclusive-OR (XOR) gate 3612, and AND gate 3614. If there are any errors, as output by AND gate 3614, the CRC is incremented once for every packet that contains a CRC error by connecting the output of gate 3614 to the input of register 3602. Note that the example circuit shown in the diagram of FIG. 36 can output more than one CRC error signal within a given CHECK\_CRC\_NOW window (see FIG. 37B). Therefore, the CRC error counter generally only counts the first CRC error

instance within each interval where CHECK\_CRC\_NOW is active. If configured as a CRC generator the CRC is clocked out of the CRC register at the time coinciding with the end of the packet.

[00223] The timing for the input and output signals, and the enabling signals, is illustrated graphically in FIGS. 37A and 37B. The generation of a CRC and transmission of a packet of data are shown in FIG. 37A with the state (0 or 1) of the Gen\_Reset, Check\_CRC\_Now, Generate\_CRC\_Now, and Sending\_MDDI\_Data signals, along with the Tx\_MDDI\_Data\_Before\_CRC and Tx\_MDDI\_Data\_With\_CRC signals. The reception of a packet of data and checking of the CRC value are shown in FIG. 37B, with the state of the Gen\_Reset, Check\_CRC\_Now, Generate\_CRC\_Now, and Sending\_MDDI\_Data signals, along with the Rx\_MDDI\_Data and CRC error signals.

#### **E. Error Code Overload for Packet CRC**

[00224] Whenever only data packets and CRC are being transferred between the host and client, there are no error codes being accommodated. The only error is a loss of synchronization. Otherwise, one has to wait for the link to timeout from a lack of a good data transfer path or pipeline and then reset the link and proceed. Unfortunately, this is time consuming and somewhat inefficient.

[00225] For use in one embodiment, a new technique has been developed in which the CRC portion of packets is used to transfer error code information. This is generally shown in the over view of FIG. 65, and in more detail in FIGS. 66A, 66B, and 67. That is, one or more error codes are generated by the processors or devices handling the data transfer which indicate specific predefined errors or flaws that might occur within the communication processing or link. When an error is encountered, that the appropriate error code is generated and transferred using the bits for the CRC of a packet. That is, the CRC value is overloaded, or overwritten, with the desired error code, or some other pre-selected value to represent the presence of an error, which can be detected on the receiving end by an error monitor or checker that monitors the values of the CRC field. For those cases in which the error code matches the CRC value for some reason, the compliment of the error is transferred to prevent confusion.

[00226] In one embodiment, to provide a robust error warning and detection system, the error code may be transferred several times, using a series of packets, generally all, that are transferred or sent after the error has been detected. This occurs until the point at

which the condition creating the error is cleared from the system, at which point the regular CRC bits are transferred without overloading by another value.

[00227] This technique of overloading the CRC value provides a much quicker response to system errors while using a minimal amount of extra bits or fields.

[00228] As shown in FIG. 66, a CRC overwriting mechanism or apparatus 6600 is shown using an error detector or detections means 6602, which can form part of other circuitry previously described or known, detects the presence or existence of errors within the communication link or process. An error code generator or means 6604, which can be formed as part of other circuitry or use techniques such as look up tables to store pre-selected error messages, generates one or more error codes to indicate specific predefined errors or flaws that have been detected as occurring. It is readily understood that devices 6602 and 6604 can be formed as a single circuit or device as desired, or as part of a programmed sequence of steps for other known processors and elements.

[00229] A CRC value comparator or comparison means 6606 is shown for checking to see if the selected error code or codes are the same as the CRC value being transferred. If that is the case then a code compliment generator or generation means or device is used to provide the compliment of the error codes as to not be mistaken as the original CRC pattern or value and confuse or complicate the detection scheme. An error code selector or selection means element or device 6610 then selects the error code or value it is desired to insert or overwrite, or their respective compliments as appropriate. An error code CRC over-writer or over writing mechanism or means 6612 is a device that receives the data stream, packets, and the desired codes to be inserted and overwrites the corresponding or appropriate CRC values, in order to transfer the desired error codes to a receiving device.

[00230] As mentioned, the error code may be transferred several times, using a series of packets, so the over-writer 6612 may utilize memory storage elements in order to maintain copies of the codes during processing or recall these codes from previous elements or other known storage locations which can be used to store or hold their values as needed, or as desired.

[00231] The general processing the overwriting mechanism of FIG. 66 is implementing is shown in additional detail in FIGS. 67A and 67B. In 67A an error, one or more, is detected in step 6702 in the communication data or process and an error code is selected in step 6704 to indicate this condition. At the same time, or at an appropriate point, the

CRC value to be replaced is checked in a step 6706, and compared to the desired error code in step 6708. The result of this comparison, as discussed earlier, is a determination as to whether or not the desired code, or other representative values, will be the same as the CRC value present. If this is the case, then processing proceeds to a step 6712 where the compliment, or in some cases another representative value, as desired, is selected as the code to insert. Once it has been determined what error codes or values are to be inserted in steps 6710 and 6714, that appropriate code is selected for insertion. These steps are illustrated as separate for purposes of clarity but generally represent a single choice based on the output of the step 6708 decision. Finally, in step 6716 the appropriate values are overwritten in the CRC location for transfer with the packets being targeted by the process.

[00232] On the packet reception side, as shown in FIG. 67B, the packet CRC values are being monitored in a step 6722. Generally, the CRC values are being monitored by one or more processes within the system to determine if an error in data transfer has occurred and whether or not to request a retransmission of the packet or packets, or to inhibit further operations and so forth, some of which is discussed above. As part of such monitoring the information can also be used to compare values to known or preselected error codes, or representative values and detect the presence of errors. Alternatively, a separate error detection process and monitor can be implemented. If a code appears to be present it is extracted or otherwise noted in step 6724 for further processing. A determination can be made in step 6726 as to whether or not this is the actual code or a compliment, in which case an additional step 6728 is used to translate the value to the desired code value. In either case the resulting extracted code, compliment, or other recovered values are then used to detect what error has occurred from the transmitted code in step 6730.

## **V. Link Restart from Hibernation**

[00233] When the host restarts the forward link from a hibernation state it drives MDDI\_Data to a logic one state for about 150  $\mu$ sec and then activates MDDI\_Stb and simultaneously drives MDDI\_Data to a logic zero state for 50  $\mu$ sec, and then starts forward link traffic by sending a sub-frame header packet. This generally allows bus contentions to be resolved before the sub-frame header packet is sent by providing enough settling time between signals.

[00234] When the client, here a display, needs data or communication from the host it drives the MDDI\_Data0 line to a logic one state for around 70  $\mu$ sec, although other periods can be used as desired, and then disables the driver by placing it in a high-impedance state. This action causes the host to start or restart data traffic on the forward link (208) and to poll the client for its status. The host must detect the presence of the request pulse within 50  $\mu$ sec and then begin the startup sequence of driving MDDI\_Data0 to logic one for 150  $\mu$ sec and to logic zero for 50  $\mu$ sec. The display should not send a service request pulse if it detects MDDI\_Data0 in the logic one state for more than 50  $\mu$ sec. The nature of selection of the times and tolerances of time intervals related to the hibernation processing and start up sequence are discussed further below.

[00235] An example of the processing steps for a typical service request event 3800 with no contention is illustrated in FIG. 38, where the events are labeled for convenience in illustration using the letters A, B, C, D, E, F, and G. The process commences at point A when the host sends a Link Shutdown Packet to the client device to inform it that the link will transition to a low-power hibernation state. In a next step, the host enters the low-power hibernation state by disabling the MDDI\_Data0 driver and setting the MDDI\_Stb driver to a logic zero, as shown at point B. MDDI\_Data0 is driven to a zero level by a high-impedance bias network. After some period of time, the client sends a service request pulse to the host by driving MDDI\_Data0 to a logic one level as seen at point C. The host still asserts the zero level using the high-impedance bias network, but the driver in the client forces the line to a logic one level. Within 50  $\mu$ sec, the host recognizes the service request pulse, and asserts a logic one level on MDDI\_Data0 by enabling its driver, as seen at point D. The client then ceases from attempting to assert the service request pulse, and the client places its driver into a high-impedance state, as seen at point E. The host drives MDDI\_Data0 to a logic zero level for 50  $\mu$ sec, as shown at point F, and also begins to generate MDDI\_Stb in a manner consistent with the logic zero level on MDDI\_Data0. After asserting MDDI\_Data0 to a zero level and driving MDDI\_Stb for 50  $\mu$ sec, the host begins to transmit data on the forward link by sending a Sub-frame Header Packet, as shown at point G.

[00236] A similar example is illustrated in FIG. 39 where a service request is asserted after the link restart sequence has begun, and the events are again labeled using the letters A, B, C, D, E, F, and G. This represents a worst case scenario where a request

pulse or signal from the client comes closest to corrupting the Sub-frame Header Packet. The process commences at point A when the host again sends a Link Shutdown Packet to the client device to inform it that the link will transition to a low-power hibernation state. In a next step, the host enters the low-power hibernation state by disabling the MDDI\_Data0 driver and setting the MDDI\_Stb driver to a logic zero, as shown at point B. As before, MDDI\_Data0 is driven to a zero level by a high-impedance bias network. After a period of time, the host begins the link restart sequence by driving MDDI\_Data0 to a logic one level for 150  $\mu$ sec as seen at point C. Prior to 50  $\mu$ sec passing after the link restart sequence begins the display also asserts MDDI\_Data0 for a duration of 70  $\mu$ sec, as seen at point D. This happens because the display has a need to request service from the host and does not recognize that the host has already begun the link restart sequence. The client then ceases attempting to assert the service request pulse, and the client places its driver into a high-impedance state, as seen at point E. The host continues to drive MDDI\_Data0 to a logic one level. The host drives MDDI\_Data0 to a logic zero level for 50  $\mu$ sec, as shown at point F, and also begins to generate MDDI\_Stb in a manner consistent with the logic zero level on MDDI\_Data0. After asserting MDDI\_Data0 to a zero level, and driving MDDI\_Stb for 50  $\mu$ sec, the host begins to transmit data on the forward link by sending a Sub-frame Header Packet, as shown at point G.

[00237] From the above discussion, one sees that the prior solution involved having the host go through two states as part of a wakeup sequence. For the first state, the host drives the MDDI\_Data0 signal high for 150  $\mu$ s, and then drives the MDDI\_Data0 signal low for 50us while activating the MDDI\_Stb line, and then begins to transmit MDDI packets. This process works well to advance the state of the art in terms of data rates achievable using the MDDI apparatus and methods. However, as stated earlier, more speed in terms of reduced response time to conditions or the ability to more quickly select the next step or process, or the ability to simplify processing or elements, are always in demand.

[00238] Applicants have discovered a new inventive approach to wake-up processing and timing in which the host uses a clock cycle based timing for the signal toggling. In this configuration, the host starts toggling MDDI\_Stb from 0 to 10  $\mu$ sec after the host drives the MDDI\_Data0 signal high at the beginning of the wake-up sequence, and does not wait until the signal is driven low. During a wake-up sequence, the host toggles



MDDL\_Stb as though the MDDL\_Data0 signal were always at a logic-zero level. This effectively removes the concept of time from the client side, and the host changes from the prior 150  $\mu$ s and 50  $\mu$ s periods for the first two states, to 150 clock cycles and 50 clock cycles, for these periods.

[00239] The host now becomes responsible for driving that data line high, and within 10 clock cycles starting to transmit a strobe signal as if the data line was zero. After the host has driven the data line high for 150 clock cycles, the host drives the data line low for 50 clock cycles while continuing to transmit the strobe signal. After it has completed both of these processes, the host can begin to transmit the first sub-frame header packet.

[00240] On the client side, the client implementation can now use the generated clock to calculate the number of clock cycles that the data line is first high, and then low. The number of clock cycles that need to occur in both the data line driven high state is 150 and data line driven low state is 50. This means that for a proper wakeup sequence, the client should be able to count at least 150 continuous clock cycles of the data line being high, followed by at least 50 continuous clock cycles of the data line being low. Once these two conditions are met, the client can begin to search for the unique word of the first sub-frame. A break in this pattern is used as a basis to return the counters to an initial state in which the client again looks for the first 150 continuous clock cycles of the data line being high.

[00241] A client implementation of the invention for host based wakeup from hibernation is very similar to the initial start-up case except that the clock rate is not forced to start at 1Mbps., as discussed earlier. Instead the clock rate can be set to resume at whatever previous rate was active when the communication link went into hibernation. If the host begins transmission of a strobe signal as described above, the client should be able to again count at least 150 continuous clock cycles of the data line being high, followed by at least 50 continuous clock cycles of the data line being low. Once these two conditions have been met, the client can begin the search for the unique word.

[00242] A client implementation of the invention for client based wakeup from hibernation is similar to the host based wakeup except that it starts by having the client driving the data line. The client can asynchronously drive the data line without a clock to wake up the host device. Once the host recognizes that the data line is being driven high by the client, it can begin its wakeup sequence. The client can count the number of

clock cycles generated by the host starting or during its wakeup process. Once the client counts 70 continuous clock cycles of the data being high, it can stop driving the data line high. At this point, the host should already be driving the data line high as well. The client can then count another 80 continuous clock cycles of the data line being high to reach the 150 clock cycles of the data line being high, and can then look for 50 clock cycles of the data line being low. Once these three conditions have been met the client can begin to look for the unique word.

[00243] An advantage of this new implementation of wake-up processing is that it removes the need for a time measuring device. Whether this is an oscillator, or capacitor discharge circuit, or other such known devices, the client no longer needs such external devices to determine the start up conditions. This saves money and circuit area when implementing controllers, counters, and so forth on a client device board. While this may not be as advantageous to the client, for the host, this technique should also potentially simplify the host in terms of very high density logic (VHDL) being used for core circuitry. The power consumption of using the data and strobe lines as the wakeup notification and measurement source will also be lower since no external circuitry will need to be running for the core elements to be waiting for a host based wakeup.

[00244] The number of cycles or clock periods used are exemplary and other periods can be used as will be apparent to one skilled in the art.

[00245] An advantage of this new implementation of wake-up processing is that it removes the need for a time measuring device. Whether this is an oscillator, or capacitor discharge circuit, or other such known devices, the client no longer needs such external devices to determine the start up conditions. This saves money and circuit area when implementing controllers, counters, and so forth on a client device board. While this may not be as advantageous to the client, for the host, this technique should also potentially simplify the host in terms of very high density logic (VHDL) being used for core circuitry. The power consumption of using the data and strobe lines as the wakeup notification and measurement source will also be lower since no external circuitry will need to be running for the core elements to be waiting for a host based wakeup.

[00246] To clarify and illustrate the operation of this new technique, the timing of MDDI\_Data0, MDDI\_Stb, and various operations relative to the clock cycles are shown in FIGS. 68A, 68B, and 68C.

[00247] An example of the processing steps for a typical Host-initiated Wake-up with no contention is illustrated in FIG. 68A, where the events are again labeled for convenience

in illustration using the letters A, B, C, D, E, F, and G. The process commences at point A when the host sends a Link Shutdown Packet to the client device to inform it that the link will transition to a low-power hibernation state. In a next step, point B, the host toggles MDDI\_Stb for about 64 cycles (or as desired for system design) to allow processing by the client to be completed prior to stopping MDDI\_Stb from toggling, which stops the recovered clock in the client device. The host also initially sets MDDI\_Data0 to logic-zero level and then disables the MDDI\_Data0 output in the range of 16 to 48 cycles (generally including output disable propagation delays) after the CRC. It may be desirable to place high-speed receivers for MDDI\_Data0 and MDDI\_Stb in the client in a low power state some time after the 48 cycles after the CRC and prior to the next stage (C).

[00248] The host enters the low-power hibernation state at point or step C, by disabling the MDDI\_Data0 and MDDI\_Stb drivers and placing a host controller in a low power hibernation state. One can also set the MDDI\_Stb driver to a logic-zero level (using a high-impedance bias network) or to continue toggling during hibernation, as desired. The client is also in a low power level hibernation state.

[00249] After some period of time, the host commences the link restart sequence at point D, by enabling the MDDI\_Data0 and MDDI\_Stb driver output. The host drives MDDI\_Data0 to a logic-one level and MDDI\_Stb to a logic-zero level for as long as it should take for the drivers to fully enable their respective outputs. The host typically waits around 200 nanoseconds after these outputs reach desired logic levels before driving pulses on MDDI\_Stb. This allows the client time to prepare to receive.

[00250] With the host drivers enabled and MDDI\_Data0 being driven to a logic-one level, the host begins to toggle MDDI\_Stb for a duration of 150 MDDI\_Stb cycles, as seen at point E. The host drives MDDI\_Data0 to a logic zero level for 50 cycles, as shown at point F, and the client begins to look for the Sub-frame Header Packet after MDDI\_Data0 is at a logic-zero level for 40 MDDI\_Stb cycles. The host begins to transmit data on the forward link by sending a Sub-frame Header Packet, as shown at point G.

[00251] An example of the processing steps for a typical Client-initiated Wake-up with no contention is illustrated in FIG. 68B, where the events are again labeled for convenience in illustration using the letters A, B, C, D, E, F, G, H, and I. As before, the process commences at point A when the host sends a Link Shutdown Packet to inform the client that the link will transition to the low power state.

[00252] At point B, the host toggles MDDI\_Stb for about 64 cycles (or as desired for system design) to allow processing by the client to be completed prior to stopping MDDI\_Stb from toggling, which stops the recovered clock in the client device. The host also initially sets MDDI\_Data0 to a logic-zero level and then disables the MDDI\_Data0 output in the range of 16 to 48 cycles (generally including output disable propagation delays) after the CRC. It may be desirable to place high-speed receivers for MDDI\_Data0 and MDDI\_Stb in the client in a low power state some time after the 48 cycles after the CRC and prior to the next stage (C).

[00253] The host enters the low-power hibernation state at point or step C, by disabling the MDDI\_Data0 and MDDI\_Stb drivers and placing a host controller in a low power hibernation state. One can also set the MDDI\_Stb driver to a logic-zero level (using a high-impedance bias network) or to continue toggling during hibernation, as desired. The client is also in a low power level hibernation state.

[00254] After some period of time, the client commences the link restart sequence at point D, by enabling the MDDI\_Stb receiver, and also enabling an offset in the MDDI\_Stb receiver to guarantee the state of the received version of MDDI\_Stb is a logic-zero level in the client before the host enables its MDDI\_Stb driver. It may be desirable for the client to enable the offset slightly ahead of enabling the receiver to ensure the reception of a valid differential signal and inhibit erroneous signals, as desired. The Client enables the MDDI\_Data0 driver while driving the MDDI\_Data0 line to a logic one level

[00255] Within about 1 msec., point E, the host recognizes the service request pulse from the client, and the host begins the link restart sequence by enabling the MDDI\_Data0 and MDDI\_Stb driver outputs. The host drives MDDI\_Data0 to a logic-one level and MDDI\_Stb to a logic-zero level for as long as it should take for the drivers to enable their respective outputs. The host typically waits around 200 nanoseconds after these outputs reach desired logic levels before driving pulses on MDDI\_Stb. This allows the client time to prepare to receive.

[00256] With the host drivers enabled and MDDI\_Data0 being driven to a logic-one level, the host begins outputting pulses on MDDI\_Stb for a duration of 150 MDDI\_Stb cycles, as seen at point F. When the client recognizes the first pulse on MDDI\_Stb it disables the offset in its MDDI\_Stb receiver. The client continues to drive MDDI\_Data0 to a logic-one level for 70 MDDI\_Stb cycles, and disables its MDDI\_Data0 driver at point G.

[00257] As seen at points G and H, the host drives MDDI\_Data0 to a logic-zero level for 50 cycles, and the client begins to look for the Sub-frame Header Packet after MDDI\_Data0 is at a logic-zero level for 40 MDDI\_Stb cycles. The host begins to transmit data on the forward link by sending a Sub-frame Header Packet, as shown at point I.

[00258] An example of the processing steps for a typical Host-initiated Wake-up with contention from the client, that is the client also wants to wake up the link, is illustrated in FIG. 68C. The events are again labeled for convenience in illustration using the letters A, B, C, D, E, F, G, H, and I. As before, the process commences at point A when the host sends a Link Shutdown Packet to inform the client that the link will transition to the low power state, proceeds to point B where MDDI\_Stb is toggled for about 64 cycles (or as desired for system design) to allow processing by the client to be completed, and then to point C, where the host enters the low-power hibernation state, by disabling the MDDI\_Data0 and MDDI\_Stb drivers and placing a host controller in a low power hibernation state. After some period of time, the host commences the link restart sequence at point D, by enabling the MDDI\_Data0 and MDDI\_Stb driver output, and begins to toggle MDDI\_Stb for a duration of 150 MDDI\_Stb cycles, as seen at point E.

[00259] At up to 70 MDDI\_Stb cycles after point E, here point F, the client has not yet recognized that the host is driving MDDI\_Data0 to a logic-one level so the client also drives MDDI\_Data0 to a logic-one level. This occurs here because the client has a desire to request service but does not recognize that the host it is trying to communicate with has already begun the link restart sequence. At point G, the client ceases to drive MDDI\_Data0, and places its driver into a high impedance state by disabling its output. The host continues to drive MDDI\_Data0 to a logic-one level for 80 additional cycles.

[00260] The host drives MDDI\_Data0 to a logic zero level for 50 cycles, as shown at point H, and the client begins to look for the Sub-frame Header Packet after MDDI\_Data0 is at a logic-zero level for 40 MDDI\_Stb cycles. The host begins to transmit data on the forward link by sending a Sub-frame Header Packet, as shown at point I.

## **VI. Interface Electrical Specifications**

[00261] In the example embodiments, Data in a Non-Return-to-Zero (NRZ) format is encoded using a data-strobe signal or DATA-STB format, which allows clock

information to be embedded in the data and strobe signals. The clock can be recovered without complex phase lock loop circuitry. Data is carried over a bi-directional differential link, generally implemented using a wire-line cable, although other conductors, printed wires, or transfer elements can be used, as stated earlier. The strobe signal (STB) is carried over a uni-directional link which is driven only by the host. The strobe signal toggles value (0 or 1) whenever there is a back-to-back state, 0 or 1, that remains the same on the Data line or signal.

[00262] An example of how a data sequence such as bits "1110001011" can be transmitted using DATA-STB encoding is shown in graphical form in FIG. 40. In FIG. 40, a DATA signal 4002 is shown on the top line of a signal timing chart and a STB signal 4004 is shown on a second line, each time aligned as appropriate (common starting point). As time passes, when there is a change of state occurring on the DATA line 4002 (signal), then the STB line 4004 (signal) maintains a previous state, thus, the first '1' state of the DATA signal correlates with the first '0' state for the STB signal, its starting value. However, if or when the state, level, of the DATA signal does not change then the STB signal toggles to the opposite state or '1' in the present example, as is the case in FIG. 40 where the DATA is providing another '1' value. That is, there is one and only one transition per bit cycle between DATA and STB. Therefore, the STB signal transitions again, this time to '0' as the DATA signal stays at '1' and holds this level or value as the DATA signal changes level to '0'. When the DATA signal stays at '1', the STB signal toggles to the opposite state or '1' in the present example, and so forth, as the DATA signal changes or holds levels or values.

[00263] Upon receiving these signals, an exclusive-OR (XOR) operation is performed on the DATA and STB signals to produce a clock signal 4006, which is shown on the bottom of the timing chart for relative comparison with the desired data and strobe signals. An example of circuitry useful for generating the DATA and STB outputs or signals from input data at the host, and then recovering or recapturing the data from the DATA and STB signals at the client, is shown in FIG. 41.

[00264] In FIG. 41, a transmission portion 4100 is used to generate and transmit the original DATA and STB signals over an intermediary signal path 4102, while a reception portion 4120 is used to receive the signals and recover the data. As shown in FIG. 41, in order to transfer data from a host to a client, the DATA signal is input to two D-type flip-flop circuit elements 4104 and 4106 along with a clock signal for triggering the circuits. The two flip-flop circuit outputs (Q) are then split into a differential pair of

signals MDDI\_Data0+, MDDI\_Data0- and MDDI\_Stb+, MDDI\_Stb-, respectively, using two differential line drivers 4108 and 4110 (voltage mode). A three-input exclusive-NOR (XNOR) gate, circuit, or logic element 4112 is connected to receive the DATA and outputs of both flip-flops, and generates an output that provides the data input for the second flip-flop, which in turn generates the MDDI\_Stb+, MDDI\_Stb- signals. For convenience, the XNOR gate has the inversion bubble placed to indicate that it is effectively inverting the Q output of the flip-flop that generates the Strobe.

[00265] In reception portion 4120 of FIG 41, the MDDI\_Data0+, MDDI\_Data0- and MDDI\_Stb+, MDDI\_Stb- signals are received by each of two differential line receivers 4122 and 4124, which generate single outputs from the differential signals. The outputs of the amplifiers are then input to each of the inputs of a two-input exclusive-OR (XOR) gate, circuit, or logic element 4126 which produces the clock signal. The clock signal is used to trigger each of two D-type flip-flop circuits 4128 and 4130 which receive a delayed version of the DATA signal, through delay element 4132, one of which (4128) generates data '0' values and the other (4130) data '1' values. The clock has an independent output from the XOR logic as well. Since the clock information is distributed between the DATA and STB lines, neither signal transitions between states faster than half of the clock rate. Since the clock is reproduced using the exclusive-OR processing of the DATA and STB signals, the system effectively tolerates twice the amount of skew between the input data and clock compared to the situation when a clock signal is sent directly over a single dedicated data line.

[00266] The MDDI Data pairs, MDDI\_Stb+, and MDDI\_Stb- signals are operated in a differential mode to maximize immunity from the negative affects of noise. Each portion of the differential signal path is source terminated with one-half of the characteristic impedance of the cable or conductor being used to transfer signals. MDDI Data pairs are source terminated at both the host and client ends. Since only one of these two drivers is active at a given time, a termination continuously exists at the source for the transfer link. The MDDI\_Stb+ and MDDI\_Stb- signals are only driven by the host.

[00267] An exemplary configuration of elements useful for achieving the drivers, receivers, and terminations for transferring signals as part of the inventive MDD interface are shown in FIG. 42, while corresponding DC electrical specifications of MDDI\_Data and MDDI\_Stb are shown in Table VII. This exemplary interface uses

low voltage sensing, here 200 mV, with less than 1 volt power swings and low power drain.

[00268] **TABLE VII**

Parameter	Description	Min.	Typ.	Max.	Units
$R_{term}$	Series Termination	41.3	42.2	43.0	Ohms
$R_{hibernate}$	Hibernate State bias termination	8	10	12	K-Ohms
$V_{hibernate}$	Hibernate State open-circuit voltage	0.5		2.8	V
$V_{Output-Range}$	Allowable driver output voltage range with respect to GND	0		2.8	V
$V_{OD+}$	Driver differential output high voltage	0.5			V
$V_{OD-}$	Driver differential output low voltage			-0.5	V
$V_{IT+}$	Receiver differential input high threshold voltage			10	mV
$V_{IT-}$	Receiver differential input low threshold voltage	-10			mV
$V_{Input-Range}$	Allowable receiver input voltage range with respect to GND	0		3.0	V
$I_{in}$	Input leakage current (excluding hibernate bias)	-25		25	$\mu A$

[00269] The electrical parameters and characteristics of the differential line drivers and line receivers are described in Table VIII. Functionally, the driver transfers the logic level on the input directly to a positive output, and the inverse of the input to a negative output. The delay from input to outputs is well-matched to the differential line which is driven differentially. In most implementations, the voltage swing on the outputs is less than the swing on the input to minimize power consumption and electromagnetic emissions. Table VIII presents a minimum voltage swing to be around 0.5V. However, other values can be used, as would be known by those skilled in the art, and the inventors contemplate a smaller value in some embodiments, depending on design constraints.

[00270] The differential line receivers have the same characteristic as a high-speed voltage comparator. In FIG. 41, the input without the bubble is the positive input and the input with the bubble is the negative input. The output is a logic one if:  $(V_{input+}) - (V_{input-})$  is greater than zero. Another way to describe this is a differential amplifier



with very large (virtually infinite) gain with the output clipped at logic 0 and 1 voltage levels.

[00271] The delay skew between different pairs should be minimized to operate the differential transmission system at the highest potential speed.

[00272] In FIG. 42, a host controller 4202 and a client or display controller 4204 are shown transferring packets over the communication link 4206. The host controller employs a series of three drivers 4210, 4212, and 4214 to receive the host DATA and STB signals to be transferred, as well as to receive the client Data signals to be transferred. The driver responsible for passage of the host DATA employs an enable signal input to allow activation of the communication link generally only when transfer from the host to the client is desired. Since the STB signal is formed as part of the transfer of data, no additional enable signal is employed for that driver (4212). The outputs of each of the DATA and STB drivers are connected to termination impedances or resistors 4216a, 4216b, 4216c, and 4216d, respectively.

[00273] Termination resistors 4216a and 4216b will also act as impedances on the input of the client side receiver 4220 for the STB signal processing while additional termination resistors 4216e and 4216f are placed in series with resistors 4216c and 4216d, respectively on the input of the client data processing receiver 4222. A sixth driver 4226 in the client controller is used to prepare the data signals being transferred from the client to the host, where driver 4214, through termination resistors 4216c and 4216d, on the input side, processes the data for transfer to the host for processing.

[00274] Two additional resistors 4218a and 4218b are placed between the termination resistors and ground and a voltage source 4220, respectively, as part of the hibernation control discussed elsewhere. The voltage source is used to drive the transfer lines to the high or low levels previously discussed to manage the flow of data.

[00275] The above drivers and impedances can be formed as discrete components or as part of a circuit module, or an application specific integrated circuit (ASIC) which acts as a more cost effective encoder or decoder solution.

[00276] It can be easily seen that power is transferred to the client device, or display, from the host device using the signals labeled MDDI\_Pwr and MDDI\_Gnd over a pair of conductors. The MDDI\_Gnd portion of the signal acts as the reference ground and the power supply return path or signal for the display device. The MDDI\_Pwr signal acts as the display device power supply which is driven by the host device. In an exemplary configuration, for low power applications, the display device is allowed to

draw up to 500 mA. The MDDI\_Pwr signal can be provided from portable power sources, such as but not limited to, a lithium-ion type battery or battery pack residing at the host device, and may range from 3.2 to 4.3 volts with respect to MDDI\_Gnd.

## VII. Timing Characteristics

### A. Overview

[00277] The steps and signal levels employed by a client to secure service from the host and by the host to provide such service, are illustrated in FIG. 43. In FIG. 43, the first part of signals being illustrated shows a Link Shutdown Packet being transferred from the host and the data line is then driven to a logic zero state using the high-impedance bias circuit. No data is being transmitted by the client display, or host, which has its driver disabled. A series of strobe pulses for the MDDI\_Stb signal line can be seen at the bottom, since MDDI\_Stb is active during the Link Shutdown Packet. Once this packet ends and the logic level changes to zero as the host drives the bias circuit and logic to zero, the MDDI\_Stb signal line changes to a zero level as well. This represents the termination of the last signal transfer or service from the host, and could have occurred at any time in the past, and is included to show the prior cessation of service, and the state of the signals prior to service commencement. If desired, such as signal can be sent just to reset the communication link to the proper state without a 'known' prior communication having been undertaken by this host device.

[00278] As shown in FIG. 43, the signal output from the client is initially set at a logic level of zero. In other words, the client output is at a high impedance, and the driver is disabled. When service is being requested, the client enables its driver and sends a service request to the host, which is a period of time, designated tservice, during which the line is driven to a logic one level. A certain amount of time then passes or may be needed before the host detects the request, termed thost-detect, after which the host responds with a link startup sequence by driving the signal to a logic one level. At this point, the client de-asserts the request, and disables the service request driver so that the output line from the client goes to a zero logic level again. During this time, the MDDI\_Stb signal is at a logic zero level.

[00279] The host drives the host data output at the '1' level for a period termed trestart-high, after which the host drives the logic level to zero and activates MDDI\_Stb for a period termed trestart-low, after which the first forward traffic begins with a Sub-Frame

Header Packet, and the forward traffic packets are then transferred. The MDDI\_Stb signal is active during the t<sub>restart-low</sub> period and the subsequent Sub-Frame Header Packet.

[00280] Table VIII shows representative times for the length of the various periods discussed above, and the relationship to exemplary minimum and maximum data rates, where:

$$t_{\text{bit}} = \frac{1}{\text{Link\_Data\_Rate}}$$

[00281] **Table VIII**

Parameter	Description	Min.	Typ.	Max.	Units
t <sub>service</sub>	Duration of display service request pulse	60	70	80	μsec
t <sub>restart-high</sub>	Duration of host link restart high pulse	140	150	160	μsec
t <sub>restart-low</sub>	Duration of host link restart low pulse	40	50	60	μsec
t <sub>display-detect</sub>	Time for display to detect link restart sequence	1		50	μsec
t <sub>host-detect</sub>	Time for host to detect service request pulse	1		50	μsec
1/t <sub>bit-min-perf</sub>	Link data rate for a minimum performance device	0.001		1	Mbps
1/t <sub>bit-max-perf</sub>	Maximum link data rate range for a device	0.001		450	Mbps
	Reverse Link data rate	0.0005		50	Mbps
t <sub>bit</sub>	Period of one forward link data bit	2.2		10 <sup>9</sup>	nsec

[00282] Those skilled in the art will readily understand that the functions of the individual elements illustrated in FIGS. 41 and 42, are well known, and the function of the elements in FIG. 42 is confirmed by the timing diagram in FIG. 43. Details about the series terminations and hibernation resistors that are shown in FIG. 42 were omitted from FIG. 41 because that information is unnecessary for a description of how to perform the Data-Strobe encoding and recover the clock from it.

### B. Data-Strobe Timing Forward Link

[00283] The switching characteristics for the transfer of data on the forward link from the host driver output is shown in Table IX. Table IX presents a tabular form of the minimum and maximum desired, versus typical times for certain signal transitions to occur. For example, the typical length of time for a transition to occur from the start to the end of a data value (output of a '0' or '1'), a Data0 to Data0 transition, termed  $t_{dd}(\text{host-output})$ , is  $t_{bit}$  while the minimum time is about  $t_{bit}-0.5$  nsec., and the maximum is about  $t_{bit}+0.5$  nsec. The relative spacing between transitions on the Data0, other data lines (DataX), and the strobe lines (Stb), is illustrated in FIG. 44 where the Data0 to Strobe, Strobe to Strobe, Strobe to Data0, Data0 to non-Data0, non-Data0 to non-Data0, non-Data0 to Strobe, and Strobe to non-Data0 transitions are shown, which are referred to as  $t_{ds}(\text{host-output})$ ,  $t_{ss}(\text{host-output})$ ,  $t_{sd}(\text{host-output})$ ,  $t_{ddx}(\text{host-output})$ ,  $t_{dxdx}(\text{host-output})$ ,  $t_{dxs}(\text{host-output})$ , and  $t_{sdx}(\text{host-output})$ , respectively.

[00284] **Table IX**

Parameter	Description	Min.	Typ.	Max.	Units
$t_{dd}(\text{host-output})$	Data0 to Data0 transition	$t_{bit} - 0.5$	$t_{bit}$	$t_{bit} + 0.5$	nsec
$t_{ds}(\text{host-output})$	Data0 to Strobe transition	$t_{bit} - 0.8$	$t_{bit}$	$t_{bit} + 0.8$	nsec
$t_{ss}(\text{host-output})$	Strobe to Strobe transition	$t_{bit} - 0.5$	$t_{bit}$	$t_{bit} + 0.5$	nsec
$t_{sd}(\text{host-output})$	Strobe to Data0 transition	$t_{bit} - 0.8$	$t_{bit}$	$t_{bit} + 0.8$	nsec
$t_{ddx}(\text{host-output})$	Data0 to non-Data0 transition		$t_{bit}$		nsec
$t_{dxdx}(\text{host-output})$	non-Data0 to non-Data0 transition	$t_{bit} - 0.5$	$t_{bit}$	$t_{bit} + 0.5$	nsec
$t_{dxs}(\text{host-output})$	non-Data0 to Strobe transition		$t_{bit}$		nsec
$t_{sdx}(\text{host-output})$	Strobe to non-Data0 transition		$t_{bit}$		nsec

[00285] The typical MDDI timing requirements for the client receiver input for the same signals transferring data on the forward link is shown in Table X. Since the same signals are being discussed but time delayed, no new figure is needed to illustrate the signal characteristics or meaning of the respective labels, as would be understood by those skilled in the art.

[00286] Table X

Parameter	Description	Min.	Typ.	Max.	Units
$t_{dd}(\text{display-input})$	Data0 to Data0 transition	$t_{bit} - 1.0$	$t_{bit}$	$t_{bit} + 1.0$	nsec
$t_{ds}(\text{display-input})$	Data0 to Strobe transition	$t_{bit} - 1.5$	$t_{bit}$	$t_{bit} + 1.5$	nsec
$t_{ss}(\text{display-input})$	Strobe to Strobe transition	$t_{bit} - 1.0$	$t_{bit}$	$t_{bit} + 1.0$	nsec
$t_{sd}(\text{display-input})$	Strobe to Data0 transition	$t_{bit} - 1.5$	$t_{bit}$	$t_{bit} + 1.5$	nsec
$t_{ddx}(\text{host-output})$	Data0 to non-Data0 transition		$t_{bit}$		nsec
$t_{ddx}(\text{host-output})$	non-Data0 to non-Data0 transition		$t_{bit}$		nsec
$t_{dxs}(\text{host-output})$	non-Data0 to Strobe transition		$t_{bit}$		nsec
$t_{sdx}(\text{host-output})$	Strobe to non-Data0 transition		$t_{bit}$		nsec

[00287] FIGS. 45 and 46 illustrate the presence of a delay in response that can occur when the host disables or enables the host driver, respectively. In the case of a host forwarding certain packets, such as the Reverse Link Encapsulation Packet or the Round Trip Delay Measurement Packet, the host disables the line driver after the desired packets are forwarded, such as the Parameter CRC, Strobe Alignment, and All Zero packets illustrated in FIG. 45 as having been transferred. However, as shown in FIG. 45, the state of the line does not necessarily switch from '0' to a desired higher value instantaneously, although this is potentially achievable with certain control or circuit elements present, but takes a period of time termed the host Driver Disable Delay period to respond. While it could occur virtually instantly such that this time period is 0 nanoseconds (nsec.) in length, it could more readily extend over some longer period with 10 nsec. being a desired maximum period length, which occurs during the Guard Time 1 or Turn Around 1 packet periods.

[00288] Looking in FIG. 46, one sees the signal level change undergone when the host Driver is enabled for transferring a packet such as the Reverse Link Encapsulation Packet or the Round Trip Delay Measurement Packet. Here, after the Guard Time 2 or Turn Around 2 packet periods, the host driver is enabled and begins to drive a level, here '0', which value is approached or reached over a period of time termed the Host Driver Enable Delay period, which occurs during the Driver Re-enable period, prior to the first packet being sent.

[00289] A similar process occurs for the drivers and signal transfers for the client device, here a display. The general guidelines for the length of these periods, and their respective relationships are shown in Table XI, below.

[00290] **Table XI**

Description	Min.	Max.	Units
Host Driver Disable Delay	0	10	nsec
Host Driver Enable Delay	0	2.0	nsec
Display Driver Disable Delay	0	10	nsec
Display Driver Enable Delay	0	2.0	nsec

### C. Data-Strobe Timing Reverse Link

[00291] The switching characteristics and timing relationships for the data and strobe signals used to transfer data on the reverse link from the client driver output are shown in FIGS. 47, and 48. The typical times for certain signal transitions are discussed below. FIG. 47 illustrates the relationship at the host receiver input between the timing of the data being transferred and the leading and trailing edges of the strobe pulses. That is, what is referred to as the set-up time for the rising or leading edge of the strobe signals, tsu-sr and the set-up time for the trailing or falling edge of the strobe signals, tsu-sf. A typical length of time for these set-up periods is on the order of a minimum of 8 nanoseconds.

[00292] FIG. 48 illustrates the switching characteristics and corresponding client output delay developed by the reverse data timing. In FIG. 48, one can see the relationship between the timing of the data being transferred and the leading and trailing edges of the strobe pulses accounting for induced delay. That is, what is referred to as the propagation delay between the rising or leading edge of the strobe signals and the data (valid), tpd-sr, and the propagation delay between the data and the trailing or falling edge of the strobe signals, tpd-sf. A typical maximum length of time for these propagation delay periods is on the order of 8 nanoseconds.

## VIII. Implementation of Link Control (Link Controller Operation)

### A. State Machine Packet Processor

[00293] Packets being transferred over a MDDI link are dispatched very rapidly, typically at a rate on the order of 300 Mbps or more, such as 400 Mbps, although lower rates are certainly accommodated, as desired. This type of bus or transfer link speed is too great for currently commercially available (economical) general-purpose microprocessors or the like to control. Therefore, a practical implementation to accomplish this type of signal transfer is to utilize a programmable state machine to parse the input packet stream to produce packets that are transferred or redirected to the appropriate audio-visual subsystem for which they are intended. Such devices are well known and use circuits generally dedicated to a limited number of operations, functions, or states to achieve a desired high speed or very high speed operation.

[00294] General purpose controllers, processors, or processing elements, can be used to more appropriately act upon or manipulate some information such as control or status packets, which have lower speed demands. When those packets (control, status, or other pre-defined packets) are received, the state machine should pass them through a data buffer or similar processing element to the general-purpose processor so the packets can be acted upon to provide a desired result (effect) while the audio and visual packets are transferred to their appropriate destination for action. If future, microprocessors or other general purpose controllers, processors, or processing elements are manufactured to achieve higher data rate processing capabilities, then the states or state machine discussed below might also be implemented using software control of such devices, typically as programs stored on a storage element or media.

[00295] The general purpose processor function can be realized in some embodiments by taking advantage of the processing power, or excess cycles available for, microprocessors (CPUs) in computer applications, or controllers, processors, digital signal processors (DSPs), specialized circuits, or ASICs found in wireless devices, in much the same manner as some modems or graphics processors utilize the processing power of CPUs found in computers to perform some functions and reduce hardware complexity and costs. However, this cycle sharing or usage can negatively impact the processing speed, timing, or overall operation of such elements, so in many applications, dedicated circuits or elements are preferred for this general processing.

[00296] In order for image data to be viewed on a display (micro-display), or to reliably receive all packets sent by the host device, the display signal processing is synchronized with the forward link channel timing. That is, signals arriving at the display and the display circuits need to be substantially time synchronized for proper signal processing to occur. A high level diagram of states achieved by signal processing steps or a method by which such a synchronization can be implemented is presented in the illustration of FIG. 49. In FIG. 49, the possible forward link synchronization "states" for a state machine 4900 are shown being categorized as one ASYNC FRAMES STATE 4904, two ACQUIRING SYNC STATES 4902 and 4906, and three IN-SYNC STATES 4908, 4910, and 4912.

[00297] As shown by starting step or state 4902, the display or client, such as a presentation device, starts in a pre-selected "no sync" state, and searches for a unique word in the first sub-frame header packet that is detected. It is to be noted that this no sync state represents the minimum communication setting or "fall-back" setting in which a Type I interface is selected. When the unique word is found during the search, the display saves the sub-frame length field. There is no checking of the CRC bits for processing on this first frame, or until synchronization is obtained. If this sub-frame length is zero, then sync state processing proceeds accordingly to a state 4904 labeled here as the "async frames" state, which indicates that synchronization has not yet been achieved. This step in the processing is labeled as having encountered cond 3, or condition 3, in FIG. 49. Otherwise, if the frame length is greater than zero, then the sync state processing proceeds to a state 4906 where the interface state is set as "found one sync frame." This step in the processing is labeled as encountering cond 5, or condition 5, in FIG. 49. In addition, if the state machine sees a frame header packet and good CRC determination for a frame length greater than zero, processing proceeds to the "found one sync frame" state. This is labeled as meeting cond 6, or condition 6, in FIG. 49.

[00298] In each situation in which the system is in a state other than "no sync", when the unique word is detected and a good CRC result is determined for the sub-frame header packet, and the sub-frame length is greater than zero, then the interface state is changed to the "in-sync" state 4908. This step in the processing is labeled as having encountered cond 1, or condition 1, in FIG. 49. On the other hand, if either the unique word or the CRC in the sub-frame Header Packet are not correct, then the sync state processing proceeds or returns to the interface state 4902 of "NO SYNC FRAME" state. This



portion of the processing is labeled as encountering cond 2, or condition 2, in the state diagram of FIG. 49.

#### **B. Acquisition Time for Sync**

[00299] The interface can be configured to accommodate a certain number of "sync errors" prior to deciding that synchronization is lost and returning to the "NO SYNC FRAME" state. In FIG. 49, once the state machine has reached the "IN-SYNC STATE" and no errors are found, it is continuously encountering a cond 1 result, and remains in the "IN-SYNC" state. However once one cond 2 result is detected, processing changes the state to a "one-sync-error" state 4910. At this point, if processing results in detecting another cond 1 result, then the state machine returns to the "in-sync" state, otherwise it encounters another cond 2 result, and moves to a "TWO-SYNC-ERRORS" state 4912. Again, if a cond 1 occurs, processing returns the state machine to the "IN-SYNC" state. Otherwise, another cond 2 is encountered and the state machine returns to the "no-sync" state. It is also understandable that should the interface encounter a "link shutdown packet", then this will cause the link to terminate data transfers and return to the "no-sync frame" state as there is nothing to synchronize with, which is referred to as meeting cond 4, or condition 4, in the state diagram of FIG. 49.

[00300] It is understood that it is possible for there to be a repeating "false copy" of the unique word which may appear at some fixed location within the sub-frame. In that situation, it is highly unlikely that the state machine will synchronize to the sub-frame because the CRC on the sub-frame Header Packet must also be valid when processed in order for the MDD interface processing to proceed to the "IN SYNC" state.

[00301] The sub-frame length in the sub-frame Header Packet may be set to zero to indicate that the host will transmit only one sub-frame before the link is shut down, and the MDD interface is placed in or configured into an idle hibernation state. In this case, the display must immediately receive packets over the forward link after detecting the sub-frame Header Packet because only a single sub-frame is sent before the link transitions to the idle state. In normal or typical operations, the sub-frame length is non-zero and the display only processes forward link packets while the interface is in those states collectively shown as "IN-SYNC" states in FIG. 49.

[00302] The time required for a display to synchronize to the forward link signal is variable depending on the sub-frame size and the forward link data rate. The likelihood of detecting a "false copy" of the unique word as part of the random, or more random,

data in the forward link is greater when the sub-frame size is larger. At the same time, the ability to recover from a false detection is lower, and the time taken to do so is longer, when a forward link data rate is slower.

### **C. Initialization**

[00303] As stated earlier, at the time of "start-up", the host configures the forward link to operate at or below a minimum required, or desired, data rate of 1 Mbps, and configures the sub-frame length and media-frame rate appropriately for a given application. That is, both the forward and reverse links begin operation using the Type-I interface. These parameters are generally only going to be used temporarily while the host determines the capability or desired configuration for the client display (or other type of client device). The host sends or transfers a sub-frame Header Packet over the forward link followed by a Reverse Link Encapsulation Packet which has bit '0' of the Request Flags set to a value of one (1), in order to request that the display or client responds with a Display Capability Packet. Once the display acquires synchronization on (or with) the forward link, it sends a Display Capability Packet and a Display Request and Status Packet over the reverse link or channel.

[00304] The host examines the contents of the Display Capability Packet in order to determine how to reconfigure the link for optimal or a desired level of performance. The host examines the Protocol Version and Minimum Protocol Version fields to confirm that the host and display use versions of the protocol that are compatible with each other. The protocol versions generally remain as the first two parameters of the display capability Packet so that compatibility can be determined even when other elements of the protocol might not be compatible or completely understood as being compatible.

### **D. CRC Processing**

[00305] For all packet types, the packet processor state machine ensures that the CRC checker is controlled appropriately or properly. It also increments a CRC error counter when a CRC comparison results in one or more errors being detected, and it resets the CRC counter at the beginning of each sub-frame being processed.

### E. Alternative Loss Of Synchronization Check

[00306] While the above series of steps or states work to produce higher data rates or throughput speed, Applicants have discovered that an alternative arrangement or change in the conditions the client uses to declare that there is a loss of synchronization with the host, can be used effectively to achieve even higher data rates or throughput. The new inventive embodiment has the same basic structure, but with the conditions for changing states changed. Additionally a new counter is implemented to aid in making checks for sub-frame synchronization. These steps and conditions are presented relative to FIG. 63, which illustrates a series of states and conditions useful in establishing the operations of the method or state machine. Only the "ACQUIRING-SYNC STATES" and "IN-SYNC STATES" portions are shown for clarity. In addition, since the resulting states are substantially the same, as is the state machine itself, they use the same numbering. However, the conditions for changing states (and the state machine operation) vary somewhat, so that all are renumbered for clarity between the two figures (1, 2, 3, 4, 5, and 6, versus 61, 62, 63, 64, and 65), as a convenience in identifying differences. Since the ASYNC FRAME state is not considered in this discussion, one state (4904) and condition (6) are no longer used in the figure.

[00307] In FIG. 63, the system or client (for display or presentation) starts with state machine 5000 in the pre-selected "no sync" state 4902, as in FIG. 49. The first state change for changing states from the no-sync condition 4902 is in condition 64 which is the discovery of the sync pattern. Assuming that the CRC of the sub-frame header also passes on this packet (meets condition 61), the state of the packet processor state machine can be changed to the in-sync state 4908. A sync error, condition 62, will cause the state machine to shift to state 4910, and a second occurrence to state 4912. However, it has been discovered that any CRC failure of an MDDI packet will cause the state machine to move out of in-sync state 4908, to the one sync error state 4910. Another CRC failure of any MDDI packet will cause a move to the two sync failure state 4912. A packet decoded with a correct CRC value will cause the state machine to return to the in-sync state 4908.

[00308] What has been changed is to utilize the CRC value or determination for 'every' packet. That is, to have the state machine look at the CRC value for every packet to determine a loss of synchronization instead of just observing sub-frame header packets.

In this configuration or process, a loss of synchronization is not determined using the unique word and just sub-frame header CRC values.

[00309] This new interface implementation allows the MDD interface link to recognize synchronization failures much more quickly, and, therefore, to recover from them more quickly, as well.

[00310] To make this system more robust, the client should also add or utilize a sub-frame counter. The client then checks for the presence of the unique word at the time it is expected to arrive or occur in a signal. If the unique word does not occur at the correct time, the client can recognize that a synchronization failure has occurred much more quickly than if it had to wait several (here three) packet times or periods that were greater than a sub-frame length. If the test for the unique word indicates it is not present, in other words that the timing is incorrect, then the client can immediately declare a link loss of synchronization and move to the no-sync state. The process of checking for the proper unique word presence, adds a condition 65 (cond 65) to the state machine saying that the unique word is incorrect. If a sub-frame packet is expected to be received on the client and doesn't match up, the client can immediately go to the no-sync state 4902, saving additional time waiting for multiple sync errors (condition 62) normally encountered traversing through states 4910 and 4912.

[00311] This change uses an additional counter or counting function in the client core to count sub-frame length. In one embodiment, a count down function is used and the transfer of any packet that was currently being processed is interrupted to check for the sub-frame unique word if the counter has expired. Alternatively, the counter can count up, with the count being compared to a desired maximum or particular desired value, at which point the current packet is checked. This process protects the client from decoding packets that are incorrectly received on the client with extraordinarily long packet lengths. If the sub-frame length counter needed to interrupt some other packet that was being decoded, a loss of synchronization can be determined since no packet should cross a sub-frame boundary.

## **IX. Packet Processing**

[00312] For each type of packet discussed above that the state machine receives, it undertakes a particular processing step or series of steps to implement operation of the interface. Forward link packets are generally processed according to the exemplary processing listed in Table XII below.

[00313] **Table XII**

<i>Packet type</i>	<i>Packet processor state machine response</i>
Sub-Frame Header (SH)	Confirms good packet, captures sub-frame length field, and sends packet parameters to a general purpose processor.
Filler (F)	Ignores data.
Video Stream (VS)	Interprets the Video Data Format Descriptor and other parameters, unpacks packed pixel data when necessary, translates pixels through the color map if necessary, and writes pixel data to appropriate locations in the bitmap.
Audio Stream (AS)	Sends audio sample rate setting to audio sample clock generator, separates audio samples of specified size, unpacks audio sample data when necessary, and routes audio samples to appropriate audio sample FIFO
Color Map (CM)	Reads color map size and offset parameters, and writes the color map data to a color map memory or storage location.
Reverse Link Encapsulation (REL)	Facilitates sending packets in reverse direction at the appropriate time. Reverse link flags are examined, and Display Capability packets are sent as necessary. Display Request and Status packets are also sent as appropriate.
Display Capability (DC)	Sends this type of packet when requested by a host using the reverse link flags field of the Reverse Link Encapsulation Packet.
Keyboard (K)	Passes these packets to and from a general purpose processor that communicates with a keyboard type device, if one is present, and use is desired.
Pointing Device (PD)	Passes these packets to and from a general purpose processor that communicates with a pointing type device, if one is present, and use is desired.
Link Shutdown (LS)	Records fact link is shut down and informs a general-purpose processor.
Display Service Request and Status (DSRS)	Sends this packet as the first packet in the Reverse Link Encapsulation packet.
Bit Block Transfer (BPT)	Interprets packet parameters, such as Video Data Format Descriptor, determines which pixels to move first, and moves pixels in bitmap as required.

<i>Packet type</i>	<i>Packet processor state machine response</i>
Bitmap Area Fill (BAF)	Interprets packet parameters, translates pixels through color map if necessary, and writes pixel data to appropriate locations in bitmap.
Bitmap Pattern Fill (BPF)	Interprets packet parameters, unpacks packed pixel data if necessary, translates pixels through color map if necessary, and writes pixel data to appropriate locations in bitmap.
Communication Link Channel (CLC)	Sends this data directly to a general-purpose processor.
Display Service Request (DSR) during hibernation	General-purpose processor controls the low-level functions of sending request and detects contention with link restarting on its own.
Interface Type Handoff Request (ITHR) and Interface Type Acknowledge (ITA)	May pass these packets to and from the general-purpose processor. The logic to receive this type of packet and formulate a response with an acknowledgment is substantially minimal. Therefore, this operation could also be implemented within the packet processor state machine. The resulting handoff occurs as a low-level physical layer action and is not likely to affect the functionality or functioning of the general-purpose processor.
Perform Type Handoff (PTH)	May act on such packets either directly or by transferring them to the general-purpose processor, also commanding hardware to undergo a mode change.

#### X. Reducing the Reverse Link Data Rate

[00314] It has been observed by the inventors that certain parameters used for the host link controller can be adjusted or configured in a certain manner in order to achieve a maximum or more optimized (scale) reverse link data rate, which is very desirable. For example, during the time used to transfer the Reverse Data Packets field of the Reverse Link Encapsulation Packet, the MDDI\_Stb signal pair toggles to create a periodic data clock at half the forward link data rate. This occurs because the host link controller generates the MDDI\_Stb signal that corresponds to the MDDI\_Data0 signal as if it were sending all zeroes. The MDDI\_Stb signal is transferred from the host to a client where it is used to generate a clock signal for transferring reverse link data from the display, with which reverse data is sent back to the host. An illustration of typical amounts of delay encountered for the signal transfer and processing on the forward and reverse

paths in a system employing the MDDI, is shown in FIG. 50. In FIG. 50, a series of delay values 1.5 nsec., 8.0 nsec., 2.5 nsec., 2.0 nsec., 1.0 nsec., 1.5 nsec., 8.0 nsec., and 2.5 nsec., are shown near processing portions for the Stb+/- generation, cable transfer-to-display, display receiver, clock generation, signal clocking, Data0+/- generation, cable transfer-to-host, and host receiver stages, respectively.

[00315] Depending on the forward link data rate and signal processing delays encountered, it may require more time than one cycle on the MDDI\_Stb signal for this "round trip" effect or set of events to be completed, which results in the consumption undesirable amounts of time or cycles. To circumvent this problem, the Reverse Rate Divisor makes it possible for one bit time on the reverse link to span multiple cycles of the MDDI\_Stb signal. This means that the reverse link data rate is less than the forward link rate.

[00316] It should be noted that the actual length of signal delays through the interface may differ depending on each specific host-client system or hardware being used. Although not required, each system can generally be made to perform better by using the Round Trip Delay Measurement Packet to measure the actual delay in a system so that the Reverse Rate Divisor can be set to an optimum value.

[00317] A round-trip delay is measured by having the host send a Round Trip Delay Measurement Packet to the display. The display responds to this packet by sending a sequence of ones back to the host inside of, or during, a pre-selected measurement window in that packet called the Measurement Period field. The detailed timing of this measurement was described previously. The round-trip delay is used to determine the rate at which the reverse link data can be safely sampled.

[00318] The round-trip delay measurement consists of determining, detecting, or counting the number of forward link data clock intervals occurring between the beginning of the Measurement Period field and the beginning of the time period when the 0xff, 0xff, 0x00 response sequence is received back at the host from the client. Note that it is possible that the response from the client could be received a small fraction of a forward link clock period before the measurement count was about to increment. If this unmodified value is used to calculate the Reverse Rate Divisor it could cause bit errors on the reverse link due to unreliable data sampling. An example of this situation is illustrated in FIG. 51, where signals representing MDDI\_Data at host, MDDI\_Stb at host, forward link data clock inside the host, and a Delay Count are illustrated in graphical form. In FIG. 51, the response sequence was received from the display a

fraction of a forward link clock period before the Delay Count was about to increment from 6 to 7. If the delay is assumed to be 6, then the host will sample the reverse data just after a bit transition or possibly in the middle of a bit transition. This could result in erroneous sampling at the host. For this reason, the measured delay should typically be incremented by one before it is used to calculate the Reverse Rate Divisor.

[00319] The Reverse Rate Divisor is the number of MDDI\_Stb cycles the host should wait before sampling the reverse link data. Since MDDI\_Stb is cycled at a rate that is one half of the forward link rate, the corrected round-trip delay measurement needs to be divided by 2 and then rounded up to the next integer. Expressed as a formula, this relationship is:

$$reverse\_rate\_divisor = RoundUpToNextInteger\left(\frac{round\_trip\_delay + 1}{2}\right)$$

For the example given, this becomes:

$$reverse\_rate\_divisor = RoundUpToNextInteger\left(\frac{6 + 1}{2}\right) = 4$$

[00320] If the round trip delay measurement used in this example were 7 as opposed to 6, then the Reverse Rate Divisor would also be equal to 4.

[00321] The reverse link data is sampled by the host on the rising edge of the Reverse Link Clock. There is a counter or similar known circuit or device present in both the host and client (display) to generate the Reverse Link Clock. The counters are initialized so that the first rising edge of the Reverse Link Clock occurs at the beginning of the first bit in the Reverse Link Packets field of the Reverse Link Encapsulation packet. This is illustrated, for the example given below, in FIG. 52. The counters increment at each rising edge of the MDDI\_Stb signal, and the number of counts occurring until they wrap around is set by the Reverse Rate Divisor parameter in the Reverse Link Encapsulation Packet. Since the MDDI\_Stb signal toggles at one half of the forward link rate, then the reverse link rate is one half of the forward link rate divided by the Reverse Rate Divisor. For example, if the forward link rate is 200 Mbps and the Reverse Rate Divisor is 4 then the reverse link data rate is expressed as:



$$\frac{1}{2} \cdot \frac{200Mbps}{4} = 25Mbps$$

[00322] An example showing the timing of the MDDI\_Data0 and MDDI\_Stb signal lines in a Reverse Link Encapsulation Packet is shown in FIG. 52, where the packet parameters used for illustration have the values:

Packet Length = 1024 (0x0400)      Turn Around 1 Length = 1

Packet Type = 65 (0x41)      Turn Around 2 Length = 1

Reverse Link Flags = 0      Reverse Rate Divisor = 2

Parameter CRC = 0xdb43      All Zero is 0x00

Packet data between the Packet Length and Parameter CRC fields is:

0x00, 0x04, 0x41, 0x00, 0x02, 0x01, 0x01, 0x43, 0xdb, 0x00, ...

[00323] The first reverse link packet returned from the display is the Display Request and Status Packet having a Packet Length of 7 and a packet type of 70. This packet begins with the byte values 0x07, 0x00, 0x46, ... and so forth. However, only the first byte (0x07) is visible in FIG. 52. This first reverse link packet is time-shifted by nearly one reverse link clock period in the figure to illustrate an actual reverse link delay. An ideal waveform with zero host to display round-trip delay is shown as a dotted-line trace.

[00324] The MS byte of the Parameter CRC field is transferred, preceded by packet type, then the all zero field. The strobe from the host is switching from one to zero and back to one as the data from the host changes level, forming wider pulses. As the data goes to zero, the strobe switches at the higher rate, only the change in data on the data line causes a change near the end of the alignment field. The strobe switches at the higher rate for the remainder of the figure due to the fixed 0 or 1 levels of the data signal for extended periods of time, and the transitions falling on the pulse pattern (edge).

[00325] The reverse link clock for the host is at zero until the end of the Turn Around 1 period, when the clock is started to accommodate the reverse link packets. The arrows in the lower portion of the figure indicate when the data is sampled, as would be apparent from the remainder of the disclosure. The first byte of the packet field being transferred (here 11000000) is shown commencing after Turn Around 1, and the line

level has stabilized from the host driver being disabled. The delay in the passage of the first bit, and as seen for bit three, can be seen in the dotted lines for the Data signal.

[00326] In FIG. 53, one can observe typical values of the Reverse Rate Divisor based on the forward link data rate. The actual Reverse Rate Divisor is determined as a result of a round-trip link measurement to guarantee proper reverse link operation. A first region 5302 corresponds to an area of safe operation, a second region 5304 corresponds to an area of marginal performance, while a third region 5306 indicates settings that are unlikely to function properly.

[00327] The round-trip delay measurement and Reverse Rate Divisor setting are the same while operating with any of the Interface Type settings on either the forward or reverse link because they are expressed and operated on in terms of units of actual clock periods rather than numbers of bits transmitted or received.

#### **XI. Turn-Around and Guard Times**

[00328] As discussed earlier, the Turn Around 1 field in the Reverse Link Encapsulation Packet and the Guard Time 1 field in the Round Trip Delay Measurement Packet designate values for lengths of time that allow for the host interface drivers to be disabled before the display interface drivers are enabled. Turn Around 2 and Guard Time 2 fields provide time values which allow the display drivers to be disabled before the host drivers are enabled. The Guard Time 1 and Guard Time 2 fields are generally filled with pre-set or pre-selected values for lengths that are not meant to be adjusted. Depending on the interface hardware being used, these values may be developed using empirical data and adjusted in some instances to improve operation.

[00329] Several factors contribute to a determination of the length of Turn Around 1 and these are the forward link data rate, and the maximum disable time of the MDDI\_Data drivers in the host. The maximum host driver disable time is specified in Table XI, where it shows that the drivers take about 10 nsec. maximum to disable and about 2 nsec. to enable. The minimum number of forward link clocks required for the host driver to be disabled is expressed according to the relationship:

$$Clocks\_to\_disable_{TA1} = \frac{ForwardLinkDataRate}{InterfaceTypeFactor_{FWD}} \cdot HostDriverDisableDelay_{max}$$

[00330] The allowed value range of Turn Around 1 is expressed according to the relationship:

$$Turn\_Around\_1 \geq RoundUpToNextInteger \left( \frac{Clocks\_to\_disable_{TA1}}{8} \cdot InterfaceTypeFactor_{FWD} \right)$$

[00331] where the Interface Type Factor is 1 for Type-I, 2 for Type-II, 4 for Type-III, and 8 for Type-IV.

[00332] Combining the two equations from above, one can see that the Interface Type Factor term cancels out, and Turn Around 1 is defined as:

$$Turn\_Around\_1 = RoundUpToNextInteger \left( \frac{ForwardLinkDataRate \cdot HostDriverDisableDelay_{max}}{8} \right)$$

[00333] For example, a 1500 Mbps Type-III forward link would use a Turn Around 1 delay of:

$$Turn\_Around\_1 = RoundUpToNextInteger \left( \frac{1500Mbps \cdot 10nsec}{8} \right) = 2Bytes$$

[00334] As the round trip delay increases, the timing margin improves from the point in time when the host is disabled to the time the display is enabled.

[00335] The factors that determine the length of time generally used for Turn Around 2 are the forward link data rate, the maximum disable time of the MDDI\_Data drivers in the display, and the round-trip delay of the communication link. The calculation of the time required to disable the display driver is essentially the same as that for the host driver discussed above, and is defined according to the relationship:

$$Clocks\_to\_disable_{TA2} = \frac{ForwardLinkDataRate}{InterfaceTypeFactor_{FWD}} \cdot DisplayDriverDisableDelay_{max}$$

and the allowed value range for Turn Around 2 is expressed as:

$$Turn\_Around\_2 \geq RoundUpToNextInteger \left( \frac{Clocks\_to\_disable_{TA2} + round\_trip\_delay + 1}{\left( \frac{8}{InterfaceTypeFactor_{FWD}} \right)} \right)$$

[00336] For example, a 1500 Mbps Type-III forward link with a round-trip delay of 10 forward link clocks typically uses a Turn Around 2 delay on the order of:

$$Clocks\_to\_disable_{TA2} = \frac{1500Mbps}{4} \cdot 10nsec = 3.75$$

$$Turn\_Around\_2 \geq RoundUpToNextInteger \left( \frac{3.75 + 10 + 1}{\left( \frac{8}{4} \right)} \right) = 8$$

## XII. Alternative Reverse Link Timing

[00337] While the use of timing and guard bands discussed above work to achieve a high data transfer rate interface, the inventors have discovered a technique to allow for reverse bit lengths that are shorter than the round trip time, by changing the reverse timing discovery.

[00338] As presented above, the previous approach to the timing of the reverse link is configured such that the number of clock cycles is counted from the last bit of the Guard Time 1 of a reverse timing packet until the first bit is sampled on the rising edge of an IO clock. That is the clock signal(s) used to time the inputs and outputs for the MDD interface. The calculation for the reverse rate divisor is then given by:

$$reverse\_rate\_divisor = RoundUpToNextInteger \left( \frac{round\_trip\_delay + 1}{2} \right)$$

[00339] This provides a bit width equal to the round trip delay which results in a very reliable reverse link. However, the reverse link has been shown to be capable of running faster, or at a higher data transfer rate, which the inventors want to take

advantage of. A new inventive technique allows utilizing additional capabilities of the interface to reach higher speeds.

[00340] This is accomplished by having the host count the number of clock cycles until a one is sampled, but with the host sampling the data line on both the rising and falling edges during the reverse timing packet. This allows the host to pick the most useful or even optimal sampling point within the reverse bit to ensure that the bit is stable. That is, to find the most useful or optimal rising edge to sample data on for reverse traffic reverse encapsulation packets. The optimal sampling point depends on both the reverse link divisor and whether the first one was detected on a rising edge or a falling edge. The new timing method allows the host to just look for the first edge of the 0xFF 0xFF 0x00 pattern sent by the client for reverse link timing to determine where to sample in a reverse encapsulation packet.

[00341] Examples of the arriving reverse bit and how that bit would look for various reverse rate divisors, is illustrated in FIG. 64, along with a number of clock cycles that have occurred since the last bit of Guard Time 1. In Fig. 64, one can see that if the first edge occurs between a rising and falling edge (labeled as rise/fall), the optimal sampling point for a reverse rate divisor of one, the optimal sample point is a clock cycle edge labeled 'b', as that is the only rising edge occurring within the period of the reverse bit. For a reverse rate divisor of two, the optimal sampling point is probably still clock cycle leading edge 'b' as cycle edge 'c' is closer to a bit edge than 'b'. For a reverse rate divisor of four, the optimal sampling point is probably clock cycle edge 'd', as it is closer to the back edge of the reverse bit where the value has probably stabilized.

[00342] Returning to FIG. 64, if, however, the first edge occurs between a falling and rising edge (labeled as fall/rise), the optimal sampling point for a reverse rate divisor of one is sampling point clock cycle edge 'a', as that is the only rising edge within the reverse bit time period. For a reverse rate divisor of two, the optimal sampling point is edge 'b', and for a reverse rate divisor of four the optimal sampling point is edge 'c'.

[00343] One can see that as the reverse rate divisors get larger and larger, the optimal sampling point becomes easier to ascertain or select, as it should be the rising edge that is closest to the middle.

[00344] The host can use this technique to find the number of rising clock edges before the rising data edge of the timing packet data is observed on the data line. It can then decide, based on whether the edge occurs between a rising and falling edge or between a falling and rising edge, and what the reverse rate divisor is, how many additional clock

cycles to add to a number counter, to reasonably ensure that the bit is always sampled as close to the middle as possible.

[00345] Once the host has selected or determined the number of clock cycles, it can "explore" various reverse rate divisors with the client to determine if a particular reverse rate divisor will work. The host (and client) can start with a divisor of one and check the CRC of the reverse status packet received from the client to determine if this reverse rate functions appropriately to transfer data. If the CRC is corrupt, there is probably a sampling error, and the host can increase the reverse rate divisor and try to request a status packet again. If the second requested packet is corrupt, the divisor can be increased again and the request made again. If this packet is decoded correctly, this reverse rate divisor can be used for all future reverse packets.

[00346] This method is effective and useful because the reverse timing should not change from the initial round trip timing estimate. If the forward link is stable, the client should continue to decode forward link packets even if there are reverse link failures. Of course, it is still the responsibility of the host to set a reverse link divisor for the link, since this method does not guarantee a perfect reverse link. In addition, the divisor will depend primarily on the quality of the clock that is used to generate an IO clock. If that clock has a significant amount of jitter, there is a greater possibility of a sampling error. This error probability increases with the amount of clock cycles in the round trip delay.

[00347] This implementation appears to work best for Type-I reverse data, but may present problems for Type-II through Type-IV reverse data due to the skew between data lines potentially being too great to run the link at the rate that works best for just one data pair. However, the data rate probably does not need to be reduced to the previous method even with Type-II through Type-IV for operation. This method may also work best if duplicated on each data line to select the ideal or an optimal clock sample location. If they are at the same sample time for each data pair, this method would continue to work. If they are at different sample periods, two different approaches may be used. The first is to select an desired or more optimized sample location for each data point, even if it is not the same for each data pair. The host can then reconstruct the data stream after sampling all of the bits from the set of data pairs: two bits for Type-II, four bits for Type-III, and eight bits for Type-IV. The other option is for the host to increase the reverse rate divisor such that the data bits for every data pair can be sampled at the same clock edge.

### XIII. Effects of Link Delay and Skew

[00348] Delay skew on the forward link between the MDDI\_Data pairs and MDDI\_Stb can limit the maximum possible data rate unless delay skew compensation is used. The differences in delay that cause timing skew are due to the controller logic, the line drivers and receivers, and the cable and connectors as outlined below.

#### A. Link Timing Analysis Limited by Skew (MDDI Type-I)

##### 1. Delay and Skew Example of a Type-I Link

[00349] A typical interface circuit similar to that shown in FIG. 41, is shown in FIG. 57 for accommodating a Type-I interface link. In FIG. 57, exemplary or typical values for propagation delay and skew are shown for each of several processing or interface stages of an MDDI Type-I forward link. Skew in the delay between MDDI\_Stb and MDDI\_Data0 causes the duty-cycle of the output clock to be distorted. Data at the D input of the receiver flip-flop (RXFF) stage using flip-flops 5728, 5732, must change slightly after the clock edge so that it can be sampled reliably. The figure shows two cascaded delay lines 5732a and 5732b being used to solve two different problems with creating this timing relationship. In the actual implementation these may be combined into a single delay element.

[00350] Data, Stb, and Clock Recovery Timing on a Type-I Link for exemplary signal processing through the interface are illustrated in FIG. 58.

[00351] The total delay skew that is significant generally arises or comes from the sum of the skew in the following stages: transmitter flip-flop (TXFF) with flip-flops 5704, 5706; transmitter driver (TXDRVR) with drivers 5708, 5710; the CABLE 5702; receiver line receiver (RXRCVR) with receivers 5722, 5724; and receiver XOR logic (RXXOR). Delay 5732a should match or exceed the delay of the XOR gate 5736 in the RXXOR stage which is determined by the relationship:

$$t_{PD - \min( \text{ Delay } 1 )} \geq t_{PD - \max( \text{ XOR } )}$$

[00352] It is desirable to meet this requirement so that the D input of receiver flip-flop 5728, 5732 does not change before its clock input. This is valid if the hold-time of RXFF is zero.

[00353] The purpose or function of Delay2 is to compensate for the hold-time of the RXFF flip-flop according to the relationship:

$$t_{PD-min}(Delay2) = t_{H(RXFF)}$$

[00354] In many systems this will be zero because the hold time is zero, and of course in that case the maximum delay of Delay2 can also be zero.

[00355] The worst-case contribution to skew in the receiver XOR stage is in the data-late/strobe-early case where Delay1 is at a maximum value and the clock output from the XOR gate comes as early as possible according to the relationship:

$$t_{SKEW-max(RXXOR)} = t_{PD-max}(Delay1) - t_{PD-min}(XOR)$$

[00356] In this situation, the data may change between two bit periods, n and n+1, very close to the time where bit n+1 is clocked into the receiver flip-flop.

[00357] The maximum data rate (minimum bit period) of an MDDI Type-I link is a function of the maximum skew encountered through all the drivers, cable, and receivers in the MDDI link plus the total data setup into the RXFF stage. The total delay skew in the link up to the output of the RXRCVR stage can be expressed as:

$$t_{SKEW-max(LINK)} = t_{SKEW-max(TXFF)} + t_{SKEW-max(TXDRVR)} + t_{SKEW-max(CABLE)} + t_{SKEW-max(RXRCVR)}$$

and the minimum bit period is given by:

$$t_{BIT-min} = t_{SKEW-max(LINK)} + t_{SKEW-max(RXXOR)} + t_{PD-max}(Delay2) + t_{SU(RXFF)}$$

[00358] In the example shown in FIG. 57,  $t_{SKEW-max(LINK)} = 1.4$  nsec and the minimum bit period can be expressed as:



$$t_{BIT-min} = 1.4 + 0.3 + 0.2 + 0.5 = 2.4nsec, \text{ or stated as approximately 416 Mbps.}$$

### B. Link Timing Analysis for MDDI Type-II, III, and IV

[00359] A typical interface circuit similar to that shown in FIGS. 41 and 57, is shown in FIG. 59 for accommodating Type-II, III, and IV interface links. Additional elements are used in the TXFF (5904), TXDRVR (5908), RXRCVCR (5922), and RXFF (5932, 5928, 5930) stages to accommodate the additional signal processing. In FIG. 59, exemplary or typical values for propagation delay and skew are shown for each of several processing or interface stages of an MDDI Type-II forward link. In addition to skew in the delay between MDDI\_Stb and MDDI\_Data0 affecting the duty-cycle of the output clock, there is also skew between both of these two signals and the other MDDI\_Data signals. Data at the D input of the receiver flip-flop B (RXFFB) stage consisting of flip-flops 5928 and 5930, is changed slightly after the clock edge so it can be sampled reliably. If MDDI\_Data1 arrives earlier than MDDI\_Stb or MDDI\_Data0 then MDDI\_Data1 should be delayed to be sampled by at least the amount of the delay skew. To accomplish this, data is delayed using the Delay3 delay line. If MDDI\_Data1 arrives later than MDDI\_Stb and MDDI\_Data0 and it is also delayed by Delay3 then the point where MDDI\_Data1 changes is moved closer to the next clock edge. This process determines an upper limit of the data rate of an MDDI Type-II, III, or IV link. Some exemplary different possibilities for the timing or skew relationship of two data signals and MDDI\_Stb with respect to each other is illustrated in FIGS. 60A, 60B, and 60C.

[00360] In order to sample data reliably in RXFFB when MDDI\_DataX arrives as early as possible, Delay3 is set according to the relationship:

$$t_{PD-min(Delay3)} \geq t_{SKEW-max(LINK)} + t_{H(RXFFB)} + t_{PD-max(XOR)}$$

[00361] The maximum link speed is determined by the minimum allowable bit period. This is most affected when MDDI\_DataX arrives as late as possible. In that case, the minimum allowable cycle time is given by:

$$t_{BIT-min} = t_{SKEW-max(LINK)} + t_{PD-max(Delay3)} + t_{SU(RXFFB)} - t_{PD-min(XOR)}$$

The upper bound of link speed is then:

$$t_{PD-\max(Delay3)} = t_{PD-\min(Delay3)}$$

and given that assumption:

$$t_{BIT-\min(lower-bound)} = 2 \cdot t_{SKEW-\max(LINK)} + t_{PD-\max(XOR)} + t_{SU(RXPFB)} + t_{H(RXPFB)}$$

[00362] In the example given above, the lower bound of the minimum bit period is given by the relationship:

$$t_{BIT-\min(lower-level)} = 2 \cdot 1.4 + 1.5 + 0.5 + 0.1 = 4.8n\text{ sec, which is approximately 208 Mbps.}$$

[00363] This is much slower than the maximum data rate that can be used with a Type-I link. The automatic delay skew compensation capability of MDDI significantly reduces the affect that delay skew has on the maximum link rate

#### XIV. Physical Layer Interconnection Description

[00364] Physical connections useful for implementing an interface according to the present invention can be realized using commercially available parts such as part number 3260-8S2(01) as manufactured by Hirose Electric Company Ltd. on the host side, and part number 3240-8P-C as manufactured by Hirose Electric Company Ltd. on the display device side. An exemplary interface pin assignment or "pinout" for such connectors used with a Type-I/Type-II interfaces is listed in Table XIII, and illustrated in FIG. 61.

[00365] **Table XIII**

Signal Name	Pin Number	Color	Signal Name	Pin Number	Color
MDDI_Pwr	1	Red	MDDI_Gnd	2	Black paired w/Red
MDDI_Stb+	3	Green	MDDI_Stb-	4	Black paired w/Green
MDDI_Data0+	5	Blue	MDDI_Data0-	6	Black paired w/Blue
MDDI_Data1+	7	White	MDDI_Data1-	8	Black paired w/White
			Shield		

[00366] The shield is connected to the MDDI\_Gnd in the host interface, and a shield drain wire in the cable is connected to the shield of the display connector. However, the shield and drain wire are not connected to the circuit ground inside of a display.

[00367] Interconnection elements or devices are chosen or designed in order to be small enough for use with mobile communication and computing devices, such as PDAs and wireless telephones, or portable game devices, without being obtrusive or unaesthetic in comparison to relative device size. Any connectors and cabling should be durable enough for use in the typical consumer environment and allow for small size, especially for the cabling, and relatively low cost. The transfer elements should accommodate data and strobe signals that are differential NRZ data having a transfer rate up to around 450 Mbps for Type I and Type II and up to 3.6 Gbps for the 8-bit parallel Type IV version.

## **XV. Operation**

[00368] A summary of the general steps undertaken in processing data and packets during operation of an interface using embodiments of the invention is shown in FIGS. 54A and 54B, along with an overview of the interface apparatus processing the packets in FIG. 55. In these figures, the process starts in a step 5402 with a determination as to whether or not the client and host are connected using a communication path, here a cable. This can occur through the use of periodic polling by the host, using software or hardware that detects the presence of connectors or cables or signals at the inputs to the host (such as is seen for USB interfaces), or other known techniques. If there is no client connected to the host, then it can simply enter a wait state of some predetermined length, depending upon the application, go into a hibernation mode, or be inactivated to await future use which might require a user to take action to reactivate the host. For example, when a host resides on a computer type device, a user might have to click on a screen icon or request a program that activates the host processing to look for the client. Again, simple plug in of a USB type connection, such as used for the Type-U interface, could activate host processing, depending on the capabilities and configuration of the host or resident host software.

[00369] Once a client is connected to the host, or visa versa, or detected as being present, either the client or the host sends appropriate packets requesting service in steps 5404 and 5406. The client could send either Display Service Request or Status packets in step 5404. It is noted that the link, as discussed above, could have been previously shut

down or be in hibernation mode so this may not be a complete initialization of the communication link that follows. Once the communication link is synchronized and the host is trying to communicate with the client, the client also provides a Display Capabilities packet to the host, as in step 5408. The host can now begin to determine the type of support, including transfer rates, the client can accommodate.

[00370] Generally, the host and client also negotiate the type (rate/speed) of service mode to be used, for example Type I, Type U, Type II, and so forth, in a step 5410. Once the service type is established the host can begin to transfer information. In addition, the host may use Round Trip Delay Measurement Packets to optimize the timing of the communication links in parallel with other signal processing, as shown in step 5411.

[00371] As stated earlier, all transfers begin with a Sub-Frame Header Packet, shown being transferred in step 5412, followed by the type of data, here video and audio stream packets, and filler packets, shown being transferred in step 5414. The audio and video data will have been previously prepared or mapped into packets, and filler packets are inserted as needed or desired to fill out a required number of bits for the media frames. The host can send packets such as the Forward Audio Channel Enable Packets to activate sound devices. In addition, the host can transfer commands and information using other packet types discussed above, here shown as the transfer of Color Map, Bit Block Transfer or other packets in step 5416. Furthermore, the host and client can exchange data relating to a keyboard or pointing devices using the appropriate packets.

[00372] During operation, one of several different events can occur which lead to the host or client desiring a different data rate or type of interface mode. For example, a computer or other device communicating data could encounter loading conditions in processing data that causes a slow down in the preparation or presentation of packets. A display receiving the data could change from a dedicated AC power source to a more limited battery power source, and either not be able to transfer in data as quickly, process commands as readily, or not be able to use the same degree of resolution or color depth under the more limited power settings. Alternatively, a restrictive condition could be abated or disappear allowing either device to transfer data at higher rates. This being more desirable, a request can be made to change to a higher transfer rate mode.

[00373] If these or other types of known conditions occur or change, either the host or client may detect them and try to renegotiate the interface mode. This is shown in step 5420, where the host sends Interface Type Handoff Request Packets to the client

requesting a handoff to another mode, the client sends Interface Type Acknowledge Packets confirming a change is sought, and the host sends Perform Type Handoff Packets to make the change to the specified mode.

[00374] Although, not requiring a particular order of processing, the client and host can also exchange packets relating to data intended for or received from pointing devices, keyboards, or other user type input devices associated primarily with the client, although such elements may also be present on the host side. These packets are typically processed using a general processor type element and not the state machine (5502). In addition, some of the commands discussed above will also be processed by the general processor. (5504, 5508)

[00375] After data and commands have been exchanged between the host and client, at some point a decision is made as to whether or not additional data is to be transferred or the host or client is going to cease servicing the transfer. This is shown in step 5422. If the link is to enter either a hibernation state or be shut down completely, the host sends a Link Shutdown packet to the client, and both sides terminate the transfer of data.

[00376] The packets being transferred in the above operations processing will be transferred using the drivers and receivers previously discussed in relation to the host and client controllers. These line drivers and other logic elements are connected to the state machine and general processors discussed above, as illustrated in the overview of FIG. 55. In Fig. 55, a state machine 5502 and general processors 5504 and 5508 may further be connected to other elements not shown such as a dedicated USB interface, memory elements, or other components residing outside of the link controller with which they interact, including, but not limited to, the data source, and video control chips for view display devices.

[00377] The processors, and state machine provide control over the enabling and disabling of the drivers as discussed above in relation to guard times, and so forth, to assure efficient establishment or termination of communication link, and transfer of packets.

## **XVI. Addendum**

[00378] In addition to the formats, structures, and contents discussed above for the various packets used to implement the architecture and protocol for embodiments of the invention, more detailed field contents or operations are presented here for some of the packet types. These are presented here to further clarify their respective use or

operations to enable those skilled in the art to more readily understand and make use of the invention for a variety of applications. Only a few of the fields not already discussed are discussed further here. In addition, these fields are presented with exemplary definitions and values in relation to the embodiments presented above. However, such values are not to be taken as limitations of the invention, but represent one or more embodiments useful for implementing the interface and protocol, and not all embodiments need be practiced together or at the same time. Other values can be used in other embodiments to achieve the desired presentation of data or data rate transfer results, as will be understood by those skilled in the art.

#### **A. For Video Stream Packets**

[00379] In one embodiment, the Display attributes field (1 byte) has a series of bit values that are interpreted as follows. Bits 1 and 0 select how the display pixel data is routed. For bit values of '00' or '11' data is displayed for both eyes, for bit values '10', data is routed only to the left eye, and for bit values '01', data is routed only to the right eye. Bit 2 indicates whether or not the Pixel Data is presented in an interlace format, with a value of '0' meaning the pixel data is in the standard progressive format, and that the row number (pixel Y coordinate) is incremented by 1 when advancing from one row to the next. When this bit has a value of '1', the pixel data is in interlace format, and the row number is incremented by 2 when advancing from one row to the next. Bit 3 indicates that the Pixel Data is in alternate pixel format. This is similar to the standard interlace mode enabled by bit 2, but the interlacing is vertical instead of horizontal. When Bit 3 is 0 the Pixel Data is in the standard progressive format, and the column number (pixel X coordinate) is incremented by 1 as each successive pixel is received. When Bit 3 is 1 the Pixel Data is in alternate pixel format, and the column number is incremented by 2 as each pixel is received. Bits 7 through 4 are reserved for future use and are generally set as zero.

[00380] The 2-byte X Start and Y Start fields specify the absolute X and Y coordinates of the point (X Start, Y Start) for the first pixel in the Pixel Data field. The 2-byte X Left Edge and Y Top Edge fields specify the X coordinate of the left edge and Y coordinate of the top edge of the screen window filled by the Pixel Data field, while the X Right Edge and Y Bottom Edge fields specify the X coordinate of the right edge, and the Y coordinate of the bottom edge of the window being updated.

- [00381] The Pixel Count field (2 bytes) specifies the number of pixels in the Pixel Data field below.
- [00382] The Parameter CRC field (2 bytes) contains a CRC of all bytes from the Packet Length to the Pixel Count. If this CRC fails to check then the entire packet is discarded.
- [00383] The Pixel Data field contains the raw video information that is to be displayed, and which is formatted in the manner described by the Video Data Format Descriptor field. The data is transmitted one "row" at a time as discussed elsewhere.
- [00384] The Pixel Data CRC field (2 bytes) contains a 16-bit CRC of only the Pixel Data. If a CRC verification of this value fails then the Pixel Data can still be used, but the CRC error count is incremented.

#### **B. For Audio Stream Packets**

- [00385] In one embodiment, the Audio Channel ID field (1 byte) identifies a particular audio channel to which audio data is sent by the client device. The physical audio channels are specified in or mapped by this field as values of 0, 1, 2, 3, 4, 5, 6; or 7 which indicate the left front, right front, left rear, right rear, front center, sub-woofer, surround left, and surround right channels, respectively. An audio channel ID value of 254 indicates that the single stream of digital audio samples is sent to both the left front and right front channels. This simplifies applications where a stereo headset is used for voice communication, productivity enhancement apps are used on a PDA, or other applications where a simple User Interface generates warning tones. Values for the ID field ranging from 8 through 253, and 255 are currently reserved for use where new designs desire additional designations.
- [00386] The Audio Sample Count field (2 bytes) specifies the number of audio samples in this packet.
- [00387] The Bits Per Sample and Packing field contains 1 byte that specifies the pacing format of audio data. The format generally employed is for Bits 4 through 0 to define the number of bits per PCM audio sample. Bit 5 then specifies whether or not the Digital Audio Data samples are packed. As mentioned above, FIG. 12 illustrates the difference between packed and byte-aligned audio samples. A value of '0' for Bit 5 indicates that each PCM audio sample in the Digital Audio Data field is byte-aligned with the interface byte boundary, and a value of '1' indicates that each successive PCM audio sample is packed up against the previous audio sample. This bit is effective only when the value defined in bits 4 through 0 (the number of bits per PCM audio sample)

is not a multiple of eight. Bits 7 through 6 are reserved for use where system designs desire additional designations and are generally set at a value of zero.

[00388] The Audio Sample Rate field (1 byte) specifies the audio PCM sample rate. The format employed is for a value of 0 to indicate a rate of 8,000 samples per second (sps), a value of 1 indicates 16,000 sps., value of 2 for 24,000 sps, value of 3 for 32,000 sps, value of 4 for 40,000 sps, value of 5 for 48,000 sps, value of 6 for 11,025 sps, value of 7 for 22,050 sps, and value of 8 for 44,100 sps, respectively, with values of 9 through 15 being reserved for future use, so they are currently set to zero.

[00389] The Parameter CRC field (2 bytes) contains a 16-bit CRC of all bytes from the Packet Length to the Audio Sample Rate. If this CRC fails to check appropriately, then the entire packet is discarded. The Digital Audio Data field contains the raw audio samples to be played, and is usually in the form of a linear format as unsigned integers. The Audio Data CRC field (2 bytes) contain a 16-bit CRC of only the Audio Data. If this CRC fails to check then the Audio Data can still be used, but the CRC error count is incremented.

#### **C. For User-Defined Stream Packets**

[00390] In one embodiment, the 2-byte Stream ID Number field is used to identify a particular user defined stream. The contents of the Stream Parameters and Stream Data fields, are typically defined by the MDDI equipment manufacturer. The 2-byte Stream Parameter CRC field contains a 16-bit CRC of all bytes of the stream parameters starting from the Packet Length to the Audio Coding byte. If this CRC fails to check then the entire packet is discarded. The 2-byte Stream Data CRC field contains a CRC of only the Stream Data. If this CRC fails to check appropriately, then use of the Stream Data is optional, depending on the requirements of the application. Use of the stream data contingent on the CRC being good, generally requires that the stream data be buffered until the CRC is confirmed as being good. The CRC error count is incremented if the CRC does not check.

#### **D. For Color Map Packets**

[00391] The Color Map Data Size field (2 bytes) specifies the total number of color map table entries that exist in the Color Map Data in this packet. In this embodiment, the number of bytes in the Color Map Data is 3 times the Color Map Size. The Color Map Size is set equal to zero to send no color map data. If the Color Map Size is zero then a



Color Map Offset value is generally still sent but it is ignored by the display. The Color Map Offset field (2 bytes) specifies the offset of the Color Map Data in this packet from the beginning of the color map table in the display device.

[00392] A 2-byte Parameter CRC field contains a CRC of all bytes from the Packet Length to the Audio Coding byte. If this CRC fails to check then the entire packet is discarded.

[00393] For the Color Map Data field, each color map location is a 3-byte value, where the first byte specifies the magnitude of blue, the second byte specifies the magnitude of green, and the third byte specifies the magnitude of red. The Color Map Size field specifies the number of 3-byte color map table items that exist in the Color Map Data field. If a single color map cannot fit into one Video Data Format and Color Map Packet, then the entire color map may be specified by sending multiple packets with different Color Map Data and Color Map Offsets in each packet.

[00394] A 2-byte Color Map Data CRC field contains a CRC of only the Color Map Data. If this CRC fails to check then the Color Map Data can still be used but the CRC error count is incremented.

#### **E. For Reverse Link Encapsulation Packets**

[00395] In one embodiment, the Reverse Link Flags field (1 byte) contains a set of flags to request information from the display. If a bit (for example, Bit 0) is set to one then the host requests the specified information from the display using the Display Capability Packet. If the bit is zero then the host does not need the information from the display. The remaining bits (here Bits 1 through 7) are reserved for future use and are set to zero. However, more bits can be used as desired to set flags for the reverse link.

[00396] The Reverse Rate Divisor field (1 byte) specifies the number of MDDI\_Stb cycles that occur in relation to the reverse link data clock. The reverse link data clock is equal to the forward link data clock divided by two times the Reverse Rate Divisor. The reverse link data rate is related to the reverse link data clock and the Interface Type on the reverse link. For a Type I interface the reverse data rate equals the reverse link data clock, for Type II, Type III, and Type IV interfaces the reverse data rates equal two times, four times, and eight times the reverse link data clock, respectively.

[00397] The Turn-Around 1 Length field (1 byte) specifies the total number of bytes that are allocated for Turn-Around 1. The recommended length of Turn-Around 1 is the number of bytes required for the MDDI\_Data drivers in a host to have the outputs

disabled. This is based on the output disable time discussed above, the forward link data rate, and the forward link Interface Type selection being used. A more complete description of the setting of Turn-Around 1 is given above.

[00398] The Turn-Around 2 Length field (1 byte) specifies the total number of bytes that are allocated for Turn-Around. The recommended length of Turn-Around 2 is the number of bytes required for the MDDI\_Data drivers in the Display to disable their outputs plus the round-trip delay. A description of the setting of Turn-Around 2 is given above.

[00399] The Parameter CRC field (2 bytes) contains a 16-bit CRC of all bytes from the Packet Length to the Turn-Around Length. If this CRC fails to check then the entire packet is discarded.

[00400] The All Zero field (1 byte) is set equal to zero, and is used to ensure that all MDDI\_Data signals are in the zero state prior to disabling the line drivers during the first Guard Time period.

[00401] The Turn-Around 1 field is used for establishing the first turn-around period. The number of bytes specified by the Turn-Around Length parameter are allocated by this field to allow the MDDI\_Data line drivers in the host to disable before the line drivers in the client (display) are enabled. The host disables its MDDI\_Data line drivers during bit 0 of Turn-Around 1 and the client (display) enables its line drivers immediately after the last bit of Turn-Around 1. The MDDI\_Stb signal behaves as though the Turn Around period were all zeros.

[00402] The Reverse Data Packets field contains a series of data packets being transferred from the client to a host. As stated earlier, Filler packets are sent to fill the remaining space that is not used by other packet types.

[00403] Turn-Around 2 field is used for establishing the second turn-around period. The number of bytes specified by the Turn-Around Length parameter are allocated by this field.

[00404] The Driver Re-enable field uses 1 byte that is equal to zero to ensure that all MDDI\_Data signals are re-enabled prior to the Packet Length Field of the next packet.

#### **F. For Display Capability Packets**

[00405] In one embodiment, the Protocol Version field uses 2 bytes to specify a protocol version used by the client. The initial version is set equal to zero, while the Minimum Protocol Version field uses 2 bytes to specify the minimum protocol version that the

client can employ or interpret. The Display Data Rate Capability field (2 bytes) specifies the maximum data rate the display can receive on the forward link of the interface, and is specified in the form of megabits per second (Mbps). The Interface Type Capability field (1 byte) specifies the interface types that are supported on the forward and reverse links. This is currently indicated by selecting Bit 0, Bit 1, or Bit 2 to select either a Type-II, Type-III or Type-IV mode on the forward link, respectively, and Bit 3, Bit 4, or Bit 5 to select either a Type-II, Type-III, or Type-IV mode on the reverse link, respectively; with Bits 6 and 7 being reserved and set to zero. The Bitmap Width and Height fields (2 bytes) specify the width and height of the bitmap in pixels.

[00406] The Monochrome Capability field (1 byte) is used to specify the number of bits of resolution that can be displayed in a monochrome format. If a display cannot use a monochrome format then this value is set at zero. Bits 7 through 4 are reserved for future use and are, thus, set as zero. Bits 3 through 0 define the maximum number of bits of grayscale that can exist for each pixel. These four bits make it possible to specify values of 1 to 15 for each pixel. If the value is zero then monochrome format is not supported by the display.

[00407] The Colormap Capability field (3 bytes) specifies the maximum number of table items that exist in the colormap table in the display. If the display cannot use the colormap format then this value is zero.

[00408] The RGB Capability field (2 bytes) specifies the number of bits of resolution that can be displayed in RGB format. If the display cannot use the RGB format then this value is equal to zero. The RGB Capability word is composed of three separate unsigned values where: Bits 3 through 0 define the maximum number of bits of blue, Bits 7 through 4 define the maximum number of bits of green, and Bits 11 through 8 define the maximum number of bits of red in each pixel. Currently, Bits 15 through 12 are reserved for future use and are generally set to zero.

[00409] The Y Cr Cb Capability field (2 bytes) specifies the number of bits of resolution that can be displayed in Y Cr Cb format. If the display cannot use the Y Cr Cb format then this value is set equal to zero. The Y Cr Cb Capability word is composed of three separate unsigned values where: Bits 3 through 0 define the maximum number of bits in the Cb sample, Bits 7 through 4 define the maximum number of bits in the Cr sample, Bits 11 through 8 define the maximum number of bits in the Y sample, and Bits 15 through 12 are currently reserved for future use and are set to zero.

- [00410] The Display Feature Capability Indicators field uses 4 bytes that contain a set of flags that indicate specific features in the display that are supported. A bit set to one indicates the capability is supported, and a bit set to zero indicates the capability is not supported. The value for Bit 0 indicates whether or not Bitmap Block Transfer Packet (packet type 71) is supported. The value for Bits 1, 2, and 3 indicate whether or not Bitmap Area Fill Packet (packet type 72), Bitmap Pattern Fill Packet (packet type 73), or Communication Link Data Channel Packet (packet type 74), respectively, are supported. The value for Bit 4 indicates whether or not the display has the capability to make one color transparent, while values for bits Bit 5 and 6 indicate if the display can accept video data or audio data in packed format, respectively, and the value for Bit 7 indicates if the display can send a reverse-link video stream from a camera. The value for Bits 11 and 12 indicate when the client is communicating either with a pointing device and can send and receive Pointing Device Data Packets, or with a keyboard and can send and receive Keyboard Data Packets, respectively. Bits 13 through 31 are currently reserved for future use or alternative designations useful for system designers and are generally set equal to zero.
- [00411] The Display Video Frame Rate Capability field (1 byte) specifies the maximum video frame update capability of the display in frames per second. A host may choose to update the image at a slower rate than the value specified in this field.
- [00412] The Audio Buffer Depth field (2 bytes) specifies the depth of the elastic buffer in a Display which is dedicated to each audio stream.
- [00413] The Audio Channel Capability field (2 bytes) contains a group of flags that indicate which audio channels are supported by the display (client). A bit set to one indicates the channel is supported, and a bit set to zero indicates that channel is not supported. The Bit positions are assigned to the different channels, for example Bit positions 0, 1, 2, 3, 4, 5, 6, and 7 indicate the left front, right front, left rear, right rear, front center, sub-woofer, surround left, and surround right channels, respectively. Bits 8 through 15 are currently reserved for future use, and are generally set to zero.
- [00414] A 2-byte Audio Sample Rate Capability field, for the forward link, contains a set of flags to indicate the audio sample rate capability of the client device. Bit positions are assigned to the different rates accordingly, such as Bits 0, 1, 2, 3, 4, 5, 6, 7, and 8 being assigned to 8,000, 16,000, 24,000, 32,000, 40,000, 48,000, 11,025, 22,050, and 44,100 samples per second (SPS), respectively, with Bits 9 through 15 being reserved for future or alternative rate uses, as desired, so they are currently set to '0'. Setting a bit

value for one of these bits to '1' indicates that that particular sample rate is supported, and setting the bit to '0' indicates that that sample rate is not supported.

[00415] The Minimum Sub-frame Rate field (2 bytes) specifies the minimum sub-frame rate in frames per second. The minimum sub-frame rate keeps the display status update rate sufficient to read certain sensors or pointing devices in the display.

[00416] A 2-byte Mic Sample Rate Capability field, for the reverse link, that contains a set of flags that indicate the audio sample rate capability of a microphone in the client device. For purposes of the MDDI, a client device microphone is configured to minimally support at least an 8,000 sample per second rate. Bit positions for this field are assigned to the different rates with bit positions 0, 1, 2, 3, 4, 5, 6, 7, and 8, for example, being used to represent 8,000, 16,000, 24,000, 32,000, 40,000, 48,000, 11,025, 22,050, and 44,100 samples per second (SPS), respectively, with Bits 9 through 15 being reserved for future or alternative rate uses, as desired, so they are currently set to '0'. Setting a bit value for one of these bits to '1' indicates that that particular sample rate is supported, and setting the bit to '0' indicates that that sample rate is not supported. If no microphone is connected then each of the Mic Sample Rate Capability bits are set equal to zero.

[00417] The Content Protection Type field (2 bytes) contains a set of flags that indicate the type of digital content protection that is supported by the Display. Currently, bit position 0 is used to indicate when DTCP is supported and bit position 1 is used to indicate when HDCP is supported, with bit positions 2 through 15 being reserved for use with other protection schemes as desired or available, so they are currently set to zero.

#### **G. For Display Request and Status Packets**

[00418] The Reverse Link Request field (3 byte) specifies the number of bytes the display needs in the reverse link in the next sub-frame to send information to the host.

[00419] The CRC Error Count field (1 byte) indicates how many CRC errors have occurred since the beginning of the media-frame. The CRC count is reset when a sub-frame header packet with a Sub-frame Count of zero is sent. If the actual number of CRC errors exceeds 255 then this value generally saturates at 255.

[00420] The Capability Change field uses 1 byte to indicate a change in the capability of the display. This could occur if a user connects a peripheral device such as a microphone, keyboard, or display, or for some other reason. When Bits[7:0] are equal

to 0, then the capability has not changed since the last Display Capability Packet was sent. However, when Bits[7:0] are equal to 1 to 255, the capability has changed. The Display Capability Packet is examined to determine the new display characteristics.

#### **H. For Bit Block Transfer Packets**

[00421] The Window Upper Left Coordinate X Value and Y Value fields use 2 bytes each to specify the X and Y value of the coordinates of the upper left corner of the window to be moved. The Window Width and Height fields use 2 bytes each to specify the width and height of the window to be moved. The Window X Movement and Y Movement fields use 2 bytes each to specify the number of pixels that the window is to be moved horizontally and vertically, respectively. Typically, these coordinates are configured such that positive values for X cause the window to be moved to the right, and negative values cause movement to the left, while positive values for Y cause the window to be moved down, and negative values cause upward movement.

#### **I. For Bitmap Area Fill Packets**

[00422] Window Upper Left Coordinate X Value and Y Value fields use 2 bytes each to specify the X and Y value of the coordinates of the upper left corner of the window to be filled. The Window Width and Height fields (2 bytes each) specify the width and height of the window to be filled. The Video Data Format Descriptor field (2 bytes) specifies the format of the Pixel Area Fill Value. The format is the same as the same field in the Video Stream Packet. The Pixel Area Fill Value field (4 bytes) contains the pixel value to be filled into the window specified by the fields discussed above. The format of this pixel is specified in the Video Data Format Descriptor field.

#### **J. For Bitmap Pattern Fill Packets**

[00423] Window Upper Left Coordinate X Value and Y Value fields use 2 bytes each to specify the X and Y value of the coordinates of the upper left corner of the window to be filled. The Window Width and Height fields (2 bytes each) specify the width and height of the window to be filled. The Pattern Width and Pattern Height fields (2 bytes each) specify the width and height, respectively, of the fill pattern. The 2-byte Video Data Format Descriptor field specifies the format of the Pixel Area Fill Value. FIG. 11 illustrates how the Video Data Format Descriptor is coded. The format is the same as the same field in the Video Stream Packet.

- [00424] The Parameter CRC field (2 bytes) contains a CRC of all bytes from the Packet Length to the Video Format Descriptor. If this CRC fails to check then the entire packet is discarded. The Pattern Pixel Data field contains raw video information that specifies the fill pattern in the format specified by the Video Data Format Descriptor. Data is packed into bytes, and the first pixel of each row must be byte-aligned. The fill pattern data is transmitted a row at a time. The Pattern Pixel Data CRC field (2 bytes) contains a CRC of only the Pattern Pixel Data. If this CRC fails to check then the Pattern Pixel Data can still be used but the CRC error count is incremented.

**K. Communication Link Data Channel Packets**

- [00425] The Parameter CRC field (2 bytes) contain a 16-bit CRC of all bytes from the Packet Length to the Packet Type. If this CRC fails to check then the entire packet is discarded.
- [00426] The Communication Link Data field contains the raw data from the communication channel. This data is simply passed on to the computing device in the display.
- [00427] The Communication Link Data CRC field (2 bytes) contains a 16-bit CRC of only the Communication Link Data. If this CRC fails to check then the Communication Link Data is still used or useful, but the CRC error count is incremented.

**L. For Interface Type Handoff Request Packets**

- [00428] The Interface Type field (1 byte) specifies the new interface type to use. The value in this field specifies the interface type in the following manner. If the value in Bit 7 is equal to '0' the Type handoff request is for the forward link, if it is equal to '1', then the Type handoff request is for the reverse link. Bits 6 through 3 are reserved for future use, and are generally set to zero. Bits 2 through 0 are used to define the interface Type to be used, with a value of 1 meaning a handoff to Type-I mode, value of 2 a handoff to Type-II mode, a value of 3 a handoff to Type-III mode, and a value of 4 a handoff to Type-IV mode. The values of '0' and 5 through 7 are reserved for future designation of alternative modes or combinations of modes.

**M. For Interface Type Acknowledge Packets**

- [00429] The Interface Type field (1 byte) has a value that confirms the new interface type to use. The value in this field specifies the interface type in the following manner.

If Bit 7 is equal to '0' the Type handoff request is for the forward link, alternatively, if it is equal to '1' the Type handoff request is for the reverse link. Bit positions 6 through 3 are currently reserved for use in designating other handoff types, as desired, and are generally set to zero. However, bit positions 2 through 0 are used define the interface Type to be used with a value of '0' indicating a negative acknowledge, or that the requested handoff cannot be performed, values of '1', '2', '3', and '4' indicating handoff to Type-I, Type-II, Type-III, and Type-IV modes, respectively. Values of 5 through 7 are reserved for use with alternative designations of modes, as desired.

**N. For Perform Type Handoff Packets**

[00430] The 1-byte Interface Type field indicates the new interface type to use. The value present in this field specifies the interface type by first using the value of Bit 7 to determine whether or not the Type handoff is for the forward or reverse links. A value of '0' indicates the Type handoff request is for the forward link, and a value of '1' the reverse link. Bits 6 through 3 are reserved for future use, and as such are generally set to a value of zero. However, Bits 2 through 0 are used to define the interface Type to be used, with the values 1, 2, 3, and 4 specifying the use of handoff to Type-I, Type-II, Type-III, and Type-IV modes, respectively. The use of values 0 and 5 through 7 for these bits is reserved for future use.

**O. For Forward Audio Channel Enable Packets**

[00431] The Audio Channel Enable Mask field (1 byte) contains a group of flags that indicate which audio channels are to be enabled in a client. A bit set to one enables the corresponding channel, and a bit set to zero disables the corresponding channel. Bits 0 through 5 designate channels 0 through 5 which address left front, right front, left rear, right rear, front center, and sub-woofer channels, respectively. Bits 6 and 7 are reserved for future use, and in the mean time are generally set equal to zero.

**P. For Reverse Audio Sample Rate Packets**

[00432] The Audio Sample Rate field(1 byte) specifies the digital audio sample rate. The values for this field are assigned to the different rates with values of 0, 1, 2, 3, 4, 5, 6, 7, and 8 being used to designate 8,000, 16,000, 24,000, 32,000, 40,000, 48,000, 11,025, 22,050, and 44,100 samples per second (SPS), respectively, with values of 9



through 254 being reserved for use with alternative rates, as desired, so they are currently set to '0'. A value of 255 is used to disable the reverse-link audio stream.

- [00433] The Sample Format field (1 byte) specifies the format of the digital audio samples. When Bits[1:0] are equal to '0', the digital audio samples are in linear format, when they are equal to 1, the digital audio samples are in  $\mu$ -Law format, and when they are equal to 2, the digital audio samples are in A-Law format. Bits[7:2] are reserved for alternate use in designating audio formats, as desired, and are generally set equal to zero.

**Q. For The Digital Content Protection Overhead Packets**

- [00434] The Content Protection Type field (1 byte) specifies the digital content protection method that is used. A value of '0' indicates Digital Transmission Content Protection (DTCP) while a value of 1 indicates High-bandwidth Digital Content Protection System (HDCP). The value range of 2 through 255 is not currently specified but is reserved for use with alternative protection schemes as desired. The Content Protection Overhead Messages field is a variable length field containing content protection messages sent between the host and client.

**R. For The Transparent Color Enable Packets**

- [00435] The Transparent Color Enable field (1 byte) specifies when transparent color mode is enabled or disabled. If Bit 0 is equal to 0 then transparent color mode is disabled, if it is equal to 1 then transparent color mode is enabled and the transparent color is specified by the following two parameters. Bits 1 through 7 of this byte are reserved for future use and are typically set equal to zero.
- [00436] The Video Data Format Descriptor field (2 bytes) specifies the format of the Pixel Area Fill Value. FIG. 11 illustrates how the Video Data Format Descriptor is coded. The format is generally the same as the same field in the Video Stream Packet.
- [00437] The Pixel Area Fill Value field uses 4 bytes allocated for the pixel value to be filled into the window specified above. The format of this pixel is specified in the Video Data Format Descriptor field.

**S. For The Round Trip Delay Measurement Packets**

- [00438] In one embodiment, the Parameter CRC field (2 bytes) contains a 16-bit CRC of all bytes from the Packet Length to the Packet Type. If this CRC fails to check then the entire packet is discarded.
- [00439] The All Zero field (1 byte) contains zeroes to ensure that all MDDI\_Data signals are in the zero state prior to disabling the line drivers during the first Guard Time period.
- [00440] The Guard Time 1 field (8 bytes) is used to allow the MDDI\_Data line drivers in the host to disable before the line drivers in the client (display) are enabled. The host disables its MDDI\_Data line drivers during bit 0 of Guard Time 1 and the Display enables its line drivers immediately after the last bit of Guard Time 1.
- [00441] The Measurement Period field is a 512 byte window used to allow the Display to respond with a 0xff, 0xff, 0x0 at half the data rate used on the forward link. This rate corresponds to a Reverse Link Rate Divisor of 1. The Display returns this response immediately at the beginning of the Measurement Period. This response will be received at a host at precisely the round trip delay of the link after the beginning of the first bit of the Measurement Period at the host. The MDDI\_Data line drivers in the Display are disabled immediately before and immediately after the 0xff, 0xff, 0x00 response from the Display.
- [00442] The value in the Guard Time 2 field (8 bytes) allows Client MDDI\_Data line drivers to disable before line drivers in the Host are enabled. Guard Time 2 is always present but is only required when the round trip delay is at the maximum amount that can be measured in the Measurement Period. The Client disables its line drivers during bit 0 of Guard Time 2 and the Host enables its line drivers immediately after the last bit of Guard Time 2.
- [00443] The Driver Re-enable field (1 byte) is set equal to zero, to ensure that all MDDI\_Data signals are re-enabled prior to the Packet Length Field of the next packet.

**T. For The Forward Link Skew Calibration Packets**

- [00444] In one embodiment, the Parameter CRC field (2 bytes) contains a 16-bit CRC of all bytes from the Packet Length to the Packet Type. If this CRC fails to check then the entire packet is discarded.

[00445] The Calibration Data Sequence field contains a 512 byte data sequence that causes the MDDI\_Data signals to toggle at every data period. During the processing of the Calibration Data Sequence, the MDDI host controller sets all MDDI\_Data signals equal to the strobe signal. The display clock recovery circuit should use only MDDI\_Stb rather than MDDI\_Stb Xor MDDI\_Data0 to recover the data clock while the Calibration Data Sequence field is being received by the client Display. Depending on the exact phase of the MDDI\_Stb signal at the beginning of the Calibration Data Sequence field, the Calibration Data Sequence will generally be one of the following based on the interface Type being used when this packet is sent:

Type I – 0xaa, 0xaa ... or 0x55, 0x55...

Type II – 0xcc, 0xcc ... or 0x33, 0x33...

Type III – 0xf0, 0xf0 ... or 0x0f, 0x0f ...

Type IV – 0xff, 0x00, 0xff, 0x00 ... or 0x00, 0xff, 0x00, 0xff ...

[00446] An example of the possible MDDI\_Data and MDDI\_Stb waveforms for both the Type-I and Type-II Interfaces are shown in FIGS. 62A and 62B, respectively.

## **XVII. Conclusion**

[00447] While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

What is claimed is:

## CLAIMS

1. A digital data interface for transferring digital presentation data at a high rate between a host device and a client device over a communication path comprising:

a plurality of packet structures linked together to form a communication protocol for communicating a pre-selected set of digital control and presentation data between a host and a client over said communication path; and

at least one link controller residing in said host device coupled to said client through said communications path, being configured to generate, transmit, and receive packets forming said communications protocol, and to form digital presentation data into one or more types of data packets.

2. The interface of Claim 1 further comprising said packets grouped together within media frames that are communicated between said host and client having a pre-defined fixed length with a pre-determined number of said packets have differing and variable lengths.

3. The interface of Claim 1 further comprising a Sub-frame Header Packet positioned at the beginning of transfers of packets from said host.

4. The interface of Claim 1 wherein said link controller is a host link controller and further comprising at least one client link controller residing in said client device coupled to said host through said communications path, being configured to generate, transmit, and receive packets forming said communications protocol, and to form digital presentation data into one or more types of data packets.

5. The interface of Claim 1 further comprising one or more Video Stream Packets for video type data, and Audio Stream Packets for audio type data for transferring data from said host to said client over a forward link for presentation to a client user.

6. The interface of Claim 2 further comprising:

a plurality of transfer modes, each allowing the transfer of different maximum numbers of bits of data in parallel over a given time period, with each mode selectable by negotiation between said host and client link drivers; and

wherein said transfer modes are dynamically adjustable between said modes during transfer of data.

7. The interface of Claim 1 further comprising a plurality of packets usable to transfer video information chosen from the group of Color Map, Bit Block Transfer, Bitmap Area Fill, Bitmap Pattern Fill, and Transparent Color Enable type packets.

8. The interface of Claim 1 further comprising Filler type packets generated by said host to occupy periods of forward link transmission that do not have data.

9. The interface of Claim 1 further comprising User-Defined Stream type packets for transferring interface-user defined data.

10. The interface of Claim 1 further comprising a Link Shutdown type packet for transmission by said host to said client to terminate the transfer of data in either direction over said communication path.

11. The interface of Claim 1 further comprising means for said client to wake up said host from a hibernation state.

12. A method of transferring digital data at a high rate between a host device and a client device over a communication path for presentation to a user, comprising:

generating one or more of a plurality of pre-defined packet structures and linking them together to form a pre-defined communication protocol;

communicating a pre-selected set of digital control and presentation data between said host and said client devices over said communication path using said communication protocol;

coupling at least one host link controller residing in said host device to said client device through said communications path, the host link controller being configured to generate, transmit, and receive packets forming said communications protocol, and to form digital presentation data into one or more types of data packets; and

transferring data in the form of packets over said communications path using said link controllers.

13. The method of Claim 12 further comprising grouping said packets together within media frames for communication between said host and client, the media frames having a pre-defined fixed length with a pre-determined number of said packets have differing and variable lengths.
14. The method of Claim 12 further comprising commencing transfer of packets from said host with a Sub-frame Header type packet.
15. The method of Claim 12 further comprising transferring information between said host and client bi-directionally over said communications link.
16. The method of Claim 12 further comprising at least one client link controller residing in said client device coupled to said host device through said communications path, being configured to generate, transmit, and receive packets forming said communications protocol, and to form digital presentation data into one or more types of data packets.
17. The method of Claim 16 wherein said host link controller comprises one or more differential line drivers; and said client link controller comprises one or more differential line receivers coupled to said communication path.
18. The method of Claim 12 further comprising requesting display capabilities information from the client by a host link controller so as to determine what type of data and data rates said client is capable of accommodating through said interface.
19. The method of Claim 12 further comprising operating a USB data interface by each of said link controllers as a part of said communication path.
20. The method of Claim 12 wherein said packets each comprise a packet length field, one or more packet data fields, and a cyclic redundancy check field.

21. The method of Claim 13 further comprising:  
negotiating between said host and client link drivers the use of one of a plurality of transfer modes in each direction, each allowing the transfer of different maximum numbers of bits of data in parallel over a given time period; and  
dynamically adjusting between said transfer modes during transfer of data.
22. The method of Claim 12 further comprising using one or more of a plurality of packets to transfer video information chosen from the group of Color Map, Bit Block Transfer, Bitmap Area Fill, Bitmap Pattern Fill, and Transparent Color Enable type packets.
23. The method of Claim 12 further comprising generating Filler type packets by said host to occupy periods of forward link transmission that do not have data.
24. The method of Claim 12 further comprising terminating the transfer of data in either direction over said communication path using a Link Shutdown type packet for transmission by said host to said client.
25. The method of Claim 12 further comprising waking up said host from a hibernation state by communication with said client.
26. Apparatus for transferring digital data at a high rate between a host device and a client device over a communication path for presentation to a user, comprising:  
at least one host link controller disposed in said host device for generating one or more of a plurality of pre-defined packet structures and linking them together to form a pre-defined communication protocol, and for communicating a pre-selected set of digital control and presentation data between said host and said client devices over said communication path using said communication protocol;  
at least one client controller disposed in said client device and coupled to said host link controller through said communications path; and  
each link controller being configured to generate, transmit, and receive packets forming said communications protocol, and to form digital presentation data into one or more types of data packets.

27. The apparatus of Claim 26 wherein said host controller comprises a state machine.
28. The apparatus of Claim 26 wherein said host controller comprises a general purpose signal processor.
29. The apparatus of Claim 26 further comprising a Sub-frame Header type packet at the commencing of transfer of packets from said host.
30. The apparatus of Claim 26 wherein said link controllers are configured to transfer information between said host and client devices bi-directionally over said communications link.
31. The apparatus of Claim 30 wherein said host controller comprises one or more differential line drivers; and said client receiver comprises one or more differential line receivers coupled to said communication path.
32. The apparatus of Claim 26 further comprising Video Stream type packets for video type data, and Audio Stream type packets for audio type when transferring data from said host to said client for presentation to a client user.
33. The apparatus of Claim 26 further comprising one or more Reverse Link Encapsulation type packets for transferring data from said client to said host.
34. The apparatus of Claim 33 further comprising at least one Display Capability type packet for communicating display or presentation capabilities from a client link controller to said host link controller.
35. The apparatus of Claim 26 wherein said packets each comprise a packet length field, one or more packet data fields, and a cyclic redundancy check field.
36. The apparatus of Claim 26 wherein said host and client link controllers are configured to use of one of a plurality of transfer modes in each direction, each allowing the transfer of different maximum numbers of bits of data in parallel over a given time



period; and being capable of being dynamically adjusting between said transfer modes during transfer of data.

37. The apparatus of Claim 26 further comprising one or more of a plurality of packets for transferring video information chosen from the group of Color Map, Bit Block Transfer, Bitmap Area Fill, Bitmap Pattern Fill, and Transparent Color Enable type packets.

38. The apparatus of Claim 26 further comprising Filler type packets for transfer by said host to occupy periods of forward link transmission that do not have data.

39. The apparatus of Claim 26 wherein said host controller is configured to transmit a Link Shutdown type packet to said client means for terminating the transfer of data in either direction over said communication path.

40. For use in an electronic system for transferring digital data at a high rate between a host device and a client device over a communication path for presentation to a user, a computer program product comprising:

- a computer usable medium having computer readable program code means embodied in said medium for causing an application program to execute on the computer system, said computer readable program code means comprising:

- a computer readable first program code means for causing the computer system to generate one or more of a plurality of pre-defined packet structures and link them together to form a pre-defined communication protocol;

- a computer readable second program code means for causing the computer system to communicate a pre-selected set of digital control and presentation data between said host and said client devices over said communication path using said communication protocol;

- a computer readable third program code means for causing the computer system to couple at least one host link controller disposed in said host device to at least one client controller disposed in said client device through said communications path, the link controllers being configured to generate, transmit, and receive packets forming said communications protocol, and to form digital presentation data into one or more types of data packets; and

a computer readable fourth program code means for causing the computer system to transfer data in the form of packets over said communications path using said link controllers.

41. Apparatus for transferring digital data at a high rate between a host device and a client device over a communication path for presentation to a user, comprising:

means for generating one or more of a plurality of pre-defined packet structures and linking them together to form a pre-defined communication protocol;

means for communicating a pre-selected set of digital control and presentation data between said host and said client devices over said communication path using said communication protocol;

means for coupling at least two link controllers together through said communications path, one in each of said host and client and each being configured to generate, transmit, and receive packets forming said communications protocol, and to form digital presentation data into one or more types of data packets; and

means for transferring data in the form of packets over said communications path using said link controllers.

42. The apparatus of Claim 41 further comprising means for commencing transfer of packets from said host with a Sub-frame Header type packet.

43. The apparatus of Claim 41 further comprising means for transferring information between said host and client bi-directionally over said communications link.

44. The apparatus of Claim 41 further comprising means for requesting display capabilities information from the client by a host link controller so as to determine what type of data and data rates said client is capable of accommodating through said interface.

45. The apparatus of Claim 44 further comprising means for communicating display or presentation capabilities from a client link controller to said host link controller using at least one Display Capability type packet.

46. The apparatus of Claim 42 further comprising:  
means for negotiating between said host and client link drivers the use of one of a plurality of transfer modes in each direction, each allowing the transfer of different maximum numbers of bits of data in parallel over a given time period; and  
means for dynamically adjusting between said transfer modes during transfer of data.
47. The apparatus of Claim 41 further comprising means for using one or more of a plurality of packets to transfer video information chosen from the group of Color Map, Bit Block Transfer, Bitmap Area Fill, Bitmap Pattern Fill, and Transparent Color Enable type packets.
48. A processor for use in an electronic system for transferring digital data at a high rate between a host device and a client device over a communication path, the processor configured to generate one or more of a plurality of pre-defined packet structures and link them together to form a pre-defined communication protocol; to form digital presentation data into one or more types of data packets; communicate a pre-selected set of digital control and presentation data between said host and said client devices over said communication path using said communication protocol; and transfer data in the form of packets over said communications path.
49. A state machine for use in obtaining synchronization in an electronic system transferring digital data at a high rate between a host device and a client device over a communication path, the state machine configured to have at least one Async Frames State synchronization state, at least two Acquiring Sync States synchronization states, and at least three In-Sync States synchronization states.
50. A state machine for use in obtaining synchronization in an electronic system transferring digital data at a high rate between a host device and a client device over a communication path, the state machine configured to have at least one Acquiring Sync States synchronization states, and at least two In-Sync States synchronization states.

51. The state machine of Claim 50, wherein one condition for shifting between an Acquiring Sync State and a first In-Sync State is detecting the presence of a synchronization pattern in the communication link.

52. The state machine of Claim 51, wherein a second condition for shifting between an Acquiring Sync State and a first In-Sync State is detecting the presence of a sub-frame header packet and good CRC value at a frame boundary.

53. The state machine of Claim 50, wherein one condition for shifting between a first In-Sync State and an Acquiring Sync State is detecting the presence of no synchronization pattern or a bad CRC value at a sub-frame boundary.

54. The state machine of Claim 50, wherein one condition for shifting between a first In-Sync State and a second In-Sync State is detecting the presence of no synchronization pattern or a bad CRC value at a sub-frame boundary.

55. The state machine of Claim 50, wherein one condition for shifting between an Acquiring Sync State and a first In-Sync State is detecting the presence of a synchronization pattern in the communication link is detecting the presence of a good packet CRC value.

56. The state machine of Claim 50, wherein a condition for shifting between a first In-Sync State and an Acquiring Sync State is detecting the presence of a bad CRC value in a packet.

57. A state machine for use in obtaining synchronization in an electronic system transferring digital data at a high rate between a host device and a client device over a communication path, the state machine configured to have at least one Acquiring Sync States synchronization states, and at least two In-Sync States synchronization states, wherein a condition for shifting directly between a first In-Sync State and an Acquiring Sync State is detecting the presence of a bad CRC value in any of a series of packets.

58. The state machine of Claim 57, wherein a condition for shifting directly between a first In-Sync State and an Acquiring Sync State is detecting when the unique word does not occur at a time it is expected to arrive.

59. The method of Claim 26 further comprising waking up a communication link by driving a data line to a high state for at least 10 clock cycles and starting to transmit a strobe signal as if the data line was zero, by said host.

60. The method of Claim 59 further comprising driving the data line low for 50 clock cycles by said host while continuing to transmit a strobe signal after the host has driven the data line high for 150 clock cycles.

61. The method of Claim 59 further comprising beginning to transmit the first sub-frame header packet by said host.

62. The method of Claim 60 further comprising counting at least 150 continuous clock cycles of the data line being high, followed by at least 50 continuous clock cycles of the data line being low, by said client.

63. The method of Claim 62 further comprising searching for the unique word of the first sub-frame by said client.

64. The method of Claim 60 further comprising stopping driving the data line high by said client after the client counts 70 continuous clock cycles of the data being high

65. The method of Claim 64 further comprising counting another 80 continuous clock cycles of the data line being high to reach the 150 clock cycles of the data line being high by said client, and looking for 50 clock cycles of the data line being low, and looking for the unique word.

66. The method of Claim 26 further comprising counting the number of clock cycles occurring until a one is sampled by said host, by sampling the data line on both the rising and falling edges during the reverse timing packet.

67. A method of transferring error codes in a communication system in which digital data is transferred in the form of packets having CRC values between a host device and a client device over a communication path comprising detecting the presence of an error, selecting a pre-determined error code corresponding to said error, and overwriting the CRC value with said code.

68. The method of Claim 67 further comprising overwriting said CRC value in successive ones of packets being transferred until said error is corrected.

69. A method of transferring digital data at a high rate between a host device and a client device over a communication path for presentation to a user, comprising:

- generating one or more of a plurality of pre-defined packet structures each including at least one CRC field, and linking them together to form a pre-defined communication protocol;

- communicating a pre-selected set of digital control and presentation data between said host and said client devices over said communication path using said communication protocol;

- coupling at least one host link controller residing in said host device to said client device through said communications path, the host link controller being configured to generate, transmit, and receive packets forming said communications protocol, and to form digital presentation data into one or more types of data packets;

- transferring data in the form of packets over said communications path using said link controllers;

- detecting the presence of an error for the communication link;

- selecting a pre-determined error code corresponding to said error; and overwriting the CRC value with said code.

70. The method of Claim 69 further comprising overwriting said CRC value in successive ones of packets being transferred until said error is corrected.




FIG. 1A




FIG. 1B






FIG. 2



FIG. 3




FIG. 4




FIG. 5




FIG. 6



FIG. 7




FIG. 8




FIG. 9




FIG. 10

Video Data Format Descriptor - Monochrome

0	0	0	P	not used = 0				number of bits per pixel			
15	14	13	12	11	4	3	2	1	0		

Video Data Format Descriptor - Color Using Color Map

0	0	1	P	not used = 0				number of bits per pixel			
15	14	13	12	11	6	5	4	3	2	1	0

Video Data Format Descriptor - Color, Raw RGB

0	1	0	P	number of bits of red per pixel				number of bits of green per pixel				number of bits of blue per pixel			
15	14	13	12	11	8	7	6	5	4	3	2	1	0		

Video Data Format Descriptor - Color Component Video, Y Pr Pb

0	1	1	P	number of bits of Y per pixel				number of bits of Pr per pixel				number of bits of Pb per pixel			
15	14	13	12	11	8	7	6	5	4	3	2	1	0		

FIG. 11

9/53

Byte-Aligned (not packed) Pixel Data, P = 0

← MDDI byte n →				← MDDI byte n+1 →				← MDDI byte n+2 →				← MDDI byte n+3 →				← MDDI byte n+4 →				← MDDI byte n+5 →			
0	1	2	3	4	5	6	7	0	1	2	3	4	5	6	7	0	1	2	3	4	5	6	7
0	1	2	3	4	5			0	1	2	3	4	5			0	1	2	3	4	5		
Pixel 1 Blue				Pixel 1 Green				Pixel 1 Red				Pixel 2 Blue				Pixel 2 Green				Pixel 2 Red			
un-				un-				un-				un-				un-				un-			
used				used				used				used				used				used			

Packed Pixel Data, P = 1

← MDDI byte n →				← MDDI byte n+1 →				← MDDI byte n+2 →				← MDDI byte n+3 →				← MDDI byte n+4 →				← MDDI byte n+5 →			
0	1	2	3	4	5	6	7	0	1	2	3	4	5	6	7	0	1	2	3	4	5	6	7
0	1	2	3	4	5	0	1	2	3	4	5	0	1	2	3	4	5	0	1	2	3	4	5
Pixel 1 Blue				Pixel 1 Green				Pixel 1 Red				Pixel 2 Blue				Pixel 2 Green				Pixel 2 Red			
un-				un-				un-				un-				un-				un-			
used				used				used				used				used				used			

FIG. 12




FIG. 13




FIG. 15




FIG. 16






FIG. 14




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25

Packet Length	Packet Type = 74	Parameter CRC	Communication Link Data	Comm. Data CRC
2 bytes	1 byte	2 bytes	length - 5 bytes	2 bytes

FIG. 26

Packet Length	Packet Type = 75	Interface Type	CRC
2 bytes	1 byte	1 byte	2 bytes

FIG. 27

Packet Length	Packet Type = 76	Interface Type	CRC
2 bytes	1 byte	1 byte	2 bytes

FIG. 28

Packet Length	Packet Type = 77	Interface Type	CRC
---------------	------------------	----------------	-----

2 bytes                      1 byte                      1 byte                      2 bytes

FIG. 29

Packet Length	Packet Type = 78	Audio Channel Enable Mask	CRC
---------------	------------------	---------------------------	-----

2 bytes                      1 byte                      1 byte                      2 bytes

FIG. 30

Packet Length	Packet Type = 79	Audio Sample Rate	CRC
---------------	------------------	-------------------	-----

2 bytes                      1 byte                      1 byte                      2 bytes

FIG. 31





FIG. 32




FIG. 33




FIG. 34

20/53




FIG. 35




FIG. 36




FIG. 37A




FIG. 37B




FIG. 38




FIG. 39




FIG. 40




Fig. 14

26/53





FIG. 42





27/53

FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47





FIG. 48



cond 1 = Sub-frame header packet & good CRC at frame boundary,  
Frame Length > 0

cond 2 = no sync pattern or bad CRC at frame boundary


cond 3 = found sync pattern, Frame Length = 0

cond 4 = received link shutdown packet

cond 5 = found sync pattern, Frame Length > 0

cond 6 = frame header packet & good CRC, Frame Length > 0

FIG. 49



50





FIG. 51



25  
G  
F






FIG. 53

36/53




FIG. 54A




FIG. 54B

38/53




FIG. 55





FIG. 56



F. G. 57

41/53




FIG. 58




FIG. 59



43/53




FIG. 60A




FIG. 60B




FIG. 60C




FIG. 61




FIG. 62A




FIG. 62B




FIG. 63

48/53




FIG. 64




FIG. 65

50/53




FIG. 66






FIG. 67A

52/53




FIG. 67B




FIG. 68A




FIG. 68B




FIG. 68C

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number  
**WO 2004/110021 A3**

(51) International Patent Classification<sup>7</sup>: **H04L 29/06**,  
12/64, G06F 3/14

5740 Brittany Forrest Lane, San Diego, CO 92130 (US).  
**SHEKHAR, Shashank** [IN/US]; 1597 Holeman Drive,  
Érie, CO 80516 (US).

(21) International Application Number:  
PCT/US2004/017579

(74) Agent: **OGROD, Gregory, D.**; 5775 Morehouse Drive,  
San Diego, CA 92121 (US).

(22) International Filing Date: 2 June 2004 (02.06.2004)

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/475,459 2 June 2003 (02.06.2003) US

(71) Applicant (for all designated States except US): **QUAL-  
COMM INCORPORATED** [US/US]; 5775 Morehouse  
Drive, San Diego, CA 92121 (US).


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SI, SK,  
TR), OAPI (BF, BJ, CI, CG, CL, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ANDERSON,  
Jon, James** [US/US]; 7436 Augusta Drive, Boulder, CO  
80301 (US). **STEELE, Brian** [US/US]; 1074 Iliad Way,  
Lafayette, CO 80026 (US). **WILEY, George, A.** [US/US];

[Continued on next page]

(54) Title: GENERATING AND IMPLEMENTING A SIGNAL PROTOCOL AND INTERFACE FOR HIGHER DATA RATES



(57) Abstract: A data Interface for transferring digital data between a host (100) and a client (104,108) over a communication path (110) using packet structures linked together to form a communication protocol for communicating a pre-selected set of digital control and presentation data. The signal protocol is used by link controllers configured to generate, transmit, and receive packets forming the communications protocol, and to form digital data into one or more types of data packets, with at least one residing in the host device (100) and being coupled to the client (104,108) through the communications path (110). The interface provides a cost-effective, low power, bi-directional, high-speed data transfer mechanism over a short-range "serial" type data link, which lends itself to implementation with miniature connectors and thin flexible cables which are especially useful in connecting display elements such as wearable micro-displays (104) to portable computers (100) and wireless communication devices (102).

WO 2004/110021 A3

**Declarations under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW. ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

**Published:**

— with international search report  
 — before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:

31 March 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US2004/017579

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L29/06 H04L12/64 G06F3/14

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04J H04L G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 03/023587 A (QUALCOMM INC) 20 March 2003 (2003-03-20)	1-48
X	paragraph '0237! - paragraph '0242!; figure 49	49-58
X	paragraph '0207! - paragraph '0210!; figures 38,39	59-65
X	paragraph '0251! - paragraph '0265!; figures 50,51	66
Y	----- -/--	68-70

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*Z\* document member of the same patent family

Date of the actual completion of the international search

14 January 2005

Date of mailing of the international search report

25.01.05

Name and mailing address of the ISA

European Patent Office, P.B. 5619 Patentlaan 2  
NL - 2280 HM Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Jurca, A

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US2004/017579

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	"Transmission and Multiplexing (TM); High bit rate Digital Subscriber Line (HDSL) transmission system on metallic local lines; HDSL core specification and applications for 2 048 kbit/s based access digital sections; ETR 152" ETSI STANDARDS, EUROPEAN TELECOMMUNICATIONS STANDARDS INSTITUTE, SOPHIA-ANTIPO, FR, vol. TM-3;TM-6, no. Third Edition, December 1996 (1996-12), XP014011258 ISSN: 0000-0001 page 59 figure 15	49,50,57
X	US 5 862 160 A (IRVIN DAVID R ET AL) 19 January 1999 (1999-01-19) column 3, line 38 - column 7, line 53	67
Y		68-70

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US2004/017579

## Box II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

☐ The additional search fees were accompanied by the applicant's protest.

☒ No protest accompanied the payment of additional search fees.



## FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-48

Claims 1-48 are directed to transferring high rate digital presentation data between a host device and a client device. This is done by using a communication protocol. However claims 1-48 present no special technical features in the sense of Rule 13.2 PCT, since they are not novel over the disclosure of the closest prior art document D1.

---

2. claims: 26 and 59-65

Claims 26 and 59-65 are directed to faster link wake up procedure. This is done by using current clock rate, instead of falling back to the minimum 1 Mbps clock rate, as disclosed in D1 (special technical features disclosed in claim 59).

---

3. claim: 26 and 66

Claims 26 and 66 are directed to improving the reliability of the reverse link between the host and the client. This is done by sampling the data line on both rising and falling edges during the reverse timing packet (special technical features of claim 66 over the disclosure of D1).

---

4. claims: 49-58

Claims 49-58 are directed to synchronization in an electronic system. This is done by using a state machine having at least one Acquiring synchronization state and at least two In-Sync synchronization states.

---

5. claims: 67-70

Claims 67-70 are directed to transferring error codes in a communication system. This is done by overwriting CRC value of a packet in case of detecting an error.

---

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.

PCT/US2004/017579

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 03023587	A	20-03-2003	US 2003033417 A1	13-02-2003
			CA 2459941 A1	20-03-2003
			EP 1423778 A2	02-06-2004
			WO 03023587 A2	20-03-2003
			US 2004199652 A1	07-10-2004
US 5862160	A	19-01-1999	AU 5623098 A	31-07-1998
			BR 9713794 A	01-02-2000
			CA 2276153 A1	09-07-1998
			CN 1249091 A , B	29-03-2000
			EP 0950300 A1	20-10-1999
			JP 2001507893 T	12-06-2001
			WO 9829978 A1	09-07-1998